

Douglas County Surveyor's Record of
Government Corners Renewed

T 23

T. S.

R 8

R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 97301

129

Closing Corner for Secs. 24 and 25 only of T.23-9
Found - 1" x 30" iron pipe with 1967 County Surveyors brass cap lying
loose on top of ground. Ren. #67

Original monument not found.

Note: As Tracy found the original BTs to be reference by slope
distances, we determine a point using record bearing and slope distances
to the face of the original bearing trees. Holding record distances as
horizontal does not agree well with bearings, nor does holding slope
distances to the center of the root crown.

From the point determined the original bearing trees were found as follows

A 48" now 65" fir, bark scribed "T2 S R W 25 BT" bears
S.73 1/2°W., 38.3 ft. slope distance to face (horizontal
dist. = 34.0 ft. to face and 37.2 ft. to center of root
crown)

A 12" now 28" cedar with rescribing "BT" visible in partially
healed blaze bear- N.50°W., 20.5 ft. slope dist. to face.
(horizontal dist. = 14.0 ft. to face and 15.2 ft. to center of
root crown which agrees with distance per Ren. #67)

BT from Ren. #67 - A 5" now 8" dia. trunk of a 4 trunk maple
with well healed blaze bears S.79 1/2°W., 11.3 ft. horizontal
to center of scribed trunk. (Rec. S.74 1/2°W., 11.4 ft.)
Center of root crown is 12.2 ft.

Set - At point previously described, we dig down to bed rock and
chisel an "+" 7 in. x 7 in. in bedrock. Over this point in
a mound of stone and soil, we set the 1" x 30" iron pipe with
brass cap mkd. "County Surveyors Office T23S R9W S24 S25
R8W C.C. 1967". We add the marks "RESET 1984" to brass cap.

New BT - A 10" dia. hemlock double blazed and scribed "X CS BT" bears
S.66°E., 17.2 ft. to center of root crown.

This corner lies on a steep easterly slope.

1/25/84

Closing Corner for Sec. 6, in T.24-7; & Sec. 1, in T.24-8.

130

Found - I.P. w/properly marked B.C., protruding 12" per Ren. #79 in T.24-7.
I.P. w/properly marked B.C., protruding 8". Ren. #113.

BTs - 8", now 17" W. Fir w/well healed dbl. blaze bears East, 32.8-ft.
6", now 11" D. Fir w/well healed single blaze bears S.53°W., 74.2-ft.
These two BTs are as per Ren. #34. (DCSO AM).

12" fir w/partially healed dbl. blaze with visible scribing:
"T24" bears S62°W., 64.1-ft.

8" fir w/partially healed dbl. blaze, with visible scribing:
"BT" bears S.55°E., 11.2-ft.

These two BTs are as per Ren. #113. (RPLS #1039).

Set - The letters "AM" were added to the DCSO Closing Corner Cap.

Note - See file for sketches.

3/84

Section corner for Secs. 24 and 25; and Secs. 19 & 30 of T.23-7

131

Found - BLM 1964 2 1/2" iron pipe with brass cap, properly marked,
protruding 6" above ground.

18" now a 28" diam., D. fir with a single healed blaze, bears
N.6°E., 268.0 ft. (1964 dependent resurvey)

37" now a 42" diam. D. fir with a single healed blaze bears
N.39°W., 376.9 ft. (1964 resurvey)

A steel fence post 6 ft. long, set 2 ft. in the ground is along
side east edge of iron pipe. (1964 resurvey)

A 12" rebar 5 ft. long, set 2 ft. in the ground, is along side
west edge of iron pipe. (probably 1979 resurvey)

New BTs - 4" diam., D. fir, double blazed and scribed "X BT" bears S.46°W.,
20.6 ft.

4" diam., D. fir, double blazed and scribed "X BT" bears S.86°E.,
81.5 ft.

Note: Corner lies on a gentle north slope. Map # M 90 - 38A shows NE
and NW BT as not found.

5/30/84

Larry E. Monrean
Deputy, Doug. Co.
Surveyors Office
R.W. Smith and
S.J. Flause,
Witnesses.
Jan. 25, 1984
C.S. 62/16

Larry (Ed) Monrean
RLS #1830
Deputy, Doug. County
Surveyors Office
Randall Smith,
Stephen Flause
March 5, 1984
C.S. 62/16

Larry Monrean, Deputy
Douglas Co. Surveyors
Office
Party Chief: Randall
Smith
Witness: Stephen J.
Flause
May 30, 1984
C.S. 62/18