

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 9 W. R.W.W.M.

J.W. Cole, C.S.  
Wit: Kenneth  
Peterson &  
Bill Judy  
Aug. 19, 1923  
S.S. 1013, 1216B

1  
 $\frac{1}{4}$  Corner N. Side of Section 19.  
Both bearing trees alive and standing, bearing scribe marks.  
Also an 18" Fir checks for position of corner & bears scribe  
marks  $\frac{1}{4}$  S".  
Set - Bar of Iron  $\frac{1}{2}$ " x 2" x 30" to perpetuate Corner.

SEE CS FILE  
4199  
1948  
NOTES  
21

H. T. Lewis,  
Eng. 722  
Dec. 27, 1933

2  
S. W. Corner of Section 16.  
At the corner of 16 & 17, I found both witness Trees, as described  
in the field notes, but N. W. Tree was dead.  
I therefore, set a Fir Post 4' long 4" diam., 18" in the ground,  
as there were no available trees to the N. W., I Marked:  
12" Hemlock, which bears S. 69° W. 20.0 ft., Mkd: T23S R9W S20 BT #722.

3  
Corner to Sections 20 and 28, S.E. Corner Section 20.  
At the corner of Sections 20 & 28, I found the N. W. Witness Tree  
in place. Also, the S. W. Tree, but it was a rotten snag.  
Set - 4' Cedar Post 4" diam., 18" in the ground, Mkd: S28 on the  
SE face and S20 on the NW face from which:  
6" Cedar bears N. 48° W. 27 ft., Mkd: T23S R9W S20 BT. #722.

4  
C. C. Sections 6 - 7.  
Found - Fir BT. N. 38 $\frac{1}{2}$ ° E. 16 lks.  
Set - 4" x 4" x 36" Fir Stake  
Blazed & Scribed New BT: 8" Fir S. 42° E. 28.1 ft. Mkd: CC S7 T23 R9W RE2741BT.

CORNER NO. 48

5  
Section Corner to Secs. 16 and 20 only.  
Found - 4 Orig. BT's.: 16" Fir N. 10° E., 33 lks. (stump)  
20" Fir S. 88° E. 26 lks.  
48" Fir S. 60° W. 16 lks.  
20" Fir N. 70° W. 9 lks.  
N. E. and S. E. BT's. do not apply, having been obliterated in re-survey  
of sections 16 and 21, but are still in good shape.  
Set - 4" x 4" x 24" Hemlock Stake for Corner.  
New BT's: 24" Fir S. 13° W. 35 ft., Mkd: S20 T23S R9W BT.  
(Nailed copper tags to stake & H. BT., labeled RE 2741)

6  
E  $\frac{1}{4}$  Corner Section 20, T23-9W.  
Found - 60" Fir S. 5° W. 43 lks., evidently intended for 60" Cherry  
recorded in gov't. field notes. Very old bark blaze,  
faces properly. Top rescribed, but BT. scribe, very old.  
Topography fits very well.  
Set - 1" Iron Pipe for Corner. (SAME AS 9A)

7  
 $\frac{1}{4}$  Corner to Sections 19 and 20.  
Location determined by testimony of A. O. Gustafson, who has seen  
Original Stake in place.  
Set - 1" Iron Pipe for Corner, blazed and scribed BT's:  
10" Alder, S. 60° E., 60.5 feet.  
12" Alder, N. 50° E., 25.0 feet.  
No suitable trees in Section 19.

Arthur R. Evans  
Wit: J. I. Clinton & Elvin DeGnath  
February 25, 1952  
C. 5 41-6