

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

Wit. Cor. to  $\frac{1}{4}$  Sec. Cor. to Sections 27 and 26.

Found - 29" D.Fir S.  $6^{\circ}$  E. 73.9 ft., prev. opened, good scribing visible " $\frac{1}{4}$  S26 BT".

Did not find N. W. BT.

Note - Corner position falls on bare rock face, very steep slope, impossible to set corner here.

Set - Wit. Cor. S. 75.0 ft. of  $\frac{1}{4}$  Cor. - Drove  $\frac{3}{4}$ " Rod at Wit. Cor.

New BT's: 27" D.Fir N.  $41^{\circ}$  W. 11.7 ft. Mkd: WC  $\frac{1}{4}$  S27 CS BT.

BT. for  $\frac{1}{4}$  Cor. - 29" D.Fir bears N.  $85^{\circ}$  E. 7.8 ft. from Wit. Corner.

7A

#31

$\frac{1}{4}$  Corner to Sections 22 and 23.

Found  $\frac{3}{4}$  Mound of Rocks - One Rock marked "4".

36" Fir N.  $10^{\circ}$  E. 9.2 ft., from face, very plain axe scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964

T23S R9W  $\frac{1}{4}$  S 22/S 23

Both BT's. are in good condition, scars plain. Did not rescribe.

Note - Corner is approx. 50 ft. North of ridge top and 50 feet West of Ridge Top.

7-B

#30

Section Corner to Secs. 22 - 23 - 26 - 27.

Found - 42" Fir N.  $52^{\circ}$  W. 6.6 ft., prev. opened, good scribing "S22" visible on old face.

48" Red Cedar N.  $2\frac{1}{2}^{\circ}$  E. 46.9 ft., old face apparently rotted away.

Dead Fir Snag S.  $32^{\circ}$  W. 33.9 ft., no scars or old face visible.

The S. E. tree is uprooted & has slid downhill from where it stood. Large Stump Hole visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R9W S 22/S 23 Office, 1964 S 27/S 26

New BT's: 7" Hemlock S.  $84^{\circ}$  W. 25.3 ft. Mkd: T23S R9W S27 CS BT.

9" Hemlock S.  $76^{\circ}$  E. 26.2 ft. Mkd: T23S R9W S26 CS BT.

The N. E. & N. W. Orig. BT's. are still alive and in good condition.

7-C

Oct. 19, 1964

$\frac{1}{4}$  Corner Section 6 only, T23S-R8W. (E. Bdry. R9W)

Found - Orig. 8", now 12" Hemlock, very badly decayed stub, N.  $45^{\circ}$  W.

17.8 ft. Open & find "BT" reverse scribe & " $\frac{1}{4}$ " reverse scribe in decayed log on ground.

Orig. 20", now 34" Fir, S.  $1^{\circ}$  E. (record S.  $10^{\circ}$  E.) 17.8 ft., Alive, shows scars. Do not open.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S Office, 1967 R 9 W  $\frac{1}{4}$  S 6 R 8W

New BT: 9" Hemlock N.  $74\frac{1}{2}^{\circ}$  E. 10.8 ft. mkd.  $\frac{1}{4}$  S6 CS BT.

14" Hemlock N.  $47^{\circ}$  E. 19.0 ft. mkd.  $\frac{1}{4}$  S6 CS BT.

Note - This corner lies on top of small spur ridge course N.W.

Unrecorded  $1\frac{1}{2}$ " I.P. bears N.  $71^{\circ}$  W. 3.9 ft.

7-D

N.W. Corner Section 6 only, T23S-R8W.

Found - 1963 Co. Surv. Brass Cap. See Ren. #21, T23 S W. REN. 14, T23-9W

Orig. 40" Fir Stump N.  $40^{\circ}$  W. 27.1 ft., rescribed "T23S R8W S6 CS BT", decaying badly.

9", now 12" D.Fir, Alive, S.  $70^{\circ}$  E. 56.2 ft., scribe visible on nearly healed blaze.

New BT's: 4" D.Fir N.  $49^{\circ}$  E. 26.5 ft. mkd. "CS BT."

4" D.Fir N.  $21^{\circ}$  W. 115.5 ft. mkd. "CS BT".

Note - This corner lies approx. 300 ft. W. of top of spur ridge on W. Slope.

7-E

Milo E. Godfrey, Deputy  
Wm. Stoffel & Mike Stone  
October 1964  
D. S. File No. 53/84

Vernon "Ray" Tracy  
Jack Heritage & E. West  
February, 1967  
C. S. File No. 54/12