

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

25

Sec. Corner to Sections 18 and 19 only, T23-8W.

Found - Orig. 50", now 72" Fir, N. 15° E., 18.5 ft. Alive, shows good scar. We do not open.

Orig. 20", now 38" Eedar, S. 75° E. 44.2 ft. Alive, scribe visible on unhealed blaze.

Orig. 14", now 30" Cedar, N. 79° W. 9.9 ft., badly injured, no scribe found.

No trace of sandstone called for in original notes.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

R	T 23 S	R
9	S 18	8
W	S 19	W

New BT's: 8" Hemlock S. 59° E. 26.3 ft. mkd. T23S R8W S19 CS BT.

14" Hemlock N. 75° E. 30.8 ft. mkd. T23S R8W S18 CS BT.

Note - This corner lies on stee, S.W. slope, approx. 200 ft. N. of creek.

Vernon  
"Ray"  
Tracy  
&  
Crew  
1/31/67  
C.S.  
File  
No.  
54/12

Closing Corner to Sections 24 and 25, T23-9W.

Found - Orig. 48", now 63" D. Fir, S. 73½° W. 38.3 ft. (slope dist.) bark scribed "T23 9W BT".

Orig. 12", now 27" Cedar, N. 50° W. 20.5 ft. (slope dist.) good face.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

R	T 23 S	R
9	S 24	8
W	S 25	W

Rescribed: 27" Cedar N. 50° W. 15.2 ft. (level dist)

scribed T23S R9W S24 CC CS BT.

New BT's: 5" Maple S. 74½° W. 11.4 ft. mks. T23S R9W S25 CC CS BT.

Note - Corner lies 60' N. of creek, course E. & 125' W. of creek, course N. Corner set on top of 20' bluff.

2/1/67

Closing Corner to Sections 11 and 14, T23-8W.

Found - Orig. 10", now 42" Fir, N. 89° W. 30.4 ft. Alive, shows good scars. Rescribe: "T23S R8W S11 CC CS BT" in bark.

Orig. 20", now 40" Fir, S. 87½° E. 48.8 ft. Alive, shows good scars. Do not open.

Orig. 10", now 14" Dogwood, S. 20° W. 76.6 ft., now 7 ft. high stub., prev. opened & shows "S R8W BT" in very poor condition.

No trace of stone called for.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 23 S
S 11 CC
S 14

New BT's: 5" Maple S. 74° W. 26.4 ft. mkd. CC S14 CS BT.

7" D. Fir S. 54° E. 12.6 ft. mkd. CC S11 S14 CS BT.

Note - This corner lies on very steep, N. slope. Sec. Cor. of Secs. 12 & 13, T23-8W. bears N. 110.2 ft., see corner below.

Vernon "Ray" Tracy  
Jack Heritage & E. West  
February, 1967  
C. S. File No. 54/12

Sec. Cor. to Sections 12 and 13 only, T23-8W.

Found - Badly, broken Sandstone with 2 notches on 1 piece & possible notch on edge.

Orig. 30", now 50" Fir, S. 1° W., 16.5 ft. Alive, prev. opened & rehealed. Open & find axe notch & burned face with possible scribe. Ring count 100+ yrs., opened 70+ yrs. ago.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 23 S
S 12
S 13

New BT's: 12" Maple N. 78° E. 26.8 ft. mkd. T23S R8W S12 CS BT.

5" D. Fir S. 25½° E. 27.8 ft. mkd. S13 CS BT.

Note - This corner lies on small bench 110.2 ft., N. of Cl. Cor. above.

28

29

RE-RENEWED, SEE CORNER NO. #91