

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Oregon State Bd. of Forestry
Arnold G. Gibson
October & November, 1967
C. S. File No. 55/68

Oregon State Bd. of Forestry
Arnold G. Gibson
March 15, 1968
Map File M 36 - 32

Closing Corner common to Sections 6 and 7. 48
Original - Post, now missing, from which a:
6" Fir bears N.38 $\frac{1}{2}$ °E. 16 lks.; now 17", exposed scribe C.
30" Fir bears S.24°E. 133 lks.; now destroyed by road,
portions of the stump still in road berm.
Ridge, course S.50°W., bears South 2.08 chs.; in place.
Restoration by Arthur R. Evans, Feb., 1952. See Ren. #4.
4"x4"x36" Fir Stake, found in place, from which a:
8" Fir bears S.42°E. 281.1 ft.; now 9" Fir, in place, face
pitched over.

Restored: Set 1 $\frac{1}{2}$ " x36" galv. iron pipe with 3" br. cap mkd. "Ore.St.Bd.
of Forestry T23S S1 S6 S7 CC R10W R9W 1967 RS359", 34" in ground,
in place of Evans post, in mound of rock, and from which a:
24" Fir bears N.71°E. 20.0 ft. to face; scribed T23S R9W S6CC BTRS359.
Set - 4"x4"x72" white painted cedar post 1 ft. W. of corner pipe.
Ore.St. Forestry Dept. metal location poster on 24° Fir N.39°W. 9.5 ft.
(See Ren. #50 for True C. C. established - 3/15/68)

$\frac{1}{4}$ Corner to Section 6, South Side. 49
Original - Post, now missing, from which a:
60" Fir bears N.2 $\frac{1}{2}$ °W. 134 lks.; now 80" Fir, exposed scribe 1.
30" Fir bears S.50°E. 61 lks. ; now 3 ft. high stub, rotted.
Restored - Set 1 $\frac{1}{2}$ " x36" galv. iron pipe with 3" br. cap mkd. "Ore.St.Bd. of
Forestry $\frac{1}{4}$ S6 1967 RS359", 33" in ground, and from which a:
14" Fir bears N.1 $\frac{1}{4}$ °W. 50.5 ft. to face; scribed $\frac{1}{4}$ S6 BT RS359.
24" Fir bears N.40 $\frac{1}{4}$ °E. 52.4 ft. to face; scribed $\frac{1}{4}$ S6 BT.
Set - 4"x4"x72" white painted Cedar post 1 ft. SE of corner pipe.
Ore.St.Forestry Dept. metal location poster on 12" Alder S.61°W. 7.4 ft.

True Cl. Corner to Sections 6 and 7. 50
Set S.88°37'06" W. 40.24 ft. of C.C., See Ren. #48.
Set - Ore.St.Bd.of Forestry 1 $\frac{1}{2}$ "x36" Galv. I.P. with 3" Bronze Cap.
20" Fir N. 31 $\frac{1}{4}$ ° E. 17.7 ft. (RS359) Yellow Metal Location Poster.
20" Fir S. 82° E. 23.3 ft.
White Painted Cedar Post bears S. 10° E. 1.0 ft.

$\frac{1}{4}$ Corner Section 6 only, ~~West~~ ^{East} Side. 51
Set - Ore.St.Bd.of Forestry 1 $\frac{1}{2}$ "x36" Galv.I.P. with Bronze Cap.
24" Fir N. 62 3/4° W. 38.5 ft. ($\frac{1}{4}$ S6 BT)
21" Fir S. 80° E. 28.4 ft.
25" Fir S. 27 $\frac{1}{2}$ ° E. 31.4 ft. (RS359) Yellow Metal Location Poster.
Ridge top, crs. NE., south 65.0 ft.
White Painted Cedar Post bears N. E. 1.0 ft.

Closing Township Corner for Sections 1 and 6, T23 - ~~9W~~ ^{E10W}, reestablished. 52
Set - Ore.St.Bd. of Forestry 1 $\frac{1}{2}$ "x36" Galv. I.P. with Bronze Cap.
26" Fir N. 72 $\frac{1}{4}$ °E. 27.5 ft.
42" Fir S. 38 $\frac{1}{4}$ ° W. 12.8 ft. (RS359) Yellow Metal Location Poster.
46" Fir S. 60° E. 34.8 ft.
White Painted Cedar Post bears N.W. 1.0 ft.

Center $\frac{1}{4}$ Corner Section 6 established. 53
Set - Ore.St.Bd. of Forestry 1 $\frac{1}{2}$ " x 36" Galv. I.P. with Bronze Cap,
in mound of Rocks.
24" Fir S. 28 $\frac{1}{2}$ ° W. 16.4 ft. (RS359)
34" Fir N. 62 $\frac{1}{2}$ ° E. 37.7 ft.
34" Fir N. 68° W. 8.8 ft., Yellow Metal Location Poster.
White Painted Cedar Post bears N. W. 2.5 ft.

East $\frac{1}{4}$ Corner, Section 12. 54
Set - 2 $\frac{1}{2}$ " Brass Cap Mkd: SEEK, Inc.
T 23 S R 10 W
 $\frac{1}{4}$ S 12
1968
Bearing Trees: 30" Fir N. 18* W. 28.0 ft. mkd: $\frac{1}{4}$ S12.
36" Fir S. 78* W. 19.7 ft. mkd: $\frac{1}{4}$ S12.

By SEEK, Inc.
Wm.C. Stiles
Sept. 13, 1968
C.S. 55/89
Map M 36 - 42

Sept. 13, 1968