

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 23 S. T. S. R. 9 W. R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

65

Sec. Corner for Sec. 6 only, T23-8 and Secs. 1 and 12, T23-9  
Unrecorded evidence found. Corner not set.

Found = 2" sq. post out of ground with "location marker"  
tag "S B Merrick, D. Mower 1 | 8/15/57

12 |  
6' stump, uprooted and down hill from its orig.  
location, bears a tag mkd. "R<sub>D</sub> 5/2/67, Sadler  
Scribed stake, 2' north, H O Malac, 10-15-64.  
15" Fir with Forestry appraisal tag.

All BT's are gone or uprooted with no scribing.

10/19/73

66

Section corner, Secs. 1, 2, 11 and 12.

Unrecorded evidence fd. Corner not set.

Found - Wood post 4" x 3"; out of ground with scribing.

30" Fir, scribed "R P S1" tagged with BLM BT tag,  
reads as follows; Cor. is approx. 28 ft. S.8°E.,  
T23S R9W Sec. 2. Posted by P.A.S. Ap 71.

30" Fir, scribed "? MRP 2.2 ft. tagged with BLM  
BT tag which reads as follows; Cor. is approx.  
24.7 ft. N.25°W., T23S R9W Sec. 12 posted by  
PAS Apr. 71.

Also find-36" Fir stump, bears S.63°W., 30 ft. scribed "RP  
3 5". Could possibly be orig. SW BT. old scribe  
would be lost due to new scribing.

No sign of other bearing trees. See also C.S. File 54/60.

10/29/73

67

Section corner, Secs. 23, 24, 25, and 26.

Found - Orig. corner stone 20" x 9" x 6". one notch on east  
face and two notches on south face.

Orig. 30" now 50" Fir, bears N.24°W., 6.8 ft. (rec. 7.92 ft.)  
bark scribed "T23S R9W S23 BT"

A rotted stump, bears N.61°E., 12.7 ft. Bark is gone  
no scribing visible.

Other Orig. BT's recorded, not found.

Set - Brass cap at sec. cor. mkd.

COUNTY SURVEYORS T 23 S R 9 W  
OFFICE S 23 | S 24  
1973 S 26 | S 25

RE-RENEWED FREE CORNER NO. #105

New BT's - Note: All trees used for BT's tagged with BLM tags  
set 8/13/69 by TS & CS. no scribing found.

10" fir, bears S.47°E., 16.3 ft. (tag reads 15.0)  
scribed T23S R9W S25 BT.

16" fir, bears N.30°E., 18.9 ft. (tagged N.28°E, 18.0 ft.)  
scribed T23S R9W S24 CS BT.

30" fir, bears S.74°W., 21.3 ft. (tagged S.75°W.,  
20.4 ft.) scribed T23S R9W S26 CS BT.

Corner is 50' below and on the south side of a NE sloping spur.

11/1/73

68

1/4 Corner, Secs. 4 and 3.

Found - 50" Fir, now 7', bark scribed 1/4S 4 BT. bears S.33°W.  
8.6 ft.

48" Fir snag, bears S.35°E., 30.4 ft. No scribing,  
(bark gone)

Set - Brass cap mkd. COUNTY SURVEYORS T 23 S R 9 W

OFFICE 1/4  
1973 S 4 | S 3

New BT's - 18" hemlock, bears S.54°E., 8.2 ft. scribed T23S  
R9W S3 CS BT.

10/8/73

Larry E. Monrean, County Surveyors Office  
P.L. Earle  
October 1973  
C. S. 56/39