

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S T.S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

69

Section Corner, Secs. 3, 4, 9, 10.
Found - 36" now 48" Fir, N.10°E., 29.7 ft. scribed
T2 R9W
18" now 24" with double bottom fir, N.46°W., 13.2 ft.
Find no scribing.
30" Fir, S.89°W., 36.1 ft. Find blaze, no scribing.
30" Fir stump, S.8°E., No scribing.
Set - Brass Cap mkd. COUNTY SURVEYORS T 23 S R 9 W
OFFICE 4/3
1973 9/10
New BT's - 10" Hemlock, bears S.66°W., 50.4 ft. scribed
T23S R9W S9 CS BT.
8" Hemlock, bears S.18°E., 29.8 ft., scribed T23S
R9W S10 CS BT.
Rescribed 24" Fir, bears N.46°W., 13.2 ft. scribed
T23S R9W S4 CS BT.
Corner is approx. 200 ft. north on line, and on the NW side
of slope running SW. 10/9/73

L. E. Monrean
10/9/73
CS 56/39

RE-RECORDED
#82

70

1/4 Corner for Secs. 4 and 9.
Found - Orig. 6", now 16" D.Fir snag, rotten & showing
good scars on north & south faces. I open & find
scribing "1/4S" on north face & no scribing on
south face.
12" now 24" D.Fir snag, rotten, bears N.12°E., 4.3 ft.
(rec. 4.6 ft.) with partial scribe visible. I open
completely & find scribing "1/4 S3 BT". The "3" in
the scribe does not correspond with the field notes.
12" D.Fir snag, rotten, bears S.23°E., 5.0 ft. (rec.
S.28°E., 3.3 ft.) scribed area decayed & fallen.
From this location, an old line of blazes extends to the east
and a small pond is located as called for to the west. I remove
the deteriorating orig. corner tree and
Set - Brass cap mkd. COUNTY SURVEYORS T 23 S
OFFICE S 4
1974 1/4 S 9
New BT's - 26" D.Fir, bears S.39°E., 45.5 ft. scribed 1/4
S9 CS BT.
22" D.Fir, bears N.40°E., 70.4 ft. scribed 1/4
S4 CS BT.

Gary Langlitz, Surveyors Office
P. Earle
C.S. 56/43
1/24/74

71

Closing Corner for Secs. 28 and 33 only.
Found - Badly burned stump out of ground lying northeasterly. No
scribing visible. Orig. position S.11°E., 31.7 ft.
5/8" Iron rod 3.0 ft. high. Ren. No. 17
Fir stump, 29" diam. bearing & dist. to spike in notch,
N.15 1/2°E., 35.3 ft.
Fir stump, 4 ft. diam. bearing & dist. to spike in notch,
S.4 1/2°W. (rec. S.05°42'W.) 30.8 ft.
Set - Brass cap at closing corner mkd.
COUNTY SURVEYORS T 23 S R 9 W
OFFICE S 28
S 29 S 33 CC
No new BT's set (no living trees near) Corner lies approx. 150' west
of cutting line in sec. 29 & 100' south to foot of westerly ridge.
A dead fir, 28" dia. bears N.89°E., 47.9 ft. is approx. 150' high.
10/25/73
Marked brass cap with a "CC" on the closing section line between
Sec. 28 and Sec. 33, also set steel fencepost with survey marker sign
attached 1.0 ft. north of corner on this date. 3/20/74

Larry Monrean
P. Earle
C.S. 56/49
10/25/73

Gary Langlitz
P. Earle
C.S. 56/49
3/20/74

SDW 12