

Douglas County Surveyor's Record of
Government Corners Renewed

T.23 S. T.S. R.9 W, R.W.W.M.

KORF-CHAPMAN CO., EUGENE, ORE. 97401

Center 1/4 Corner to Section 20

Set - 2" X 42" I.P.
11" Fir, S.18E., 55.5' Scribed
11" Fir, N.37W., 48.9' Scribed

84

Nick Juliano
For Weyerhaeuser
Co.

May, 1979
M 77 - 50

1/4 Corner for Sections 2 and 3

I find no evidence of original 1/4 corner.

Set - 1 1/2" Brass cap with I.P. at proportionate distance

From which:

I scribe - 36" D.F., N.2°W., 13.6 ft.

42" D.F., S.43°E., 20.4 ft.

This corner is approx. 40 ft. east of a N-S draw and 100' south of dirt road.

85

Ronald E. Stuntzner
For: International

Paper &
Northwest
Exploration Co

March 14, 1980
M 82 - 57

3/14/80

RE-RENEWED, SEE CORNER NO. 86

1/4 Corner for Sections 2 and 3

I find no evidence of original 1/4 corner.

Set - 1 1/2" brass cap with iron pipe at proportionate distance.

From which:

I scribe - 36" D. Fir, N.27°E., 19.8 ft.

42" D. Fir, S.66°E., 25.7 ft.

30" D. Fir, N.62°W., 44.9 ft.

This corner is approx. 20 ft. East of a N-S draw and 100' south of dirt road.

(This 1/4 corner corrects and amends previous survey) Ren. #85)

86

Ronald Stuntzner

For: I.P. Paper
and Northwest Expl.

Sept. 10, 1980
M 85 - 31

*For OK 5/16
I.P. Tags
Added
C.S. 49/17*

Center 1/4 Corner for Section 18

Set - 2 1/2" brass cap on a 2 1/2" x 30" iron pipe extending 6" above ground.

New BTs- 14" fir bears S.60°W., 11.8 ft. (1981)

11" fir bears N.08°E., 6.8 ft. (1981)

Both BTs scribed C 1/4 S18 BT.

87

Robert W. Ward
For: Champion Inter-
national Corp.

Sept. Nov. 1981
M 89 - 63

Section corner for Secs. 18 and 19; and Secs. 13 & 24 of T.23-10

Found - 2 1/2" BLM brass cap on a 2 1/2" I.P. set in 1967.

8" myrtle bears N.69°E., 223.7 ft. (1967) scribed T23S R9W S18 BT.

8" dead, down ash (record maple) bears N.27°W., 427.7 ft. Scribing not found. (1967)

New BT- 11" Ash bears N.02°E., 81.3 ft. (1981) scribed T23S R9W S18 BT.

Nov/1981

88

1/4 Corner common to Sec. 19, & Sec. 24 of T.23-10.

Set - Oregon State Board of Forestry 1-1/2" x 36" Galv. I.P. with a 3" Bronze Cap, placed 34" in ground. (OSBF P/C 34" IG).

BTs - 20" hemlock bears N.46°W., 21.2-ft., RS.

24" hemlock bears S.10°E., 25.4-ft., YMLP.

Ren. #90/63

Ren. #90/63

BOs - WPCP bears N.57°E., 1.8-ft. (4" x 4" x 72" white painted cedar post)

5/8" x 30" I.R. bears N.80°10'58"W., 23.71-ft.

9/29/81

Lloyd Smith

For: State of OR-
Dept. of Forestry

Sept. 29, 1981

M 89 - 40

89

Section corner for Sections 3 and 4; and Secs. 33 & 34 of T.22-9

Found - Iron fence post which had been placed, by me, along side corner monument in 1980. And five BTs listed below.

Set - Drove Douglas County Surveyor's 30" x 1" galv. I.P. with 1967 Brass cap which had been removed by International Paper Co. cutting crew, alongside the fence post. Ren. #38.

From Which:

34" D. fir stump, with IPCo tag, bears N.35°E., 23.5 ft.

6" burnt hemlock stob, with IPCo tag, bears S.29 1/2°E., 77.0 ft.

14" hemlock stump, with IPCo tag, bears S.14 1/4°W., 78.7 ft.

42" D. fir stump, with IPCo tag, bears S.27°W., 57.3 ft.

15" hemlock stump, scribing visible, with IPCo tag, bears N.01°W., 34.4 ft.

BTs in Sec 3 and 4 treated with pentachlorophenol and covered with galvanized metal.

90

W. Carey Weatherl

For: International
Paper Co.

August 1982

C.S. 58/276

8/82