

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 09 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Mark Smalley  
 For: Riverbend Resources  
 Oct. 1997  
 M 124-64

1/4 Corner Secs. 11 & 12 107

Set - 5/8"x 48" iron rod & aluminum cap, mkd: "LS 2354 1997"  
 10" Hemlock, S.16°E., 8.9', scribed "¼ S BT".  
 8" Fir, S.43°W., 6.3', scribed "¼ S11 BT".  
 12" Fir, N.14°W., 14.5', scribed "¼ S BT".  
 10" Fir, S.63°E., 10.9', scribed "¼ S BT".

---

1/4 Corner Secs. 1 & 12 108

Set - 5/8"x 48" iron rod & aluminum cap, mkd: "LS 2354 1997"  
 No BTs Available in clear cut.  
 5/8"x 48" iron rods with metal tags South 10' and East 10' for bearing objects.

---

Corner Secs. 1 & 12 109

Fd - 1980 Cadastral Brass Cap on Iron pipe  
 BTs - 8" Fir, S.37 3/4°W., 9.9', healed.  
 17" Hemlock, N.55 1/2°W., 58.1', healed.  
 New BTs -  
 14" D.Fir, N.32°E., 24.4', scribed "S 6 BT"  
 10" D.Fir, S.80°E., 15.8', scribed "S 6 BT"

---

Corner Secs. 6 & 7, T23-8 110

Fd - 1980 Cadastral Brass Cap on Iron pipe  
 BTs - 20" Hemlock S.72 1/2°E., 9.6', down  
 19" Hemlock N.37°E., 46.7', (46.9' - 1980) healed.  
 New BTs -  
 12" D.Fir, S.10°W., 23.3', scribed "S12 BT"  
 16" Hemlock S.26°E., 25.1', scribed "S7 BT"  
 Note - Steel post marking orig. corner bears, West 8.6', (9.6' - 1980)  
 BTs - 30" D.Fir stump, N.70°E., 42.2', OBT  
 52" D.Fir, N.2°W., 66.0', OBT.

---

East 1/4 Corner Sec. 12 111

Fd - 1980 Cadastral Brass Cap on Iron pipe.  
 BTs - 18" Fir, S.56 3/4°W., 33.0', healed.  
 21" Fir, N.42 3/4°W. 13.9', healed.  
 New BTs -  
 20" Fir, S.56°E., 45.1', scribed "¼ S12 BT"  
 22" Fir, N.24°E., 10.2', scribed "¼ S12 BT"

---

West 1/4 Corner Sec. 7, T23-8 112

Fd - 1980 Cadastral Brass Cap on Iron pipe.  
 BTs - 23" Fir, S.26°E., 21.3', (S.24°E., 21.1' - 1980) healed.  
 13" Fir, N.52°E., 20.8', (N.46°E., - 1980) healed.  
 New BTs -  
 12" Fir, S.28°W., 34.2', scribed "¼ S7 BT"  
 11" Fir, N.32°W., 21.1', scribed "¼ S7 BT"  
 Note - Steel post marking orig. corner bears, West 7.7' (7.9' - 1980)  
 Root hole bears S.62°W., 16.5', down fir" 48" alongside.