

Douglas County Surveyor's Record of
Government Corners Renewed

23 S. T. S. R 10 W. R. W. W. M.

Aug. 19th. 1923
J. W. Cole Co Surveyor.
Wit: Bill Judy
Luther Judy
Sig Ash.
H. Peterson.

N. E. CORNER OF SEC. 25 T. 23 S. R 10 W.
I found an old stake standing, properly marked, but the bearing trees were all down and the stump of Maple could still be found. I set an iron pipe 1" x 30" inches in the ground. NO TREES NEAR.

1

June 27th. 1930
F. C. Frear Co.
Roadmaster.
Wit: B. A. Lane
P. D. Wolford.

COR. NORTH SIDE SEC. 25 T. 23 S. R 10 W.
I found the Myrtle B.T. standing but dead from Myrtle ran South 43 lks. and found cedar stake 4" x 4" standing but entirely covered by silt. I drove an iron pipe 1" x 36" for corner did not mark new trees.
On May 13th. 1932, I marked for this corner the following Trees:
A 28" Myrtle bears N. 58 3/4° W. 36.9 feet, A Myrtle 28" diam., bears N. 32° E. 61.0 feet
Signed F. C. Frear, Co. Roadmstr

2

A. R. Evans
Wit: J. E. Clinton
P. Duckett
Feb. 1952
C. S. 41-6

SEC. COR. SECS. 12 & 13.
Corner in the center of the Co. Road. Drove 1" x 34" iron bar, from which:
A 60" Fir bears N. 67 1/2° W. 17.0 feet, Old B. T.
A 12" Fir, bears S. 33 1/2° E. 38.4 feet New B. T.
A 8" Fir, bears S. 17° E. 20.5 feet Old B. T. Probably cut on account of road work.

3

SEC. COR. SECS. 1 and 12
Found O.B.T., Laurel N 20°W 45 lks. set 4" x 4" x 36" Fir stake. Blazed and scribed new B.T.s
24" Fir, S 72°W, 21.4 feet, mkd. S-12, T 23 S R 10, R.E. 2741, B.T.
12" Fir, N 10°W, 31.4 feet, " S-1, T 23, R 10, B.T.
FOUND SEE M 36-42

4

SEC. COR. SECS. 1 and 12
Found O.B.T., Laurel, N 10°W, 25 lks. Marked cross on rock in place for corner. Blazed and scribed N.B.T.s.
14" Fir, S 25°W, 22.0 feet, mkd. 1/4 S 12, R.E. 2741 B.T.
24" Fir, N 60°E, 27.0 feet, " 1/4 S 1, R.E. 2741 B.T.
NOT FOUND - SEE M 36-42
RENEWED (PROPORTION)

5

Theodore S. Ellingsen
November 18, 1954
Survey for Menasha Wooden Ware Corp.
C. S. File 41/327.

1/4 sec. corner sections 36, T23S, R10W., and 31, T23S, R9W.
Set a 3/4 inch iron pipe.
Scribe one new bearing tree to replace one which is now rotten -
A fir 41 inches in diameter, bears N.19°E., a distance of 30 feet marked 1/4 - S 31 - BT - 329.

6

Center 1/4 sec. corner section 36.
At the intersection of the two corrected center lines set a 3/4 inch iron pipe, from which:
An alder 12 inches in diam., bears N.72°E., a distance of 1.5 ft., marked C - S36 - BT - 329.
A fir 48 inches in diam., bears west, a distance of 37.7 feet, marked C - S36 - BT - 329.

7