

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 10 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

Arnold G. Gibson
By Elbert Driver
Wit: Bob Banks & Ron Witham
Sept. 9, 1957
C. S. File No. 42/331

16" Fir bears S.44°W. 13.5 ft., scribed RS 359.
40" Fir (orig.) bears S.88°W. 30.4 ft., scribed BT in wood.
Oregon State Board of Forestry metal location poster on 16" Fir BT.

13

1/4 Section Corner common to Secs. 1 & 2.
Original: Post (now missing) from which a:
24" Fir bears N.33°E. 56 lks., now 50", Face grown over,
bark scribed T23S RLOW BT & 1/4 S 1, 2 visible.
6" Laurel bears West 20 lks., now missing.
Retracement August 8, 1906 by Levi Walker.
Post (found in place, scribed 1/4 S1 2 on N & T23S RLOW on
S visible) from which a:
12" Fir bears N.36°W. 1186 lks., now 40", face covered,
(bearing is N.22°W.)
Restored: Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked
"OREGON STATE BOARD OF FORESTRY 1/4 S1 S2 1957 RS 359," 33 in.
in ground, and from which a:
20" Fir bears S.1°E. 11.9 ft., scribed RS 359.
Oregon State Board of Forestry metal location poster on 13" Fir N.39°E.
4.3 ft.

Arnold G. Gibson
Elbert Driver, transitman.
Wit. D. Timmons, R. Witham
R. Huff.
Feb. 7, 1958
C. S. File No. 42/331

1/4 Corner Common to Sections 2 and 3.
Original: Post (now missing, found rotted stake point) from which a:
30" Fir bears N.36°E. 24 lks.; now 38", scribe B
exposed, remainder unexposed.
30" Fir bears S.48°W. 25 lks.; now 30" x 2' rotted stub.
Restored: Set 1 1/2" x 36" galvzd iron pipe with 3" bronze cap marked
"OREGON STATE BOARD OF FORESTRY 1/4 S2 S3 1958 RS359,"
33 inches in ground, and from which a:
40" Fir bears S.68°E. 30.2 ft.; scribed RS359.
40" Fir bears S.51 1/4°W. 31.8 ft.; scribed 1/4 S3 BT.
Oregon State Board of Forestry metal location poster on
40" Fir BT SW.

14

Closing Corner between Secs. 33 & 34.
4"x 5" Hemlock Post, replacing post set by Levi Walker, contract 763,
.436.9 ft. East of closing corner for Sec.s 3 & 4, set by Gesner
& Worrick.
Found decayed Post & B.T.'s:
30" Fir N. 6°E. 19 ft. - Old B.T.'s
16" Fir N.73°W. 43 ft. -
New B.T.'s.: 24" Fir N.10°W. 15 ft.
18" Fir S.62°W. 22 ft.

15

1/4 Section Corner to Sections 33 & 34.
Replace Post 3"x 3" Hemlock Post 24" above ground mtd.
1/4 Sec. 33 on E. Face & 34 on W.
Original B.T.'s. standing:
24" Hemlock S.69°E. 26 ft.
36" Fir N.74°W. 34 ft.

16

Corner Sections 28|27
33|34
Fir Post 3" Sq., 3 ft. long.
24" Fir N.26°E. 16.5 ft.
18" Fir S.52°E. 21 ft.
20" Fir S.57°W. 55 ft.
65 ft. North to Loon Lake Road.

17

1/4 Section Corner to Sections 27 & 34.
Old Corner Post & Original B.T.'s located:
18" Fir N.59°W. 12.5 ft. - Original
16" Fir S.53°E. 16 ft. -
Replace Post with 3" x 3" Hemlock.

18

OREGON STATE BOARD OF FORESTRY
Dated 1933
C. S. File No. 49/80 - Filed 4/24/58