

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 10 R. W. W. M.

FOX-CHAPMAN CO., EUGENE, ORE. 97196

32 (cont.)

edge of road.
West shore of Loon lake bears S.89°44'E. 167.0 ft.

33

Witness Cor. for Center $\frac{1}{4}$ Cor. for Sec. 2 (on East side of Loon Lake)
Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON
STATE BOARD OF FORESTRY WC C $\frac{1}{4}$ S2 381.9 ft. 1958 RS359," 33in.
in ground, in mound of stone, and from which a:
81" Fir bears N.39°E. 9.6 ft.; scribed X BT RS359.
21" Fir bears S.46 $\frac{1}{2}$ °W.29.0 ft.; scribed X BT.
Set 4 x 4 x 72" white painted Cedar post 1.5 ft. SE of pipe.
Oregon State Board of Forestry metal location poster on 15" Hemlock
S3E 12.2 ft.
Also poster on 4 x 4 x 72" white painted Cedar post 243.2 ft. S.89°
44'E. on East bank county road.
East shore of Loon Lake bears N.89°44'W. 63.0 ft.

Oregon St. Board of Forestry
Arnold G. Gibson
E. Driver
April 4, 1958
C.S. File #42/353
Map File M 10 - 19

North $\frac{1}{4}$ Section Corner to Section 11.

34

No positive identification of Orig. BT's. found.
See C. S. File No. for determining position of this Cor.
Set Brass Cap Mkd: County Surveyor's Office, 1958,
N. $\frac{1}{4}$ S11 T23S R10W.
New BT's: 13" Hemlock bears S.85°W. 22.3 ft. scribed $\frac{1}{4}$ S11 CS BT.
7" Hemlock bears S.68 $\frac{1}{2}$ °E. 40.7 ft. scribed $\frac{1}{4}$ S11 CS BT.
Feb. 3, 1958

Section Corner to Sections 2, 3, 10, & 11.

35

Found - Orig. 4", now 14" Fir N.25°W. 18.5 ft., I open & find good
scribing " 3".
Also find 30" Fir that checks bearing & Distance for
Original S. W. BT.
Set Brass Cap Mkd: County Surveyor's Office, 1958

S 3 S 2	T23S R10W
S10 S11	

New BT's: 10" R.Fir N.49°E. 16.5 ft. scribed S 2 T23S R10W CS BT.
10" R.Fir N.80°W. 16.8 ft. scribed S 3 T23S R10W CS BT.
30" R.Fir S.50°W. 14.3 ft. scribed S10 T23S R10W CS BT.
11" Myrtle S.58 $\frac{1}{2}$ °E. 40.9 ft. scribed S11 T23S R10W CS BT.
Feb. 3, 1958

James W. Byron, Deputy County Surveyor
Milo Godfrey
S. Bilow
For "West Shore Lodges" Subdivision" Mr. Rose & Mr. Lee.
Feb. - May, 1958
C.S. File No. 49/90 M8-72

West $\frac{1}{4}$ Section Corner to Section 11.

36

Found - Orig. 20", now 56" Fir S.47 $\frac{1}{4}$ °W., record 79.9 ft. I find
should be 83.9 ft., open & find good scribing " 3".
Note: This BT. also used as BT. for E. $\frac{1}{4}$ Corner S10.
Clump of Alders that checks bearing & distance to record
Madrone. A down Alder has small Section of apparent
old face, no scribing visible.
Note: Bearing & distance between $\frac{1}{4}$ Corners check record.
Set Brass Cap at Corner Mkd: W $\frac{1}{4}$ S11 T23S R10W County Surveyor's
Office, 1958
New BT's: 28" R.Fir S.29°E. 123.0 ft. scribed $\frac{1}{4}$ S11 CS BT.
35" R.Fir N.53°E. 62.4 ft. scribed $\frac{1}{4}$ S11 CS BT.
Feb. 3, 1958

East $\frac{1}{4}$ Section Corner to Section 10.

37

Found - Both Orig. BT's. & bottom Section of Wood Stake at Corner.
Also check bearing & distance to large Rotted Snag recorded
as line Tree 33.0 ft. North of Corner. I do not open
either BT., show good scars.
The S.W. BT., now 56" Fir. This BT. same tree used for
W. $\frac{1}{4}$ Corner Sec. 10.
New BT's: 20" R.Fir bears N.11°W. 46.7 ft. scribed $\frac{1}{4}$ S10 CS BT.
18" R.Fir bears S.82 $\frac{1}{2}$ °W. 41.8ft. scribed $\frac{1}{4}$ S10 CS BT.
Set Brass Cap Mkd: E $\frac{1}{4}$ S10 T23S R10W County Surveyor's Office, 1958