

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 10 R. W. W. M.

1044-CHAPMAN CO. EUGENE, ORE. 97106

James W. Hyron, Deputy County Surveyor  
Milo Godfrey  
S. A. Bilow  
For Mr. Rose & Mr. Lee "West Shore Lodges"  
Feb. - May, 1958  
C. S. File No. 49/90

1/4 Section Corner to Sections 11 & 14. 38  
Found - Both BT's. scribed 1906 resurvey.  
I open N.W. BT. & find good scribing "BT".  
The S.W. BT. shows good scar, I do not open. Both now 13".  
Find bottom section of Orig. corner stake under surface.  
Set Brass Cap at Corner Mkd: 1/4 S11 T23S R10W County Surveyor's  
S14 Office, 1958.  
New BT: 14" R. Fir bears North 19.8' scribed 1/4 S11 CS BT.

M. C. Section 11 & 12 on South Shore of Loon Lake. 39  
Found - 40", now 44" Fir S.48°W. 75.4 ft., shows good scar. I do  
not open.  
Find, now 24" Alder N.37°E. 6.7 ft., good bark scribing,  
Cor 11 12 T23S R10W.  
Set Brass Cap at Cor. Mkd: M.C. S11/S12 T23S R10W County Surveyor's  
Office, 1958  
New BT: 13" Cedar bears 32.2 ft. S.41°E. scribed M.C. S12 CS BT.  
Note: I also find 4"x 4" scribed stake at corner vertical but  
covered with soil. Rev. # 28

Jan. 23, 1958

1/4 Section Corner to Sections 11 & 12. 40  
Found - 4" x 4" Stake at Corner & Orig. Fir, now 39", has openface,  
some scribing visible. I bark scribe this BT. Rev. # 22  
Set Brass Cap at Cor. Mkd: 1/4 S11/S12 T23S R10W County Surveyor's  
Office, 1958  
New BT: 10" Hemlock bears S.1 1/2°E. 19.7 ft. scribed 1/4 S12 CS BT.

Center 1/4 Corner to Section 11. 41  
Set 2" Iron Pipe 6" under for Initial Point & Center 1/4 Corner to  
Section T23S R10W.  
BT: 16" R. Fir bears N.73°W. 143.3 ft. scribed C 1/4 S11 CS BT.  
Bearing Object: N. 5°W. 20.0 ft., Chisled on Top of 5'x 5'x 7' Rock  
with B.O. chisled on South Face Near Top.

1/4 Section Corner on the East Boundary of Section 13. 42  
Search for trees & due East 80 lks. find the Maple called for in  
original field notes. Set at tree & run N.16°W. & search for  
original corner Stake. Find No evidence of stake or of Fir B.T.  
called for in field notes.  
Set Fir Post 4" x 4" x 4', 2 ft. in ground mkd: C.S. on North Side,  
S18 on East Side & S13 on West Side.  
Search North for old evidence of line, find numerous blazes.  
Checking location of stake as being on original line.  
Line of blazes also corresponds with line of old fence across  
bottom lands and shows beyond a doubt that the old accepted  
property line had been very closely maintained on original  
survey line for a long period of time.

Section Corner Common to Secs. 27, 28, 33, & 34. 43  
Orig. - Post (now missing) from which a: See # 17 # 116  
20" Fir bears N26E 25 lks.; now 27" uproot, face grown over.  
18" Fir bears S52E 32 lks.; now 20" uproot, face grown over.  
14" Fir bears S57W 84 lks.; now 24", orig. axe work & portion  
of scribe visible.  
8" Fir bears N79W 124 lks.; now missing.  
Restored - Set 1 1/2" x 36" gal. I.P. with 3" Bronze Cap Mkd: "OREGON STATE  
BOARD OF FORESTRY T23S R10W S27 S28 S33 S34 1958 RS359",  
33" in ground, and from which a:  
27" Fir bears N26E 45.9 ft.; scribed T23S R10W S27 BT RS359  
15" Fir bears N43W 37.8 ft.; scribed T23S R10W S28 BT.  
22" Fir bears S42E 23.4 ft.; scribed T23S R10W S34 BT.  
24" Fir bears S66W 74.1 ft.; scribed T23S R10W S33 BT.  
Ore. St. Bd. of Forestry metal location poster on 22" Fir BT.

F. J. Cole, Deputy  
For F.L. Newkirk  
Nov. 5, 1915  
Vol. 2, Page 227

Arnold G. Gibson  
OREGON ST. BD. OF FORESTRY  
By Elbert Driver  
Wit: R. Banks  
D. Timmons & D. McConnell  
January 1958  
C. S. File No. 42/422