

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 10 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

53

Closing Sec. Cor. common to Sections 3 and 4, T23S, R10W.
Orig. - Fir Post (now missing) from which a:
12" Hemlock bears S.59°E. 40 lks.; now down, scr. T2S R10 S3 vis.
7" Fir bears S.81°W. 22 lks.; rotten root crown in place.
Rest.-Set 1½" x 36" gal. I.P. with 3" br. cap mkd: "Ore.St.Bd. of Forestry S34 T22S R10W S4 S3 CC T23S R10W 1962 RS359", 30 inches in ground, from which a:
24" Fir bears S.80½°E. 23.1 ft.; scribed CC T23S R10W S3 BT RS359
20" Hemlock bears S.32°W. 32.5 ft.; scribed CC T23S R10W S4 BT.
Oreg. St. Forestry Dept. metal location poster on 24" Fir BT.
Set 4" x 4" x 72" White painted Cedar post 1.0 ft. SW of corner pipe.
Original Line blaze on 26" Hemlock, South 16.7 ft.

ORE. ST. BOARD OF FORESTRY
Arnold G. Gibson
D. L. McConnell, Transitionman
March 1962 - C.S. File No. 42/331

54

¼ Cor. Common to Section 34, (South Side) T22S, R10W.
Orig. 20" x 16" x 12" Stone (found in place, ¼ on N. Face, from which a:
8" Maple bears S.20°E. 30 lks.; now missing, group of small maple growing in place.
10" Fir bears N.52°W. 50 lks.; now rotten stump.
Restored: Set 4 X 4X 72" white painted Cedar post 2.0 ft. S.W. of corner stone, from which a:
28" Fir bears N.25½°W. 39.6 ft.; scribed ¼ S34 BT RS359.
18" Fir bears N.46°E. 54.8 ft.; scribed ¼ S34 BT.
Oregon St. Forestry Dept. metal location poster on 28" Fir BT.

55

Section Corner common to Sections 22 - 23 - 26 - 27.
Orig.- Fir Post, now missing, from which a:
6" Fir bears N.88°E. 28 lks.; now 8" uproot, point falls in slid out area, BT out of place downhill, scribes S23 BT visible.
6" Fir bears S.80°E. 10 lks.; now missing.
7" Fir bears S.70°W. 28 lks.; now 10" uproot with lower roots still in place, scribes T23 W S27 visible.
8" Fir bears N. 2°W. 23 lks.; now missing.
Restoration by Levi C. Walker, May 1906.
Fir Post, now missing, from which a: 8" Fir bears S.75°E. 22 lks., now missing.
Restored: Set 3" Br. cap mkd: "Ore.St.Bd. of Forestry T23S R10W S22 S23 S26 S27 1962 RS359", in mortar on a sandstone projection of which 3' x 4' x 2' is exposed, and from which a:
14" Maple bears N.40°E. 70.1 ft.; scribed T23S R10W S23 BT.
20" Fir Stump bears S.58½°W. 96.5 ft.; scribed T23SR10WS27BT RS359.
20' wide & 15' high sandstone face bears N.86°E. 13.4 ft.;
Mkd: X BO on westerly edge.
Ore. State Forestry Dept. metal location poster on 8" Maple N.87°E. 21.0 ft.
Set - 4" x 4" x 72" Wh. Painted Cedar Post 2.5 ft. N.W. of corner point.

Ore. St. Board of Forestry
Arnold G. Gibson
Donald L. McConnell
April 13, 1962 - C.S. File No. 42/422

FD. OK 9/83
C. MICHAEL
M 95-29

56

¼ Corner common to Sections 9 and 10.
Orig: Stone 24" x 20" x 20". (found crumbled stone in place, no marks visible) from which a:
12" Fir bears N.15°E. 15 lks.; now 37", face closed.
6" Fir bears N. 4°W. 24 lks.; now 13" snag, scribes S9 exposed.
Restored: Set 1½" x 36" gal. iron pipe with 3" br. cap mkd:
"Ore.St. Bd. of Forestry ¼ S9 S10 1962 RS359", 32" in ground, in mound of stone, and from which a:
24" Fir bears N.57½°W. 50.8 ft.; scribed ¼ S9 BT RS359.
Ore. St. Forestry Dept. metal location posted on Orig. 12" Fir BT.
Set 4" x 4" x 72" Wh. painted Cedar Post 2' NW of corner pipe.

Ore. St. Bd. of Forestry
Arnold G. Gibson
June 19, 1962
C.S. File No. 42/331