

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 10 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

C. S. File
No. 55/30

(continued)

Found - 30" fir N. 3°W. 42 lks., now fir snag, face visible--chopped open,
but rotted from inside--no scribing left.
Set - 3/4" x 4' Pipe, 3 1/2' into the ground for corner & re-referenced with
"W" nails and Weyerhaeuser tags: 10" hem N. 10° E. 19.8 ft.
24" hem N. 80° W. 23.4 ft.

7/31/73 - F.D. OK. V.R.T. C.S. 56/35

Section Corner to Sections 13 - 14 - 23 - 24.

Orig. - Post (now missing) from which a:

10" Hemlock bears N.85°E. 24 lks.; portions of root system remaining.
30" Fir bears S.25°E. 67 lks.; found bark scribes T23S R10W BT,
believed to be Elliott survey.

16" Hemlock bears S.45°W. 16 lks.; 30" windfall, face buried.

20" Hemlock bears N.30°W. 40 lks.; portions of rotted stump remng.

Set - 1 1/2" x 36 galv. iron pipe with 3" bronze cap mkd. "Ore.St.Bd.of Forestry

S13 S14 S23 S24 1967 RS 359", 34" in ground, from which a:

20" Hemlock bears N.29°W. 29.2 ft., to face; scribed T23S R10W S14

20" Hemlock bears S.39°E. 30.6 ft. to face; scribed T23S R10W S25

30" Cedar bears S.01°W. 25.1 ft. to face; scribed T23S R10W S23 BT.

6" Alder bears N.80°E. 13.3 ft.; bark scribed T23S R10W S13 BT.

Set 4"x4"x72" white painted Cedar post 1.0 ft. E. of corner pipe.

Ore.St.Forestry Dept. metal location poster on 30" Cedar S.01°W, 25.1 ft.

Elliott State boundary sign and line blazes on 30" Cedar.

Fnd. OK
by LLOYD SMITH
9-29-81
M 89-40
7/83 M 95-55
67

Oregon St. Forestry Dept.
Arnold G. Gibson
Wit: Kucera & Fitch
September 2, 1967
C. S. File No. 55/50

Section Corner to Sections 23 - 24 - 25 - 26.

Original - Post (found wood remains in orig. square post hole, also found
a scribed post and stub in ground, probably Elliott survey)
from which a:

24" Fir bears N. 60° E. 20 lks.; now a 12" x 8' stub. by L. SMITH

72" Fir bears S. 45° E. 5 lks.; now a 70" buckskin snag. 9-29-81
M 89-40

16" Hemlock bears N. 50° W. 43 lks.; now missing.

16" Fir bears S. 75° W. 11 lks.; now rotted to ground level.

Set - 1 1/2" x 36" galv. iron pipe with 3" br. cap mkd. "Ore.St.Board of Forestry
T23S R10W S23 S24 S25 S26, 1967 RS 359", 32 inches in ground,
and from which a:

13" Fir bears N. 26° E. 34.2 ft. to face; scribed T23S R10W S24 BT.

12" Fir bears S. 01° E. 22.8 ft. to face; scribed T23S R10W S25 BT.

8" Bowed fir bears S. 56° W. 19.4 ft. to face; scribed T23S R10W S26 BT.

15" Fir bears N. 64° W. 37.5 ft. to face; scribed T23S R10W S23 BT RS359.

36" Fir stump bears S. 71° W. 14.6 ft.; found portion of scribes BT -
probably Elliott Survey.

Set 4"x4"x72" white painted Cedar post 1.5 ft. W. of corner pipe.

Oregon State Forestry Dept. metal location poster on 72" snag
(orig. 72" Fir SE).

F.D. OK
L. SMITH
12-94 M 121-25

MICROFILM TO HERE 10/67 69

1/4 Corner to Sections 23 and 24.

Set - Ore. ST.Bd. of Forestry 1 1/2" x 36" I.P. with 3" Bronze Cap,
34" in ground.

27" Fir S. 30° E. 12.15 ft. (RS359) Yellow Metal Location Poster.

32" Fir S. 58° W. 30.5 ft.

Creek, course East, N. 0° 07' 19" W. 33.0 ft.

4"x4"x72" white painted cedar post S.25°E. 1.3 ft.

1/2" Iron Pipe N. 27° 55' W. 87.5 ft.

Fnd. OK
by LLOYD SMITH
9-29-81
M 89-40

Ore.St. Bd. of Forestry
Arnold G. Gibson
Wit. Kucera-Cook, Fitch-Bushmeier
August 29, 1967
C.S. File No. 55/50

S.1/16 Corner btwn. Sections 23 and 24, established.

Set - Ore.St.Bd.of Forestry 1 1/2" x 36" I.P. with 3" Bronze Cap,
34" in ground.

16" Fir N. 84 1/2° W. 41.4 ft. (RS359).

17" Fir S. 70° E. 27.7 ft., yellow metal location poster.

4"x4"x72" white painted cedar post East 1.0 feet.

SEE M 95-23
FOR 1/16 ESTABLISHED
BY CHAPMAN
7/83