

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 10 W, R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

82

Section Corner to Sections 35 & 36. (South Side) T22-10W.
Orig.-Post(found rotted & down, scribing visible), from which a: #114
36" Fir, now 54" Stump, bears N.75°W. 52 lks., scribed "2 S35" visible,
also, not orig., scribed T22SR10W BT & portion of 35 visible on
down log.
36" Fir bears S.82°W. 114 lks., now 63" stump, face unexposed.
36" Fir, now 56" uproot snag, N.82°E. 175 lks., face unexposed.
Set 1½"x36" galv. I.P. with 3" bronze cap mkd:"Ore.St.Bd.of Forestry
T22SR10WS35S36 T23SR10W S2 1958 RS359", 33" in ground from which a:
19" Hemlock bears N.45°E. 8.0 ft. scribed T22S R10W S36 BT".
20" Hemlock bears N.87°W. 40.2 ft. scribed T22S R10WS35 BT RS359".
Ore.St.Bd.of Forestry metal location poster on 19" Hemlock BT.

2/24/58

83

¼ Corner To Section 35 only, South Side, T22-10W.
Orig.-Post(now missing) from which a:
10" Fir bears N.80°E. 21 lks., now 23", scribed "45" visible, also
scribed "¼ S35 T22S R10W visible above original face.
16" Maple bears S.71°E. 13 lks., now 28" face unexposed.
Restored by Levi Walker, Aug 6, 1906.
Post, found rotted & down, position of scribed R10W visible.
Set 1½"x36" galv. I.P. with 3" bronze cap mkd:"Ore.St.Bd.of Forestry
¼ S35 1958 RS 359", 33" in ground, in mound of stone & from which:
34" Fir bears N.2½°W. 67.0 ft., scribed "¼ S35 BT RS359".
Ore.St.Bd. of Forestry metal location poster on Orig. 10" Fir BT.

2/24/58

84

Section Corner common to Sections 33 & 34 only, South Side, T22-10W.
Orig. 80"x20"x6" Stone(called 20"x6"x6" by Walker retracement in 1906)
found 4"x11"x12" stone with 3 notches on side, stoned rolled down-
hill, out of place, from which a:
40" Fir bears N.42°E. 12 lks.; 40" snag bears N.15°E. 12 lks.
8" Fir bears S.55°W. 17 lks.; now 30", face closed.
6" Alder bears N.42°W. 14 lks.; now missing
Also found uprooted 16" Tree mkd. originally for Cor. 33 & 34 with
scribing said to have been obliterated when above corner was set.
This tree is 2.14 chains E. of above corner, as called for in retracement
by L. C. Walker.
Set - 1½"x36" galv. I.P. with 3" br. cap mkd:"Ore.St.Bd.of Forestry
T22S R10W S33 S34 T23S R10W S4 1962 RS359", 30" in ground with
Orig.Stone alongside, in mound of stone, & from which a:
22" Fir bears N.62°W. 122.1 ft., scribed T22S R10W S33 BT.
16" Fir bears N.32°E. 17.8 ft., scribed T22S R10W S34 BT RS359.
Ore.St.Bd.of Forestry Dept. metal location poster on 16" Fir BT.
Set 4"x4"x72" white painted cedar post 1.0 ft. S.E. of corner pipe.

4/13/62

85

Section Corner for Section 31 (SW), T22-10W.
Orig. 20"x12"x8" Stone(in place, no marks visible) from which:
36" Fir bears N.73°E. 44 lks.; now 50" rotten snag 30' tall,
in place, no marks visible.
30" Fir bears S.24°W. 12 lks.; now 28" Rotten stub in place,
scribes S31 B visible.
40" Fir bears N.55°W. 29 lks.; now missing
Set 1-1/2"x36" OSBF I.P. with 3" bronze cap mkd:"Ore.St.Bd.of
Forestry T22S R10W S31 T23S R11W S1 1971 RS359, 35" in ground,
with orig. stone alongside, & from which a:
22" Fir bears N.42°E. 10.6 ft., to face; scribed
T22S R10W S31 BT RS359.
33" Fir bears N.9°W. 10.6 ft., to face; scribed
T22S R10W S31 BT.
Set 4"x4"x72" white painted cedar post 2.7 ft. S.1°W. of
corner pipe. Ore.St.Forestry Dept. metal location poster on
33" Fir BT.

11/22/71

Oregon State Board of Forestry
Arnold G. Gibson - Elbert Driver
C. S. File No. 42/341

MARCH 71

Oregon State Board of Forestry
Arnold G. Gibson
Charles W. Coe, Engineer
Eng. File 55/233

Duplicate of # 87