

Douglas County Surveyor's Record of  
Government Corners Renewed

23 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Oregon State Board of Forestry  
Arnold Gibson  
Charles W. Cook  
May 30, 1972  
C. S. File 55/233

86  
1/4 Corner common to Sections 10 and 15.  
Original Post (missing) from which a:  
10" Fir, bears S.07°E., 30 lks.; now 52" stump in place, face grown over.  
10" Fir, bears N.48°W., 85 lks.; now 42" stump in place, exposed scribes  
1/.  
Set - 1 1/2" x 36" galv. iron pipe with 3" bronze cap marked "OREGON STATE  
BOARD OF FORESTRY 1/4 S10 S15 1971 RS 359", 34" in ground, and from which a:  
19" Fir, bears S.56 1/2°E., 77.6 ft. to face; scribed 1/4 S15 BT RS 359.  
15" Fir, bears N.62°E., 62.5 ft. to face; scribed 1/4 S10 BT.  
Set - 4" x 4" x 72" white painted Cedar post 4.5 ft. N.45°W. of corner pipe.  
Oregon State Forestry Department metal location poster on 19" Fir BT  
S.56 1/2°E., 77.6 ft. 5/30/72

Oregon State Department of Forestry  
Arnold Gibson  
Jan. 21, 1972  
C.S. File 55/265  
M 45 - 3

87  
Section Corner for Section 31 only, (SW) T22-10.  
Original 20" x 12" x 8" stone (in place, no marks visible) from which a:  
36" Fir, bears N.73°E., 44 lks.; now 50" rotten snag 30' tall, in  
place, no marks visible.  
30" fir, bears S.24°W., 12 lks.; now 28" rotten stub in place, scribes  
S31 B visible.  
40" Fir, bears N.55°W., 29 lks.; now missing.  
Set - 1 1/2" x 36" gal. iron pipe with 3" bronze cap marked "OREGON STATE BOARD  
OF FORESTRY T22S R10W S31 T23S R11W S1 1971 RS 359", 35" in ground  
with original stone along side, and from which a:  
22" Fir, bears N.42°E., 10.6 ft. to face; scribed T22S R10W S31 BT 359.  
33" Fir, bears N.09°W., 10.6 ft. to face; scribed T22S R10W S31 BT.  
Set - 4" x 4" x 72" white painted Cedar post 2.7 ft. S.01°W., of corner pipe.  
Oregon State Forestry Department metal location poster on 33" Fir BT.  
11/22/71

Duplicate of #85

Oreg. St. Dept. of Forestry  
Arnold Gibson  
Charles W. Cook  
C.S. File 55/274  
Oct. 13, 1972

88  
Southeast Township Corner, Section 36 only, T.22-11.  
Set - 1 1/2" x 36" Iron pipe with 3" bronze cap, 34" in ground, from which a:  
36" Fir, N.22 1/2°W., 59.6 ft. with yellow metal location poster. (RS 359)  
21" Fir, N.63°W., 79.7 ft.  
Set - 4" x 4" x 72" white painted Cedar post S.25°E., 2.0 ft. 1/21/72

89  
Section Corner to Sections 10, 11 and 15.  
Orig.-Post(missing) from which a:  
24" Fir bears S.9°E. 85 lks.; now 63", in place,  
face burned away.  
24" Fir bears S.57°W. 63 lks.; now 46", in place, exposed  
scribes T and parts of backcast on burnt face.  
Restored: Set - 1 1/2" x 36" Galv. I.P. with 3" Br. Cap marked #100  
"Ore.St.Bd. of Forestry S10 S15 S11 T23S R10W 1972 RS359",  
34" in ground, and from which a:  
13" Fir bears S.26 1/2°W. 76.2 ft. to face; scribed T23S  
R10W S15 BT RS 359.  
56" Fir bears S.84°E. 40.1 ft. to face; scribed T23S R10W  
S11 BT.  
Set 4" x 4" x 72" White painted Cedar post 2.6 ft. S.64°E. of corner  
pipe. Ore.St.Forestry dept. metal location poster on  
56" Fir BT S.84°E. 40.1 ft.

Ore.St.Bd.  
Forestry  
A.Gibson  
Map File

90  
1/4 Corner to Sec. 24, T23-10 & Sec. 19, T23-9 #106  
Set - OSBF P/C 36" I.G.  
16" Hemlock S.57°E. 42.6 ft., YMLP (RS359)  
14" Hemlock N.22°W. 30.9 ft.  
WPCP N.84°E. 4.0 ft. - 6/29/72

91  
Center 1/4 Corner Section 24.  
Established - Set - OSBF P/C 36" I.G.  
76" Myrtle S.35°W. 11.5 ft. YMLP  
31" Myrtle S.66°W. 27.7 ft. YMLP (RS359)  
WPCP West 2.9 ft. WPCP N.89°19'E. 1155.45'W. Side of Road,  
E. Side Ash Valley School Lot. 6/29/72

RENEWED, SEE CORNER NO. #100  
RENEWED, SEE CORNER NO. #106  
RENEWED, SEE CORNER NO. #107