

Douglas County Surveyor's Record of
Government Corners Renewed

T 23

T. S.

R 10

R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97501

110

Center 1/4 Corner for Section 26
Set - 2 1/2" brass cap attached to a 2 1/2" x 30" galv. I.P. with
flared bottom and mkd: "T23S R10W C 1/4 S26 1984 RPLS 2004".
New BTs-16" cedar bears S.62°E., 17.8 ft. (1984 BT)
46" fir bears N.82°W., 46.0 ft. (1984 BT) scribed C 1/4 S26 BT.

111

1/4 Corner for Sections 26 and 27
Found - 24" fir stump. Opened face and found a scribed "T". Also found
rotted fir stump close to position of original NW BT (no
scribing found). Could not position from record distances.
The NE BT, being a flat pull of short distance, was held at
record bearing and distance to:
Set - 2 1/2" brass cap attached to a 2 1/2" x 30" I.P. with flared
bottom and mkd: "T23S R10W 1/4 S27 S26 1984 RPLS 2004".
Found - 24" fir stump bears N.65°E., 5.9 ft. (scribed "T" visible.
(1906 BT)
25" fir stump bears N.69°W., 25.9 ft. (1906 record N.65°W., 22.4')
New BTs-6" fir bears N.04°E., 25.6 ft. (1984 BT) scribed 1/4 S26 BT.
6" fir bears S.63°W., 21.8 ft. (1984 BT) scribed 1/4 S27 BT.

112

1/4 Corner for Sections 26 and 25 *FD OK 2/16 T. Hostetter 1126-31*
Found - 58" fir stump with bark scribed "BT" visible. I accept this as
the original 1879 fir bearing tree.
The original 12" maple is missing.
At record bearing and distance from the fir BT (stump) I Set:
A 2 1/2" brass cap attached to a 2 1/2" x 30" galv. I.P. with
flared bottom and mkd: "T23S R10W 1/4 S26 S25 1984 RPLS 2004".
Accessories:
58" fir stump bears due west, 46.2 ft. (1879 BT)
Section C 37" cedar stump bears N.67°E., 11.7 ft. (not of record) scribed
Found - 1/4 S26 W T22S S26 W
New BT's: 16" Fir bears N.12°E., 19.3 ft. (1984 BT) scribed 1/4 S25 BT.
18" fir bears N.82°W., 24.0 ft. scribed 1/4 S26 BT.
Note: Due to upcoming logging operations, I have removed and have in my
possession the piece of bark with the scribed "BT" visible. I will replace
it after operations are completed.

113

1/4 Corner for Section 36 Only. T22-10.
Set - A 5/8" x 30" iron rod and cap.
BT's - A 18" fir bears N 4°E, 38.1 ft. Scribed "1/4 S36 BT".
BT's - 18" fir bears N80°E, 38.5 ft. Scribed "1/4 S36 BT".
Note: Distances to 7" spike in side and center, bearings magnetic Var. 20°.

114

Section Corner for Section 35 & 36. T 22-10
Found - A Oregon State Board of Forestry brass cap "1958". Ren. #82
BT's - A 33" Hemlock bears N44°E., 9.0 ft. OSBF
60" fir stump bears S75W, 76.0 ft. 1894 BT
54" fir stump bears N75°W, 34.5 ft. 1894 BT
16" hemlock bears N66°W, 33.0 ft. 1970 BLM BT

115

Section Corner for Secs. 11, 12, 13 and 14
Remonumented corner from the remaining bearing tree: (Ren. #10)
Corner is 1 1/2" brass cap affixed to a 1 1/4" x 36" iron pipe driven 32" into
the ground. Cap is stamped "T23S R10W S11 S12 S13 S14 LS 2052 1990"
Bearing trees are:
47" (formerly 36") D. fir stump bears N.78°W., 21.7 ft. #117
27" Hemlock snag bears N.6°E., 39.4 ft.
37" D. fir stump bears S.16°W., 42.8 ft.
18" Maple bears S.7°E., 36.6 ft.

RE-NEWED CORNER NO. 117

8/8/90

Gregory K. Miller L.S. #2004
For: Champion International Corp.
June-October 1984
M 97 - 68 C.S. 58/146

Daniel Baker
For: International Paper
April 1987 M 104 -19
C.S.63/50

John Minor
Menasha Corp.
Aug. 1990
C.S. 63/104