

Government Corners Renewed

23 T. S. 10 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 31881

116

See also
M133-14

Douglas County
Surveyors Office
Stephen Flauser
R.W. Smith
July 23, 1992
C.S. 64/31

Sec. Cor. for 27, 28, 33 and 34
 Found - A 3" dia. bronze cap (mkd. by OSBF) on a 1½" I.D. Galv. I.P., firmly set, and protruding 6" from ground. Ren. #43
 No evidence of original BTs found, logging & road work in area has obliterated remains of windfalls & old stumps. Ren.#17
 A 27" Fir now a 3 ft. tall 48" dia. D.Fir stump with a fully healed single blaze bears N.26°E., 46.7 ft. dist. (Rec. N.26°E., 45.9 ft. this is a reasonable face measurement)(#43)
 A 15" Fir now an uprooted 7 ft. tall 22" DBH Fir stump with a fully healed single blaze, the root hole of which agrees well with the record bearing and distance N.43°W., 37.8 ft. (#4)
 22" Fir now a 2½ ft. tall 28" dia. D.Fir stump with the scribing "S R10W S" visible in the remains of a partially opened single blaze bears S.39°E., 24.4 ft. dist. (Record S.42°E., 23.4 ft., the dist. is a reasonable face measurement) Ren. No. 43
 No evidence of SW bearing tree is found, measurement falls in a road.
 An unrecorded reference is found, A rotted 2 ft. tall 6" dia. Chinguapin stump with a Weyerhaeuser location tag bears S.28°W., 12.8 ft. dist. (agrees w/Weyerhaeuser tag)
 New BTs - A 4" DBH D.Fir scribed "X BT" on a double blaze bears S.17½°E., 35.3 ft. distant.
 A 5" DBH Chinguapin scribed "X BT" on a double blaze bears S.26°W., 13.2 ft. dist.
 Monument is in a recent clearcut North of an older clearcut and between roadways as shown in sketch (in C.S. File). Monument is approx. 250 ft. ENE from large D.Fir snag wildlife tree.

7/23/92

117

Section Corner for 11, 12, 13 & 14
 Found - 1¼" iron pipe with brass cap, 1990 (in place with Douglas Co. Surveyor's Office brass cap w/iron pipe alongside out of ground)
 42" Fir, (DCSO) N.78°W., 21.78 ft. (now 43" x 3 ft. high stump in place, face closed, bearing tree tag visible).
 48" Fir stump, (DCSO) S.11°W., 42.90 ft. (now 32" x 3 ft. high stub in place, bearing tree tag visible).
 40" Fir stump, (orig.) S.43°E., 36.96 ft. (now 27" x 3 ft. high stump in place, face chopped out, no scribes visible).
 18" Maple, (1990) S.07°E., 36.6 ft. (now 20" dying Maple in place, bearing tree tag visible).
 27" Hemlock snag, (1990) N.06°E., 39.4 ft. (now 24" x 10 ft. high stump in place, face closed, bearing tree tag visible).
 48" Fir (DCSO) N.48°E., 5.94 ft. (now windfall, face buried)
 New Accessories -
 Orange carsonite marker labeled witness post, bears N.55°W., 4.1 ft. to base.
 Orange carsonite marker labeled witness post, bears S.61°W., 4.5 ft. to base.

Lloyd Smith
For: Or. St. Dept. of
Forestry
Dec. 1997
M128 - 17

118

James M McIntosh
For: Oregon Dept.
Of Forestry
March 1999
M 131-44

Corner Secs. 14 & 23, West line, Only
 Found - Oregon St. Board of Forestry 1½" x 36" galv. IP/3" bronze cap, 1970_E Ren #80
 60" Fir (1879) N.30°W., 8 lks., now 60"x2' high rotten stump, some axe work visible.
 24" Fir (1879) S.45°E., 154 lks., now 40"x2' high rotten stump, old axe work visible.
 60" Fir (1879) S.45°W., 6 lks., obliterated by Levi Walker, now 55"x2' high rotten stump
 8" Fir (1970) N.82°E., 11.4 ft., yellow metal location poster, now 17", face closed.
 5" Fir (1970) S.46°E., 68.1 ft., now 15", bark scribes visible.
 Set - Orange Carsonite markers, CBM-25OR WP, bears:
 N.47°E., 3.0 ft to base.
 S.26°E., 2.3 ft. to base.