

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Sections 18 and 17. *-(SEE REN. NO. 71)* 24
 Found - Ponderosa Pine (instead of Fir) 17" diam. N.37°E. 12.5 ft.
 Opened scar & found good scribing "1/4".
 54" Dbl. Sugar Pine (instead of Fir) N.30°W. 15.2 ft.
 Two very plain scars.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 T24S RLW 1/4 S18/S17
 Blaze & Scribe one new tree: 21" D. Fir N.23°E. 24.0 ft. Mkd: 1/4 S17 CS BT.

1/4 Corner to Sections 15 and 22. 25
 Found - Badly rotted Fir Stake lying on ground by Corner, some scribing
 still visible "1/4S". I believe this is Original Stake.
 Fir, now 40", N.52°W., not N.52°E.) 6.6 ft. shows very plain axe scar
 Fir, now 22", S.54°W. 33.7 ft., shows very plain axe scar.
 (Did Not open either tree mentioned above.)
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 T24S RLW 1/4 S15
 S22
 New BT's: 22" D. Fir S.54°W. 33.7 ft. Rescribed: 1/4 S22 CS BT. 91
 7" W. Fir N.5°E. 31.2 ft. Mkd: 1/4 S15 CS BT.

1/4 Corner to Sections 33 and 34. 26
 Found - Faint "X" on Rock Outcrop, 3' x 8' x 10' above ground.
 Did not find "1/4" on W. face.
 D. Fir, now 40", N.28°E. 21.1 ft; slope dist.. Tree shows very
 plain axe scar. Did not open -(level dist. 19.6 ft.)
 No trace found of S. E. Bearing Tree.
 I deepen cross on rock outcrop (cross is on S. edge of Rock about 2 ft.
 East of S.W. Cor. of top of Rock.)
 New BT: 23" Sugar Pine N.30°W. 10.6 ft. Mkd: 1/4 S33 CS BT.

Section Corner to Sections 15 - 16 - 21 - 22. 27
 Found - Rock, 14"x8"x6", with notches as called for, tipped over &
 downhill about 2 feet from corner.
 42" Fir Snag S.62°E. 37.6 ft. (slope dist.) scribing visible on
 old face, not grown over, "T23S RLW S21 BT".
 Hemlock, down & Rotten, but stump part in position, N.22°E. 17.8 ft.
 Fir, uprooted & down, bears S.84°W, approx. 55 ft. (slope dist.)
 (Notes call for tree S.84°W. 41.6 ft.) No scars vis. on this tree.
 60" Fir, uprooted & down, showing very plain axe scar approx.
 S.10°E. 41 or 42 ft. (not called for in notes)
 Set - Brass Cap alongside Rock & Mkd: County Surveyor's Office, 1962 T24S RLW S16 | S15
 S21 | S22
 New BT's: 11" I. Cedar N.18°W. 38.3 ft. Mkd: T24S RLW S16 CS BT.
 48" D. Fir N.84°E. 25.2 ft. Mkd: T24S RLW S15 CS BT.
 34" D. Fir S.52°W. 51.4 ft. Mkd: T24S RLW S21 CS BT.
 7" Chinquapin S.40°E. 14.8 ft. mkd: T24S RLW S22 CS BT.

Sec. Cor. To Secs. 24 & 35, T24-1W. & Secs. 3 & 2, T25-1W. 28
 Found - Fir Snag, now 28", N.71°E. 17.8 ft. (slope dist.) Cut open &
 found good scribing "SRLW".
 Fir, now 45", S.5°W. 20.5 ft., shows very plain axe scar. Didn't open.
 Fir, now 26", S.64°E., not S.69°E., 29.0 ft.; slope dist. shows scar.
 20" Cedar, (not Fir) N.4°W. 27.1 ft., shows faint axe scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 T24S S34 | S35
 T25S S3 | S2 RLW
 New BT's: 20" R. Cedar N.4°W. 26.3 ft. Mkd: T24S RLW S34 CS BT. (Rescribed)
 16" Hemlock N.21°E. 34.0 ft. Mkd: T24S RLW S35 CS BT.
 8" Hemlock S.40°W. 25.1 ft. Mkd: T25S RLW S3 CS BT.

Milo E. Godfrey, Deputy Co. Surveyor
 Vernon Tracy and Mike Stone
 July 31 - August 1962
 C. S. File No. 52/42