

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 S. T. S. R 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Sec. Cor. to Secs. 32 & 33, T24-1W. & Secs. 4 & 5, T25-1W. **29**
 Found - New 4" x 4" Cedar Stake at Corner.
 Fir, now 34", S.10°E. 33.7 ft., shows 2 good axe scars.
 Fir Tree, uprooted & down, S.51½°W. 4.0 ft., opened scar & found good scribing "SR".
 Fir Tree, uprooted & down, N.60°E. 5.3 ft., shows good scar.
 Fir Tree, uprooted & down, N.44°W. 18.5 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T24S S32 | S33 T25S RLW
 Office, 1962 S 5 | S 4
 New BT's: 16" D.Fir S.24°W. 22.9 ft. Mkd: T25SRLW S5 CS BT. *F.O.K. 5/70 V.R.T.*
 11" D.Fir N.20°W. 14.7 ft. Mkd: T24SRLW S32 CS BT.
 8" D.Fir N.45°E. 23.2 ft. Mkd: T24SRLW S33 CS BT.

½ Corner to Sections 27 and 34. **30**
 Found - Rock, as called for in notes, still firmly set, "½" marked on North Face. #156
 15" Fir S.25°E. 9.1 ft. (not 8.6 ft.) shows 2 good axe scars.
 22" Fir N.46°E. 10.0 ft. (not 10.6 ft.) shows 2 good axe scars.
 Set - Brass Cap alongside Orig. Rock & Mkd: County Surv. T24SRLW ½ S27
 Office, 1962 S34
 Rescribed Orig. Trees: 15" D.Fir S.25°E. 9.1 ft. Mkd: ½ S34 CS BT.
 22" D.Fir N.46°E. 10.0 ft. Mkd: ½ S27 CS BT.

½ Corner to Sections 21 and 22. **31**
 Found - Rock Mkd: "½" lying alongside Corner Location.
 9" Hemlock N.5°W. 23.1 ft. Cut open & fd. good scribing "BT".
 Blaze & Rescribe this tree "½ S21 CS BT".
 18" Hemlock N.32°E. 13.9 ft., shows good scar. Did not open.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 T24S RLW ½ S21/S22
 Pile Mound of Rocks around Cap. Place Corner Rock Alongside.
 New BT: 8" R.Cedar N.78°W. 10.3 ft. Mkd: ½ S22 CS BT.
 Corner lies under overhang of Rock Bluff 25 feet high.

½ Corner to Section 33, T24-1W. & Sec. 4, T25-1W. **32**
 Found - 14" Yew tree S.82°E. 17.8 ft. (slope dist.) Both scars previously opened. Good scribing vis. on still solid faces.
 36" W.Fir N.55°W. 11.2 ft., broken off about 25 ft. above ground, nearly dead snag. Both scars previously opened & good scribing "½ SBT" visible on old face.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T24S RLW ½ S33
 Office, 1962 T25S S 4 **59**
 New BT: 8" Hemlock N.12°W. 38.5 ft. Mkd: ½ S33 CS BT.

½ Corner to Sections 10 and 11. **33**
 Found - 12" Hemlock N.43°W. 6.6 ft. Has been opened previously, good scribing "½ S BT" visible.
 8" Dead Hemlock Snag N.75½°E. 2.6 ft., previously opened.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 T24S RLW ½ S10/S11
 New BT: 18" Hemlock S.57°E. 20.0 ft. Mkd: ½ S11 CS BT. (pocket knife scribe)
 Corner lies approx. 400 ft. West of E. Pass Creek Road.

Oct. 22, 1962

Section Corner to Sections 25 - 26 - 35 - 36. **34**
 Found - 9" Fir S.34°W. 37.6 ft., previously opened, good scribing vis.
 12" Fir S.42°E. 16.5 ft., shows good scars. Did not open.
 13" Fir N.18°E. 29.7 ft., shows good scars. Did not open.
 60" Fir N.64°W. 56.8 ft. (26 lks. not 66 lks.) shows very plain axe scar.
 Set - Brass Cap at Cor Mkd: County Surveyor's T24S RLW S26 | S25
 Office, 1962 S35 | S36
 New BT's: 13" W.Pine S.66°W. 17.9 ft. Mkd: T24S RLW S35 CS BT. *F.O.K. 5/70 V.R.T.*
 8" D.Fir N.30°W. 18.7 ft. Mkd: T24S RLW S26 CS BT.
 Corner lies on W. slope, approximately 50 ft. South of top of spur sloping N. W.
 Nov. 5, 1962

Milo E. Godfrey, Deputy Co. Surv.
 Vernon Tracey and Mike Stone
 August & September 1962
 C. S. File No. 52/42