

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Milo E. Goffrey, Deputy County Surveyor  
Vernon Tracy and Mike Stone  
June 4, 1963  
C. S. File No. 52/30

Vernon R. Tracy  
and Crew  
Dec. 1964  
C. S. File No.  
52/42

Bruce A. Shaner  
For- Evans Products Co.  
April - May 1965  
Map File M 29 - 65

Sec. Cor. to Secs. 35 & 36, T24-1W. & Secs. 2 & 1, T25-1W. 35  
Found - 11" Fir S.30°E. (not S.10°E.) 13.2 ft., previously opened,  
good scribing visible "T25S RLW S1".

30" Fir N.14°E. 15.8 ft., shows good scar.  
48" Sugar Pine S.15°W. 13.9 ft., shows good scar.  
15" Fir N.26°W. 20.5 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 #126  
T24S RLW 

S35	S36
S 2	S 1

  
New BT's: 21" D. Fir S.55°W. 11.0 ft. Mkd: T25S RLW S2 CS BT.  
12" I. Cedar N.47°E. 24.1 ft. Mkd: T24S RLW S36 CS BT.

$\frac{1}{4}$  Corner to Sec. 35, T24-1W. & Sec. 2, T25-1W. 36  
Found - At Corner, Rock mkd: "18 on N. face as called for in Gov't notes.

60" Fir N.50°E. 23.1 ft., shows good scar, Did not open.  
24" Fir S.5°E. 7.3 ft., shows good scar, Did not open.

Set - Alongside Rock, Brass Cap Mkd: County Surveyor's Office, 1963 T24S RLW  $\frac{1}{4}$  S35 S 2  
T25S  
New BT's: 9" R. Cedar N.53°W. 10.1 ft. Mkd:  $\frac{1}{4}$  S35 CS BT.  
18" Red Cedar S.77°E. 15.0 ft. Mkd:  $\frac{1}{4}$  S2 CS BT.

$\frac{1}{4}$  Corner to Sections 26 and 35. 37  
Found - Both BT's. & Basalt Stone 6" x 8" x 12", set firmly in the ground marked " $\frac{1}{4}$ ".  
16", now 24" Cedar N.25°E. 17.2 ft., shows very good scars. Didn't open.  
36", now 40" Cedar S.15°W. 16.5 ft., shows faint scar. Didn't open.

Set - *Brass Cap Set See #65*  
New BT's: 6" Hemlock N.72°E. 35.7 ft. Mkd:  $\frac{1}{4}$  S26 CS BT.  
8" Hemlock S.26°W. 81.4 ft. Mkd:  $\frac{1}{4}$  S35 CS BT.

Dec. 8, 1964

Closing Corner common to Sections 19 & 30, T24-1W. 38  
Set - Square Stake, from which a: 52  
30" D. Fir, Orig. BT. with scribes visible, bears N.29°E. 8.0 ft.  
20" D. Fir, Orig. BT., now missing.  
Scribed - 60" D. Fir bears S.10°E. 71.0 ft., I scribed "T24S RLW S30 BT".

Closing Corner common to Sections 18 and 19, T24-1W. 39  
I chisled "X" on Rock Cliff at westerly side of Rock Creek, from which: 54  
12" Cedar, Orig. BT. with old faces, bears N.4°E. 90.4 ft.  
36" D. Fir Snag, Orig. BT. with old face, bears N.88°E. 68.0 ft.

Sec. Cor. common to Sections 13 & 24, only, T24-2W. 40  
Set - Sq. Post from which a: 53  
12" D. Fir Snag, Orig. BT. with bark scribes visible, bears N. 31° W., 6.6 feet.  
24" D. Fir, Orig. BT. with a bark scribe visible, now a blown down tree, bears S. 46° W., 27.0 feet.  
New BT's: 20" D. Fir, I scribed "T24S R2W S24 BT" bears N.88°W. 36.7 ft.  
36" D. Fir, I " " "T24S R2W S18 BT" bears N.7°E. 11.3 ft.  
15" D. Fir, I " " "T24S R2W S13 BT" bears N.15°W. 30.1 ft.

East  $\frac{1}{4}$  Corner of Section 24, T24-2W. 41  
Set - Square Stake from which a:  
20" D. Fir, Orig. BT. with scribes visible, bears S.30°W. 12.5 ft.  
16" Hemlock, Orig. BT. with old face, bears N.20°E. 9.2 ft.  
New BT's: 60" D. Fir, I scribed " $\frac{1}{4}$ S S24 BT" bears S.78°W. 56.0 ft. 55  
28" D. Fir, I scribed " $\frac{1}{4}$ S S24 BT", bears S.50°W. 72.6 ft.  
Note - This corner is approx. 30 ft. W. of L191+65 on proposed BLM access Rd.