

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

42

Section Corner to Sections 24 and 25 only, T24-2W.

Set - Square Post, from which a:

- 60" D.Fir, Orig. BT. with old face, but bark scribes, now missing, I scribe "T24S R2W S25 BT"; S.59°W. 22.0 ft.
- 16" D.Fir, Orig. BT. set by McQuinn in 1883 with bark scribes visible; bears N.21°E. 24.2 ft. (Chapman & Nicklin in 1896 said this tree did not fit . . .)
- 12" Hemlock BT. set by C. & N., now missing.
- 38" D.Fir, I scribed "T24S R2W S24 BT" bears N.8°W. 37.7 ft.

Bruce A. Shaner
For Evans Prod.
May - 1965
Map File M 29-65

43

Section Corner to Sections 2 - 3 - 10 - 11.

Found - 2 Stones with no marks visible.

- Orig. 24", now 39" Cedar N.65°E. 29.0 ft. (slope) mkd: "T2 R1 S2 BT" on partially-healed scar.
- Orig. 24", now 29" Fir S.45°E. 31.7 ft. (slope), shows good scar.
- Orig. 24", now 30" Fir S.72°W. 33.0 ft. (slope), shows good "
- Orig. 30", now 36" Fir N.8½°W. 29.0 ft. (level), very good scar.
- Orig. 24", now 39" Cedar N.65°E. 29.0 ft. (slope) See above)

Set - Brass Cap at Cor. Mkd: County Surveyor's T24S RLW $\frac{S 3}{S 10} | \frac{S 2}{S 11}$
Office, 1965

No new BT's. marked as Originals are all in good condition.
This corner lies on steep west slope approx. 300 ft. E. of Road.

FD. OK-DCSO - Dec. 17, 1966 - CS 64/71-6

44

¼ Corner to Sections 24 and 25.

Found - Orig. 18", now 22" Hemlock S.72°E. 3.3 ft., open & shows "4S" scribe, tree alive.

20" Fir, down & badly rotted, N.40°E. 17.8 ft., fragments of old face visible. #157

Set - Brass Cap at Cor. Mkd: County Surveyor's T24S RLW $\frac{1}{4} \frac{S 24}{S 25}$
Office, 1965

New BT: 10" Hemlock N.22°E. 54.4 ft. Mkd: $\frac{1}{4}$ S24 CS BT.

Note - This corner lies on steep East slope approx. 230 ft. West of Creek.

Vernon "Ray" Tracy
Terry Connell
June 1965
C. S. File No. 52/42

45

¼ Corner to Sec. 24, 1W. & Sec. 19, R.1E.

Found - Orig. 18", now 28" Fir N.30°E. 7.3 ft., down & out of place, We open & find scribe marks.

Orig. 36", now 37" Fir, S.15°W. 10.6 ft., shows good scar, alive & in good condition.

No trace of Rock called for.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T 24 S RLW $\frac{1}{4}$ S 24/S 19 R1E. #128

Cap is set under root was of N. E. BT.

New BT: 22" D.Fir S.78°E. 24.6 ft. Mkd: $\frac{1}{4}$ S19 CS BT.

Note - This corner is on steep south slope approx. 300 ft. from foot of hill.

46

¼ Corner to Sec. 25, RLW. & Sec. 30, R.1E.

Found - Basalt Stone 14 x 12 x 6" Mkd: "¼" on W. Face.

Orig. 10", now 18" Fir S.28½°E. 26.4 ft. (face). We open & find "¼" scribe. Alive.

Orig. 30", now 37" Fir N.49°W. 38.3 ft. (face), shows good scar. Alive.

Set - Brass Cap at Cor. Mkd: Doug. County Surveyor's Office, 1965
T24S RLW $\frac{1}{4}$ S 25/S 30 R1E.

New BT: 9" Yew S.21°E. 19.7 ft. Mkd: $\frac{1}{4}$ S30 DC3BT.

Note - This corner is on the Douglas & Lane County Line. 89