

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

47

Sec. Corner to Secs. 24 & 25, RLW. & Sec. 19 & 30, RLE.
Found - Basalt Stone 12 x 8 x 16" with 4 notches on N. edge & 2 notches on S. edge, firmly set.
Orig. 36", now 42" Fir N.60°E. 38.3 ft.(face) alive, shows good scar.
Orig. 30", now 52" Fir S.58°E. 44.9 ft.(face) alive, shows good scar.
Orig. 12", now 17" Fir N.79°W. 66.0 ft.(face) alive, open & shows "T2S R S24 BT", rotting due to injury.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
Douglas RLW $\frac{S\ 24}{S\ 25}$ | $\frac{S\ 19}{S\ 30}$ RLE
Set Rock alongside.
New BT's: 10" Hemlock N.69°W. 19.9 ft. Mkd: T24S RLW S24 DCS BT"
10" Hemlock S.73°W. 21.5 ft. Mkd: T24S RLW S25 DCS BT
Note - This corner is on Douglas - Lane County Line.

48

Section to Section 26 and 25.
Found - Basalt Stone 8" x 8" x 8", firmly set, and mkd. "1/4" on W. Face.
Orig. 36", now 42" Fir, alive & in good cond. East 5.9 ft., shows good scar, We do not open.
Orig. 12", now 16" Cedar N.30°W. 17.1 ft., open & find "S" scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T24S $\frac{1}{4}$ S 26/S 25 RLW.
New BT's: 5" D. Fir N.77°W. 12.5 ft. Mkd: $\frac{1}{4}$ S26 CS BT.
Note - We set Rock alongside Cap- This corner is on steep East Slope.

49

Section Corner to Secs. 21 - 22 - 27 - 28.
Found - Orig. 18", now 32" Pine N. 18° E. 35.6 ft., Alive & in good condition.
Orig. 6", now 12" Fir S. 43° E. 12.5 ft., " " "
Orig. 16", now 30" Pine S. 29° W. 35.0 ft., " " "
Orig. 24", now 36" Pine N. 53° W. 54.1 ft., " " "
Set - Brass Cap Mkd: County Surveyor's Office, 1966 T24S RLW $\frac{S\ 21}{S\ 28}$ | $\frac{S\ 22}{S\ 27}$
Note - Since all BT's are O.K., We do not mark new ones.
Corner lies on easterly slope of spur ridge, sloping N. approx. 60 ft. off top of ridge.
May 6, 1966

50

Corner to Sections 15 and 16.
Found - 3' x 3' x 2' Boulder at Corner, failed to find marks on E. face.
Orig. 16", now 20" Fir S. 38° E. 21.1 ft. Open & shows "1/4 S BT", now snag.
Orig. 24", now 30" Fir N. 67° W. 5.9 ft., alive, shows good scar, we do not open.
Set - Brass Cap Mkd: County Surveyor's Office, 1966 T24S RLW $\frac{S\ 16}{S\ 15}$ #153
New BT: 1 1/2" D. Fir N. 74° E. 26.0 ft. Mkd: $\frac{1}{4}$ S15 CS BT.
Note - Brass Cap is against East face of boulder set in a mound of stone. Corner lies on steep east slope.
May 12, 1966

51

Corner to Sections 21 and 28.
Found - Orig. 42", now 50" Fir N. 13° E. 42.4 ft., shows good scar, We do not open. Alive.
Orig. 36", now 42" Fir S. 46° W. 17.2 ft., Alive, open & find "1/4 S" scribe & reverse.
Basalt Rock 8"x7"x11" downhill from corner & out of ground, possible chisel marks "1/4".
Set - Brass Cap Mkd: County Surveyor's Office, 1966 T24S $\frac{1}{4}$ S 21 | RLW $\frac{S\ 28}$
New BT's: 6" D. Fir S. 70° E. 7.4 ft. Mkd: $\frac{1}{4}$ S28 CS BT.
7" D. Fir N. 18° E. 7.7 ft. Mkd: $\frac{1}{4}$ S21 CS BT.
Note - Corner lies on steep, southwesterly slope.
May 6, 1966

Vernon "Ray" Tracy
Terry Connell
June 1965
C. S. File No. 52/42

FD-02-T-5120m
11/10 MS+55

RE-RENEWED, SEE CORNER NO. #140

RE-RENEWED, SEE CORNER NO. #153

RE-RENEWED, SEE CORNER NO. #142