# Douglas County Surveyor's Record of Government Corners Renewed

T. 24 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

Cl. Corner to Sections 19 and 30, T24-1W. 52
Found - BT's. as recorded in Ren. #38, as follows: #139
Orig. 30" Fir N. 29° E. 8.0 ft. Alive, face pitched over.
60" Fir S. 10° E. 71.0 ft., scribe visible on pitched face. Alive.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T24S R2W | S 19 / S 30 | R1W CC
Do not mark new BT's. Closing Corner lies approx. 75 ft. East of new Rock Creek Access Road in rock fill.

RE-RENEWED, SEE CORNER NO

— — — — — — —

Witness Corner to Sections 13 and 24, T24-2W. 53
Found - Stumps only of BT's. as recorded in Ren. #40, T24-1W.
Corner falls on rock face of cut bank.
Set-Witness Corner 30 ft. West, as follows:
Brass Cap at Cor. Mkd: County Surveyor's Office, 1966, 30 ft. E. to Cor. T24S Wit.Cor. R2W | S 13 / S 24 | R1W
New BT's: 20" D. Fir N. 30½° W. 30.0 ft. mkd. W.C. T24S R2W S13 CS BT.
14" D. Fir S. 62° W. 87.6 ft. mkd. W.C. T24S R2W S24 CS BT.
Note - This Wit. Corner lies 25 ft. West of top of cut bank of new Rock Creek Access Road.

— — — — — — — —

Cl. Corner to Sections 18 & 19, T24-1W. 54
Found - Orig. 36" Fir N. 88° E. 68.0 ft., shows scar. We do not open. 75
"X" on rock face, as recorded in Ren. #39, now buried.
N. E. BT. gone.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966. T24S R2W | S 18 / S 19 | R1W CC.
New BT: 16" D. Fir S. 30° E. 24.3 ft. mkd. CC T24S R1W S19 CS BT.
No good trees to N.E. except across canyon.

RE-RENEWED SEE CORNER NO

— — — — — — — — —

Wit. Cor. to ¼ Corner Sec. 24 only, T24-2W. 55
Found - Stumps of BT's., as recorded in Ren. #41, T24-1W.
No trace of Orig. BT's.
Corner falls in approx. center of new Rock Creek Access Road.
Set - Wit. Corner 20 ft. West at bottom of verticle Rock cut bank.
Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T24S R2W ¼ S 24/ R1W Wit. Cor.
20' East to Corner.
Chisel - 4" "X" in Rock face, N. 1° W. 12.0 ft.
No trees availabel to West.
Note - This Wit. Cor. lies on west side of Road.

— — — — — — — —

Section Corner to Sections 13 - 14 - 23 - 24. 56
Found - 12"X10"x8" Basalt Stone with 3 notches on S. Side & 1 notch on E.
Orig. 8", now 16" Fir N. 26° E. 17.2 ft. Alive, shows very good scar. #113
Orig. 8", now 17" Fir, S. 48° E. 13.9 ft. Alive, shows very good scar.
Orig. 30", now 33" Fir, S. 53° W. 17.8 ft., now Snag, shows scribe on unhealed blaze.
Orig. 6", now 9" Fir N. 48° W. 21.8 ft. Alive, shows good scar. Do not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 T 24 S R 1 W | S 14 / S 23 | S 13 / S 24
Set - B.C. in mound of Stone 3' wide at base & 2' high & Orig. Stone alongside.
New BT: 8" D. Fir S. 50° W. 11.0 ft. Mkd: T24S R1W S23 CS BT.
Note - This corner lies approx. 300 ft. W. of top of ridge, course N.& S.

RE-RENEWED, SEE CORNER NO

— — — — — — — — 9/20/66

Sec. Corner to Sections 1 - 2 - 11 - 12. 57
Found - 10"x8"x8" Basalt Stone with 5 notches on S. & 1 notch on E.
Orig. 24", now 26" Fir, N.50°E. 48.2 ft. "BT" scribe on badly rotted Stump.
Orig. 30", now 34" Fir, now Snag with healed blazes, S.17°E. 59.4 ft.
Orig. 10", now 20" Fir, S. 31° W. 9.2 ft. Alive, shows good scar. Do not open.
Orig. 36", now 37" Fir N.45°W. 25.7 ft., now Snag with scribe on rotted face.
Set - Brass Cap Mkd: County Surveyor's Office 1966 T 24 S R 1 W | S 2 / S 11 | S 1 / S 12
New BT's: 9" D. Fir N. 44° W. 13.3 ft. Mkd: T24S R1W S 2 CS BT.
8" D. Fir N. 22° E. 18.8 ft. mkd: T24S R1W S 1 CS BT.
9" D. Fir S. 85° E. 18.2 ft. mkd: T24S R1 W S12 CS BT.

— — — — — — — —

Vernon "Ray" Tracy
Joe Brady & Jack Heritage
August, 1966
C. S. File No. 52/42