

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

T.E. Shrum
For. U.S. Ply.
& Champion
Papers
M 37/- 2

= Center $\frac{1}{4}$ Corner to Section 20.
Set - 2 $\frac{1}{2}$ " Aluminum Cap Mkd: " C $\frac{1}{4}$ S20 T24S R1W RE4287" Prop. Cor. 1968.
Marked BT's: Fir 10" N. 57 $\frac{1}{2}$ ° W. mkd: " C $\frac{1}{4}$ S20 B.T. RE4287.
Ced. 5" S. 37 $\frac{1}{2}$ ° E. mkd: " C $\frac{1}{4}$ S20 T24S R1W RE4287.
Sept. 1968

78

Section Corner to Secs. 1 & 12, R1W. and Secs. 6 & 7, R1E.
Found - Orig. Corner Stone 16x10x8" mkd. with 1 notch on N. and
5 notches on south sides, in place.
Orig. 12", now 20" Fir, alive, S.18°E. 23.1 ft., very good scar.
Orig. 36", now 40" Fir, alive, S.59°W. 36.3 ft., very good scar.
Orig. 36", now 40" Fir, alive, N.10°W. 35.6 ft., very good scar.
Orig. B.T. to N. E. gone. Douglas
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 24 S R
(Reset stone alongside) Office 1 S 1 | S 6 1
1969 W S 12 | S 7 E
New BT: 10" D. Fir N.41°E. 36.8 ft. mkd: T24S R1E S 6 DCS BT.
This corner lies 80 ft. N. of small creek, course S.W. Sept. 4, 1969

79

$\frac{1}{4}$ Corner to Sec. 1, R1W. and Sec. 6, R1E.
Found - Basalt Corner Stone, as called for, in place, mkd: " $\frac{1}{4}$ " on W. face.
Orig. 12", now 22" Fir, alive, N.44°E. 49.5 ft., shows good scars.
Orig. 30", now 36" Fir, alive, N.86°W. 48.2 ft., shows good scars.
Set - Brass Cap at Cor. Mkd: Doug. Co. Surveyor's Office, 1969
(Reset stone alongside T.24S R1W $\frac{1}{4}$ S 1 | S 6 R1E.
New BT's: 14" D. Fir N.15°E. 9.4 ft. mkd: " $\frac{1}{4}$ S 6 DCS BT".
12" D. Fir S.45°W. 10.0 ft. mkd: " $\frac{1}{4}$ S 1 DCS BT".
This corner lies on very steep, west slope 75 ft. N. of top of spur.

80

Sec. Cor. to Sections 7 & 18, T24-1W. and Secs. 12 & 13, T24-2W.
Found - Orig. 24", now 30" Fir, dead, N.75°E. 17.2 ft., bark scribe visible.
poor condition.
Orig. 30", now 34" Fir, dead, S.81°E. 19.8 ft., frag. bark scribe vis.
Orig. 32", now 36" Hemlock, alive, S.75°W. 30.4 ft., scribe marks
visible on unhealed blaze. Rescribe (T24SR2W S13 CSBT")
Orig. 20", now 24" Fir snag, N.61°W. 36.3 ft. (Rec. 33.0ft.) bark scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 24 S #154
Office 2 S 12 | S 7 1
1969 W S 13 | S 18 W
New BT's: 16" Hemlock N.46°E. 30.0 ft. mkd: T24S R1W S7 CS BT.
10" Hemlock N. 6°W. 22.3 ft. mkd: T24S R2W S12 CSBT.
22" Hemlock S.43°E. 59.5 ft. mkd: T24S R1W S18 CS BT.
This corner lies on steep northerly slope 90' S. of creek, course E.
9/3/69

81

$\frac{1}{4}$ Corner to Sec. 6, T24-1W. and Sec. 1, T24-2W.
Found - Orig. 24", now 48" Fir, alive, N.25°E. 8.6 ft., "BT" bark
scribe visible on lower blaze, upper blaze mostly gone.
Orig. 20", now 24" W. Fir, alive, N.80°W. 25.1 ft., very faint scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S
Office, 1969 R2W $\frac{1}{4}$ S 1 | S 6 R1W
New BT's: 14" W. Fir S.41°W. 10.0 ft. mkd: " $\frac{1}{4}$ S1 CS BT".
8" W. Fir N.54°E. 28.2 ft. mkd: " $\frac{1}{4}$ S6 CS BT".
This corner lies 60 ft. S. of 2 ft. wide creek, course S.W.

82

Section Corner to Secs. 6 & 7, T24-1W. and Secs. 1 & 12, T24-2W.
Found - Orig. 10", now 30" Fir, alive, N15°E. 54.1 ft., bark scribe, poor.
Orig. 10", now 18" S. Pine, dead, S.42°W. 5.3 ft., dead, scribe visible.
Orig. 6", now 16" S. Pine, alive, N.27°W. 4.0 ft., shows faint scar.
Rescribe: "T24S R2W S 1 CS BT".
No trace of Orig. S.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 24 S R
Office 2 S 1 | S 6 1
1969 W S 12 | S 7 W
New BT's: 9" Sugar Pine N.15°E. 5.0 ft. mkd: T24S R1W S 6 CS BT".
13" D. Fir S.72°E. 26.7 ft. mkd: T24S R1W S 7 CS BT.
13" D. Fir S.70°W. 24.0 ft. mkd: "T24S R2W S12 CS BT".
This corner lies on top of spur, sloping south.

83

C.S. File No. 52/42

C. S. File 54/27

Vernon "Ray" Tracy
Jack Heritage & V. Perron
September, 1969

RE RENEWED, SEE CORNER NO. #154