

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Section 1 and 2.

Found - Orig. 8", now 20" Fir, S. 72° E. 33.7 ft., open & find "S" scribe.
Orig. 18", now 30" Fir, alive, N. 70° W. 42.9 ft., shows good scars, we tag.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 1 W
Office, 1970 1/4 S 2 | S 1

New BT's: 10" D. Fir S. 59° E. 16.2 ft. mkd: "1/4 S 1 CS BT".
22" D. Fir S. 66° W. 8.9 ft. mkd: "1/4 S 2 CS BT".

This corner lies on very steep, north slope 95 ft. N. of ridge top.
We put line tag on Leach Cap Jeep Trail. At a point about 500' W. &
on ridge top, are trees with scribe marks "R27M" & "BT".

4/15/70

95

1/4 Corner to Sections 4 and 5.

Found - Corner Stone, as called for, in place.

Orig. 24", now 32" Fir, alive, N. 86 1/2° E. 79.2 ft., shows good scar, we tag.

Orig. 36", now 40" Fir, alive, N. 15° W. 14.5 ft., shows good scar, we tag.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 1 W
(Reset old stone alongside) Office, 1970 1/4 S 5 | S 4

We do not mark new BT's. as Original BT's. are in good condition and the
only trees available are of the same size.

Corner lies 100 ft. S. of old Bohemia Jeep Trail, not drivable.

4/16/70

96

1/4 Corner to Sections 7 and 8.

Found - Orig. 24", now 30" Fir, alive, S. 52° E. 19.1 ft., shows good scar, we tag.

Orig. 30", now 36" Fir, alive, S. 64° W. 5.3 ft. open & find "BT" scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 1 W
Office, 1970 1/4 S 7 | S 8

New BT: 10" Hemlock N. 22° W. 8.6 ft. mkd: "1/4 S 7 CS BT".

This corner lies about 1/4 mile S. of paved access road that runs along
the Calapooya Divide.

4/20/70

97

1/4 Corner to Sections 25 and 36.

Found - Orig. 48", now 56" Fir, N. 22° E. 18.5 ft., alive, open & scribe vis.

No trace other Orig. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 1 W
Office 1970 1/4 S 25 | S 36

New BT's: 10" Hemlock N. 5° E. 29.7 ft. mkd: "1/4 S 25 CS BT".

12" Cedar S. 21° W. 66.0 ft. mkd: "1/4 S 36 CS BT".

This corner lies on steep westerly slope.

5/7/70

98

1/4 Corner to Sections 6 and 7.

Found - Orig. 6", now 10" Fir, broken off near ground, N. 28° E. 23.8 ft.,
find "1/4 S 6" scribe on log.

Orig. 30", now 36" Hemlock, Alive, S. 43° E. 9.2 ft., blaze open, scribe
visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 1 W
Office, 1970 1/4 S 6 | S 7

New BT's: 14" Fir N. 27 1/2° E. 31.3 ft. mkd: "1/4 S 6 CS BT".

11" Hemlock S. 50° E. 41.8 ft. mkd: "1/4 S 7 CS BT".

This corner lies on steep N.E. slope about 300 ft. N. of top of Calapooya Divide.

5/21/70

99

Section Corner to Sections 23 - 24 - 25 - 26.

Found - Orig. 18", now 24" Fir, Alive, S. 77° E. 36.3 ft., shows good scar, we tag.

Orig. 24", now 30" Fir, Alive, N. 72° W. (Rec. N62W) 25.7 ft., shows good scar, we tag.

Orig. 30", now 32" Fir Snag, S. 45° W. (Rec. S49W) 71.3 ft., open & find scribe.

We do not find Fir BT, as described to N.E. However, 40" Fir Snag
bears N. 10° E. 50.0 ft., shows good axe scar. We open & find "4"
scribe. Looks old enough to be Original.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 1 W
Office 1970 S 23 | S 24
S 26 | S 25

New BT's: 10" D. Fir S. 58° W. 30.4 ft. mkd: "T24S R1W S26 CS BT".

9" S. Pine N. 5° E. 28.0 ft. mkd: "T24S R1W S24 CS BT".

This cor. lies on W. slope 66.0' W. of top of ridge & about 115 ft.
N. of top of same ridge.

5/22/70

100

Vernon "Ray" Tracy
V. Perron
C. S. File No. 54/27