

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gary L. Langlitz, Co. Surveyors Office
Gregory Quibell
Karen Cheney
Oct. 21, 1976
C.S. 59/24

114

Section corner for Secs. 2 and 1; and 35 and 36 of T23-1.
Found - An orig. 15" now 28" Fir, bears N.58°E., 29.1 ft. Down with illegible scribe marks in blaze opened by someone prior to this.
An orig. 14" now 34" Fir, bears S.76°E., 19.8 ft. (rec. S.81°E., 19.8 ft.) Alive with well healed blaze.
An orig. 13" now 22" Fir, bears N.18°W., 17.8 ft. Alive with well healed blaze.

We find no sign of corner post.

Set - A 1" x 30" I.Pipe with brass cap attached flush with ground marked:
Douglas Co. Surveyor
1976

T 23 S		
S 35	S 36	R 1 W
S 2	S 1	
T 24 S		

New BT's - A 7" Fir, bears N.76°E., 14.7 ft. scribed "T23S R1W S36 CS BT" in a double blaze. (Note bearing taken approx. 1.0 ft. south of tree trunk due to shape of tree).

A 13" Fir, bears S.9 1/2°W., 20.1 ft. scribed S 2 T24S R1W CS BT in a double blaze.

Corner lies on NE slope.

10/21/76

115

1/4 Corner for Sec. 1 and Sec. 36 of T23-1.

Found - An orig. 12" now 24" Hemlock, down and rotten with illegible scribe marks visible on a previously opened blaze.

An orig. 30" now 36" Hemlock, alive and in good condition with illegible scribing visible on previously opened blaze.

The original corner post is gone.

At the corner point as determined by the found orig. BT's as follows;

A down 24" Hemlock, bears N.16 3/4°W., 27.7 ft. and a 36" Hemlock bears S.76 1/2°W., 29.0 ft.

We set - A 1" x 30" Iron pipe 26" in the ground on a steep east slope approx. 30 ft. west of a small ravine, with brass cap attached marked:

Douglas Co. Surveyor

1/4	T 23 S	R
	S 36	1
	S 1	W
	T 24 S	
1976		

From which we mark the following:

New BT - A 6" hemlock, bears N.40 1/2°E., 9.9 ft. scribed "1/4 S36 CS BT" on a single blaze.

10/28/76

116

East 1/4 Corner, Section 8.

Set - 3/4" Iron pipe from orig. bearing trees by distance only:

A 20" now 22" W. Pine bears N.46°E (Rec. N.63°E), 11.0 ft. to head of R.R. spike - orig. BT.

A 12" now 22" Fir, S.70°W., (Rec. S.64°W.), 30.6 ft. (Rec. 48') to head of R.R. spike - orig. BT.

117

Section Corner for Secs. 5, 6, 7 and 8.

Found - A 2" I.P. with a 1963 BLM brass cap.

An 18" Fir, N.58°E., 2.6 ft. scribe visible. (Rec. 15", N.50 1/2°E)

An 8" Fir snag, S.10°E., 18.3 ft. scribe visible. (Rec. 9", S.12°E., 29 lks.)

A 10" Fir, S.30°W., 15.6 ft. scribe visible. (Rec. 26 lks.)

A 10" Fir, S.33°W., 17.9 ft. scribe visible. (Rec. 11", S.31°W., 30lks)

An 18" Fir, N.62°W., 12.9 ft. scribe visible. (Rec. 18", N.64°W., 20 lks.)

A 6" Fir snag, N.33°W., 4.5 ft. scribe visible. (Rec. 8", N.40°W., 7 lks.)

DID NOT RENEW.

118

1/4 Corner for Secs. 5 and 8

Found - A 2" I.P. with a 1963 BLM brass cap and a stone mkd. 1/4

A 28" Fir, N.50°E., 29.7 ft. to W. Co. nail, closed face, BLM BT. (Rec. 35", N.49°E., 47 lks.)

A 22" Fir, S.26°W., 11.8 ft. to W. Co. nail, closed face, BLM BT. (Rec. 26", S.25°W., 19 lks.)

A 38" Fir, S.81°W., 104.5 ft. to W. Co. Nail. W.Co. R.P. (not of rec.)

RE-NEWED CORNER NO. #160

not on map

NOTE: SEE C.S. 58/8 FOR TREES OF RECORD

Nick Juliano (Triangel Engineering)
For: Weyerhaeuser Company
Oct. 1976
M 62 - 35

Gary L. Langlitz
A. Vic Cangie
M.L. Tompkins
Oct. 28, 1976
C.S. 59/24