

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 24      T. S.      R 1      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

**124**

CONT. FROM LAST PAGE -

New BT's- 9" Hemlock bears N.5 1/2°W., 42.9 ft. Tree double blazed and scribed "1/4 S19 CS BT".  
A 28" D. Fir bears N.83 1/2°E., 14.4 ft. Tree double blazed and scribed "1/4 S19 CS BT". Marked for high stumping.  
Set R.R. spike in a 59" Fir stump, spike bears S.66 1/2°W., 71.6 ft. Spike marked "B0".

5/5/77

**125**

1/4 Corner for Secs. 34 and 35.

Found - A 36" Fir now 40" bears S.78°E., 9.9 ft. with well healed double blaze.  
A 10" Fir, now 19" bears N.53°W., 23.8 ft. with well healed double blaze. We opened upper blaze and found scribe mark "S"  
Set - 1" x 36" Iron pipe with brass cap 6" above ground marked:  
County Surveyors Office 1977

T 24 S  
Cor  
S 34 S 35  
R 1 W

Note: Corner is at N.E. Cor. of Clearcut unit.

7/25/77

**126**

Section corner for SEcs. 35 and 36; and Secs. 1 and 2 of T25-1

Found - 1963 Doug. Co. Brass cap & iron pipe separated and badly bent, below surface of cat trail properly stamped.  
Orig. Fir 16" now 26" snag bears N.14°E., 15.8 ft. Tree has well healed blaze.  
A 10" Fir now dead bears S.30°E., 13.2 ft. (orig. rec. S.10°E., 1963 renewal Rec. S.30°E.) Tree has partially opened blaze scribed "T25S R1W S1"  
A 48" Pine stump bears S.15°W., 13.9 ft. Tree has well healed blaze  
A 10" now 16" Fir bears N.26°W.- 20.5 ft. Tree has well healed blaze  
A 21" Fir stump bears S.55°W., 11.0 ft. Tree has partially healed blaze scribed "25S R1W S2 CS" visible Ren. #35  
An Incense cedar 12" bears N.47°E., 24.1 ft. Tree has open blaze scribed "T24S R1W S36 CS BT" Ren. #35

Set - 30" x 1" Iron pipe at section corner 22" deep. Attached brass cap is stamped "Douglas County Surveyor" T24S S35 S36 S2 S1 T25S R1W

No trees to scribe in southerly quadrants.

8/11/77

**127**

Section corner for secs. 13, 24, T. 24 S. R. 1 W. and secs. 18, 19, T. 24 S., R. 1 E.

Found - A stone 7" x 12" x 14" lying on surface of ground. Three grooves on one face and three grooves on the opposite face.  
Orig. 22" cedar, now 26" bears N. 74° W., 42.24 ft. (record, N.77° W.,) with healed blaze.  
Orig. 60" D. fir, now 51" bears S. 80° W., 29.7 ft. (Record, S. 74° W.) with healed blaze.  
Orig. 20" Fir, now a broken stob, bears S. 19° 30' E., 29.0 ft. (Record, S. 15° 30' E., 15.84 ft.) True distance is 44 lks. not 24 lks. of record. Scribing visible "T. 24 R1E S19 BT"  
Orig. 60" D. fir. now 43" bears N. 40° E., 4.62 ft. to center of tree. (Record, N. 58° E., 4.62 ft.) with healed blaze.

Set - Brass cap 2 1/2" diam. on 1" iron pipe marked.

COUNTY SURVEYOR OFFICE  
T 24 S  
R S 13 S 18 R  
1 S 24 S 19 1  
W 1977 E

Built a mound of stone around cap, buried orig. stone alongside cap.

NEW BT's - A 30" D. Fir bears S. 47° 30' E., 45.4 ft. scribed T24S R1E S19 CS BT" on a double blaze.  
Placed county BT tags on all five trees.

Larry E. Monrean  
R. B. Kimberling  
P. L. Earle  
Doug. Co. Surveyors  
Office  
May 5, 1977  
C.S. 59/34

R.B. Kimberling  
P. L. Earle  
July 25, 1977  
C.S. 59/38  
Douglas County Surveyors Office

Larry E. Monrean  
Mike Cline  
Aug. 11, 1977  
C.S. 59/38  
Douglas County Surveyors Office

Dennis Gaylord, U. S. F. S.  
Deputy County Surveyor  
Travis Worthen, Witness  
Sept. 9, 1977  
C.S. File 59/40