

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

136

C O N T - - - -

Glen Mc Chesney, For
Weyerhaeuser Co.
March 10, 1978
C.S. 58/8

Accessories added this date:
64" Fir, N.8°W., 61.3 ft.
48" Fir stump, S.48°E., 21.1 ft. Original BT.
Bearings and distances are to "W" nails driven into base of reference trees.
Weyerhaeuser plates on trees.
3/10/78

137

Glen Mc Chesney, For
Weyerhaeuser Co.
Oct. 21, 1977
(Filed 12/80)
C.S. 58/8

Center 1/4 Corner for Sec. 28
Found - 1972 Shrum Alum. cap, in place. Ren. #110
18" Hemlock stump, scribing visible, S.37°E., 17.8 ft. face measurement; 18.4 ft. to center.
26" Fir stump, scribing visible, S.60°W., 1.5 ft. face measurement; 2.6 ft. to center.
9" Hemlock, scribing visible, N.10°W., 38.3 ft. face measurement; 38.7 ft. to center.
Accessories Added:
38" D. Fir stump, S.30°E., 13.6 ft. with "W" nail and plate.
26" D. Fir stump, S.60°W., 1.4 ft. with "W" nail and plate
10/21/77

138

Sec. corner common to Sec's. 19, 20, 29, & 30.
Found - Brass Cap (DCSO) protruding 14" out of ground, & marked County Surveyors Office T24S R1W S19 S20 S30 S29 1966 .
Orig. corner stone (12" x 8" x 8"), marked with 2 notches on the South face & 5 notches on the East face, leaning against the NE side of the Brass Cap.
BT's - 24" Fir (orig. 20") stump, which has been treated & had the bark removed (face no longer recognizable), bears N.73°E., 25.0-ft. (Rec. 25.7-ft.).
18" Fir (orig. 16") stump, which has been treated & had the bark removed (face no longer recognizable), bears S.41°E., 24.9-ft. (Rec. S.45°E., 25.7-ft.).
Note: The orig's. 8" Fir & 20" Cedar, and Ren.#66 's 8" Hemlock have all three been taken out by logging.
Unrecorded 29" Fir stump, treated, bark gone, & scribed: T24S R1W S30 BT , bears S.73°W., 33.8-ft.
Unrecorded 36" Fir stump, treated, bark gone, & scribed: T24S R1W S19 BT , bears N.33°W., 52.7-ft.
- Both unrecorded BT's have 1981 BLM BT Tags -
New BO's - Set Boat Spike, stamped BO 1 , in top of orig. 20" Fir, now 24" stump, bears N.73°E., 25.0-ft.
Set Boat Spike, stamped BO 2 , in top of orig. 16" Fir, now 18" stump, bears S.41°E., 24.9-ft.
Set Boat Spike, stamped BO 3 , in top of 29" Fir stump, bears S.73°W., 33.8-ft.
Set Boat Spike, stamped BO 4 , in top of 36" Fir stump, bears N.33°W., 52.7-ft.
- All stumps have DCSO BT Tags -
8/12/81

139

Closing corner for Sec.'s 19 & 30.
Found - DCSO Brass Cap properly marked, Ren. # 52.
except that "AM" had been added at a later date.
Unrecorded B.L.M. B.C. marked: Department of Interior Bureau of Land Management T24 S19 T24S
R2W S30 CC
S25 R1W
1981
bears N.89°W., 5.8-ft. from the DCSO B.C.
BT's - 34" Fir (Orig.12") with scribing († 19|30 BT) visible bears N.19°E., 8.0-ft. (Rec. N.29°E., 7.92-ft.) from the DCSO B.C.
56" Fir (Orig.60") with healed over blaze bears S10°E., 71.8-ft. from the DCSO B.C. (Ren.#38.)
From the BLM B.C., bears:
The orig. 12" (now 34") Fir (above) bears N.47°E., 11.4-ft.
The 56" (orig. 60") Fir (above) bears S.15°E., 74.1-ft.
Unrecorded 38" Fir recently scribed T24S R1W S19 BT bears N.30°E., 73.6-ft. This tree is blacked from DCSO Cap by the orig. BT.
8/12/81

Gregory E. Quibell
Deputy, Douglas County Surveyor
Debbie Stewart, witness
Aug. 12, 1981
C.S. 61 / 27

2/2/84
See Vol. 45
Pg. 17359
FOR APPROVAL
NOTES. J.R.

Gregory E. Quibell
Deputy, County
Surveyor Office
Debbie Stewart, wit.
August 12, 1981
C.S. 61 / 27