

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

152

Section corner for Secs. 13, 14, 23 and 24.

Found - 1986 DCSO 3" dia. drill cap set in rock, 18" below ground.
Ren. #149

8" now 14" dia. 5 ft. high d. fir stump, with an opened blaze, no scribing seen, bears N.26°E., 17.2 ft. Orig. BT.

8" now 18" dia. 6 ft. high D. fir stump, with fully healed blaze, bears S.48°E., 13.9 ft. Orig. BT.

6" now 10" dia. 6 ft. high D. fir stump with partially healed blaze, no scribing seen bears S.42°W., 11.0 ft. (Rec. S.50°W., 11.0 ft.) Orig. BT.

13" now 16" dia. 4½ ft. high D. fir stump with fully healed double blaze bears N.31°W., 32.4 ft. (Rec. N.29°W., 32.4 ft.) Ren.#113

5/8" I.R. with DCSO alum. cap stamped "3" protrudes 10" above ground bears N.33°E., 557.83 ft. Ren. #149

5/8" I.R. with DCSO alum. cap stamped "4", slash pile interferes with a direct measurement. (Rec. N.49°E., 418.82 ft.) Ren. #149

Orig. 30" now remains of roots at record bearing and distance, (Rec. S.53°W., 17.8 ft.)

5/8" iron rod with alum. cap "1" from Ren. #149 NOT found.

Set - a 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. x 32" long iron pipe is set at a referenced position plumb over 1986 DCSO drill cap. BC/IP protrudes 2" above a 2½ ft. dia. mound of stone and mkd. "Douglas County Surveyors T24S S14|S13 R 1989 Office"

S23	S24	1
-----	-----	---

W

New Accessories:

A boat spike set through a bearing tree tag into a 16" dia. 4 ft. high D. fir stump, Spike is stamped "BO B" bears N.75½°W., 25.8 ft.

A boat spike set through a bearing tree tag into a 15" dia. 2½ ft. high D. fir stump, Spike is stamped "BO A" bears S.17½°W., 27.5'

Corner lies on a steep west slope in a new clear cut approx. 100 ft. west of road.

8/2/89

153

1/4 Corner for Sections 15 and 16

Found - A 3 x 3 x 2 ft. tall boulder, east side spalled. No marks found.

A 3/8 O.D. x 36" iron pipe with a 2½" 1966 County Brass cap marked as in Ren. #50 is found loose from ground and in scattered rock mound on east edge of boulder.

(Two orig. bearing trees found: (meas. to east side of boulder near north end)

A fir, 16" diam. now a 21" DBH 40 ft. tall D. fir snag with a previously opened double blaze with the scribing "1/4S BT" visible bears S.38°E., 20.0 ft. dist. (rec. S.38°E., 21.1 ft. dist.; This is a slope distance).

A fir, 24" diam. now a 30" DBH D. fir with a fully healed double blaze bears N.67°W., 5.4 ft. dist. (Rec. N.67°W., 5.9 ft. dist. this is a slope distance.)

A 14" D. fir now a 14" DBH D. fir bears N. 78½°E., 23.5 ft. dist. (Rec. N.74°E., 26.6 ft. this bearing is to near vertical section of trunk (not root crown) and dist. is a slope dist.)

Set - Point described above near North end of boulder and on most easterly side agrees well with orig. bearings and all slope distances agree to this position. The brass cap monument is positioned directly along the east edge of boulder and partially under overhang of said boulder. The BC position is the same as the above mentioned measurement to position on the boulder. The marks "RESET 1990" are added to the brass cap. A mound of stone approx. 32 x 14 x 17" tall is piled on east edge of BC. Monument is flush with top of stone mound.

New BTs - A 4" DBH hemlock scribed "X BT" on a double blaze bears N.42°E., 27.7 ft. distant.

A 10" DBH limber Pine scribed "1/4 S16 CS BT" on a double blaze bears N.09½°W., 35.5 ft. distant.

Corner lies on steep east slope approx. 200 ft. southwesterly from ridge back trail running north-easterly.

7/22/90

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
August 28, 1989
C.S. 64/3

Douglas County
Surveyors Office
Stephen Flause
Terrie Franssen
July 22, 1990
C.S. 64/10