

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 1 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

157

1/4 Corner for Sections 24 and 25

Found - 2½" dia. DCSO brass cap on a 1½" O.D. iron pipe, protrudes 12" above ground. Note: BC is orientated northwesterly. See ren. #44

Accessories Found -

18" now 24" dia. Hemlock, with a partially healed previously opened blaze, bears S.85°E., 4.0 ft. (rec. S.72°E., 3.3 ft. bearing hits center of trunk, dist. would fit a face measurement) O.B.T.

20" now down and rotted D.Fir root hole near rec bearing and dist. "N.40°E., 17.8 ft." O.B.T.

10" now 12" dia. Hemlock, with a partially healed double blaze, illegible scribing visible, bears N.22°E., 54.4 ft. (agrees with rec.) ren. #44.

New Accessories -

31" dia. Hemlock, double blazed and scribed "¼ S25 CS BT" bears S.85°W., 9.0 ft.

38" dia. D.Fir, double blazed and scribed "¼ S24 CS BT" bears N.16½°W., 54.5 ft.

Note - Corner lies approx. S.60°W., 250 ft. from the intersection of two creeks on an easterly slope.

Douglas County
Surveyor's Office
Randall Smith
Stephen Flause
Oct. 24, 1996
C.S. File 65/9-22

158

Section Corner for Sections 27, 28, 33 and 34

Found - 2½" dia. DCSO brass cap on a 1½" O.D. iron pipe. protrudes 11" above ground. Is surrounded by a 1 ft. mound of stone.

See renewal #13

Accessories Found -

6" now 7" dia. 5 ft. high rotted Chinguapin snag, with a rotted blaze, no scribing visible, bears S.29°E., 5.3 ft. (agrees with ren. #13 rec.) O.B.T.

10" now 22" dia. 70 ft. high dead Pine snag, with an unhealed double blaze, scribing visible "T24S R1W S33 CS BT" bears S.42°W., 17.8 ft (agrees with ren. # 13 rec.) O.B.T.

No other original BT's found.

13" now 12" dia. 4 ft. high rotted D.Fir stump with scribing visible on a partially healed double blaze "R1W" bears S.47½°E., 26.3 ft. (agrees with rec.) ren. #13

SW BT from ren. #13 now gone.

New Accessories -

12" dia. D.Fir, double blazed and scribed "T24S R1W S28 CS BT" bears N.84½°W., 21.7 ft.

5" dia. Hemlock, double blazed and scribed "T24S R1W S33 CS BT" bears S.33°W., 6.4 ft.

6" dia. D.Fir, double blazed and scribed "T24S R1W S27 CS BT" bears N.16°E. 19.6 ft.

3" dia. pistol butt Hemlock, double blazed and scribed "X BT", bearing and distance taken at upper blaze on straight trunk, bears S.73°E., 14.3 ft.

Douglas County
Surveyor's Office
Randall Smith
Stephen Flause
Oct. 29, 1996
C.S. File 65/9-23

159

1/4 Corner for Section 28 and 29

Found - 2½" dia. D.C.S.O. brass cap on a 1½" O.D. iron pipe. protrudes 14" above ground. See renewal #11

Accessories Found -

12" now 20" dia. D.Fir with a fully healed single blaze, bears S.76°W., 22.4 ft. (rec. S.74°W., 22.4 ft.) O.B.T.

36" now 40" dia. 4 ft. high D.Fir stump with a fully healed single blaze, bears S.74°E., 7.9 ft. (agrees with rec.) O.B.T.

New Accessories -

5" dia. Cedar, double blazed and scribed "¼ S29 CS BT" bears N.59½°W., 18.3 ft.

5" dia. Chinguapin, double blazed and scribed "¼ S28 CS BT" bears N.48°E., 8.8 ft.

3" dia. D.Fir, double blazed and scribed "X BT" bears S.74°E., 15.6 ft.

Douglas County
Surveyor's Office
Randall Smith
Oct. 31, 1996
C.S. File 65/9-24