

Douglas County Surveyor's Record of  
Government Corners Renewed

T 24 S T. S. R 1 W R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

Douglas County  
Surveyor's Office  
Randall Smith  
Stephen Flause  
Oct. 30, 1996  
C.S. File 65/9-25

1/4 Corner for Sections 5 and 8

160

Found - 3 1/4" dia. brass cap on a 2 1/2" O.D. iron pipe, protrudes 4" above ground (1963 B.L.M.) See renewal #118

20" x 8" x 8" stone, marked "1/4" is found on top of ground along southeasterly side of BC/IP (orig. stone)

Accessories Found -

20" now 26" dia. 5 1/2 ft. high D.Fir stump with a healed blaze, bears S.26°W., 13.1 ft. (brg. agrees with renewal record. Dist. is to center of root crown, original dist. 12.5 ft. would fit well with a face measurement) O.B.T.

20" now 35" dia. 2 ft. high D.Fir stump with a healed blaze, bears N.50°E., 31.0 ft. (bearing agrees with D.C.S.O. renewal record; distance agrees with orig. record) O.B.T.

42" now 42" dia. 3 ft. high D.Fir stump with Weyerhaeuser Co. "W" nail on east side of trunk, center of stump bears S.80°W., 104.5 ft. (rec. going to nail is S.81°W., 104.5 ft., bearing should be S.79°W., possibly read wrong side of compass, distance is good) 6/76 Weyerhaeuser Co.

42" now 42" dia. D.Fir with Weyerhaeuser Co. "W" nail on south side of trunk, center of tree bears N.21°W., 98.2 ft. (rec. going to nail is N.19°W., 96.4 ft. possibly read wrong side of compass, dist. is good) 6/76 Weyerhaeuser

New Accessories -

10" dia. Chinquapin, double blazed and scribed "1/4 S5 CS BT" bears N.32°E., 6.3 ft.

5" dia. Pine, double blazed and scribed "1/4 S8 CS BT" bears S.58 1/2°W., 37.2 ft. to center of root crown.

9" dia. Hemlock, double blazed and scribed "1/4 S8 CS BT" bears S.13°W., 25.9 ft. to center of straight trunk at upper blaze. Note: Tree is a pistol butt.

Corner for Sections 28, 29, 32 and 33

161

Found - 3" dia. drill cap (D.C.S.O.) set in rock on a cut bank 6" below ground on a road cut bank. See renewal #144

2 1/2" dia. D.C.S.O. brass cap on a 1 1/2" O.D. iron pipe protrudes 6" above ground in Road shoulder. See renewal # 104.

Note: This corner is a bearing object as line was not run between sections in renewal #104) From witness cor (BC/IP) corner (drill cap) bears N.89°E., 60.0 ft. (Agrees with record per renewal #144)

Accessories Found - To witness corner (BC/IP)

10" now 9" dia. 3 ft. high partially buried rotted Pine stump, no scribing visible, bears N.76°W., 14.5 ft. (agrees with renewal #144) Renewal #104

11" now 12" dia. 6 ft. high rotted D.Fir snag with an unhealed single blaze, scribing visible "WC T24S R1W S29 CS BT" bears N.37°E., 30.3 ft. (rec. per ren. #104 N.37°E., 31.4 ft. dist. goes to center of trunk) Ren. #104

Accessories Found - To Section corner (drill cap)

6" now 13" dia. 1 1/2 ft. high rotted Pine stump with scribing visible "T" bears S.28 1/2°E., 16.5 ft. (agrees with rec.) O.B.T.

48" dia. 2 ft. high D.Fir with boatspike in top, boatspike bears S.76°E., 35.4 ft. (agrees with BT tag, rec. per renewal #144 is S.76°E., 34.5 ft.)

All other BT's now gone.

New Accessories - B.T. bearing & distance go from wit. cor. (BC/IP)

8" dia. D.Fir, double blazed and scribed "WC T24S R1W S29 CS BT" bears N.66°W., 7.9 ft.

7" dia. D.Fir, double blazed and scribed "WC T24S R1W S32 CS BT" bears S.55 1/2°W., 12.9 ft.

7" dia. D.Fir, double blazed and scribed "WC T24S R1W S32 CS BT" bears S.32°E., 33.2 ft. (note: tree is a pistol butt, bearing & dist. goes to straight trunk at center of upper blaze)

Douglas County  
Surveyor's Office  
Randall Smith  
Stephen Flause  
Oct. 31, 1996  
C.S. File 65/9-26