

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 21881

Bruce A. Shaner  
For Evans Products Co.  
November 1962  
C. S. File No. 51/245

Sec. Cor. Common to Secs. 23, 24, 13 & 14. 13  
Found Orig. Basalt Stone from which a:  
14" Hemlock, scribes visible, tree now blown down, bears N.E.  
30" D. Fir bears S.22°W. 3.3 ft, with old face.  
16" D.Fir, a snag now, with old face, bears N.55°W. 12.5 ft.  
I restored above corner by setting a 1" x 36" Galv. Iron Pipe, from which:  
26" D.Fir bears N.45°W. 23.2 ft. scribed "S 14 BT".  
38" D.Fir bears N.14°E. 11.4 ft., scribed "S13 BT".  
8" Yew bears S.25°E. 46.6 ft., scribed "S 24 BT".

1/4 Corner common to Sections 23 and 24. 14  
Found - Nothing, so Set a 1" x 36" glv. iron pipe by proportional measurement.  
from which: 12" Hemlock bears S.29°W. 24.4 ft. scribed "S 23 BT".  
38" Sugar Pine " S.56°E. 54.5 ft., scribed "S 24 BT".

Corner Common to Sections 23, 24, 25 and 26. 15  
Found - Orig. 48" D.Fir BT. with scribes visible, from which bearing  
tree, on a bearing of S.29°E., 41.6 ft. I Set a  
1" x 36" galv. iron pipe, from which: 59  
24" D.Fir bears S.58°E. 31.4 ft, scribed "S 25 BT".  
10" D.Fir bears N.47°E. 33.0 ft., scribed "S 24 BT".  
14" D.Fir bears S. 5°W. 37.0 ft. scribed "S 26 BT".

Weyerhaeuser  
Co. - Robert  
Baraa.  
C.S. File  
No. 51/306

Section Corner to Secs. 4 & 5, T24-2W. & Secs. 33 & 32, T23-2W. 16  
Found - GLO Survey Record 1894 - Basalt Stone - 15" x 12" x 5", gone.  
60" Fir N.16 1/2°E. 37 lks., bark scribing visible.  
36" Fir S.31 1/2°E. 89 lks., healed faces not chopped open.  
36" Fir S.52°W. 35 lks., Snag, healed faces not open.  
48" Fir N.19°W. 40 lks., scribing on bark.  
Ref. by Marion Hale (Plates & "W" Nails only) Decl. 20°  
60" Fir N.13°E. 21.5 ft. - 26" Fir S.88°E. 45.4 ft.  
32" Fir S.54°W. 23.16ft. - 36" Fir N.84°W. 39.5 ft.

1/4 Corner to Sections 10 and 15. 17  
Found - 6" x 10" x 12" Basalt Stone, lying on top of ground,  
chisel marks "1/4".  
20" Hemlock, now 18", S. 7°W. 21.8 ft., scribing visible. (Orig. BT.)  
14" Hemlock, now 20", N.12°W. 23.1 ft., scribing visible.  
Reset Stone in the ground - 3" x 3" x 4" Hemlock Post.  
18" Hemlock S. 6°W. 21.3 ft., Orig. BT., Added "W" Nail & Plate.  
68" Fir N.80°E. 43.0 ft., added "W" Nail & Plate.  
FOUND - 1" IRON PIPE -> Cor. O.K. 8-28-70 J.M.P. C.S. 54/27 Oct. 1964 18

1/4 Corner to Sections 5 and 6. 19  
Found - 26" Hemlock, N.12°E. 15.8 ft., chopped out & fd. scribing.  
No trace of 6" Vine Maple N.28°W. 8.6 ft.  
Set - Hemlock Post for Corner, post is against a fir log.  
BT's: - 48" Fir S.56°E. 34.6 ft., "W" Nail & Plate.  
50" Fir S.52°W. 104.4 ft., "W" Nail & Plate.

Weyerhaeuser Co.  
1958-1961-1964  
C. S. File No. 53/110

West 1/4 Corner to Section 7. 20  
Found - 24" Hemlock N.40°E. 19.8 ft., now Windfall.  
No Estimated orig. position of Hemlock windfall & set a point  
on a log for corner from orig. notes.  
No trace of 5" Vine Maple S.45°W. 19.1 ft.  
No corner set, log at place for corner. 40  
BT's: - 14" Hemlock S.61°E. 60.2 ft., "W" Nail & Plate.  
62" Fir N.57°W. 102.9 ft., "W" Nail & Plate.

Section Corner to Section 10 - 11 - 14 - 15 20  
Found - 8" Yew, now 12" N.51°E. 31.7 ft., scribing visible on upper face,  
lower face rotted.  
30" Fir, now 34" Fir Snag S.20°E. 21.8 ft., scribing visible.  
14" Hemlock, now 16" W, S. 7°W. 44.9 ft., scribing visible.

(continued)