

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 2 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Found - 5" Maple, now 6" Vine Maple, N.22°W. 15.2 ft., broken over
at face, axe marks but scribing not visible. 20
62

Set - 3" Sq. Vine Maple Post.

BT's: - 50" Fir Stump N.79°E. 4.7 ft., "W" Nail & Plate.

40" Fir S.86°W. 41.8 ft., "W" Nail & Plate.

34" Fir Snag S.23°E. 21.5 ft. Orig. BT., "W" Nail & Plate.

16" Hemlock S.5°W. 44.8 ft. Orig. BT., "W" Nail & Plate.

Aug. 1958

Section Corner to Sections 15 - 16-21 - 22. 21

Found - 1894 Stone, broken by felled tree top. Found V. Hosford's
hub beside stone.

60" Fir N.14°E. 27.7 ft., 2 large faces not chopped out.

50", now 52" Fir Stump, pitch seam indicated face, S.34°E. 26.4 ft.

40", now 44" Fir S.25°W. 43.6 ft., 2 faces.

36", now 40" Fir N.53°W. 56.8 ft., 2 faces.

Set - Original Stone

BT's. as indicated above all Orig. BT's. & added "W" Nail & Plates.

1/4 Corner to Sections 19 and 20. 22

Found - 3" x 3" Dogwood Post, gone - 2" x 2" Fir Pitch Post set
in 1955 from Orig. BT's., now gone.

No trace 10" Hemlock N.10°E. 8.6 ft.

No trace 6" Vine Maple S.30°W. 5.9 ft.

1955 W.Co. - 46" Fir N.22°E. 22.1 ft., now stump "W" Nail O.K., Plate gone.

BT's: 60" Fir S.79°W. 28.0 ft., now stump "W" Nail & Plate O.K.

50" Fir N.23°W. 32.9 ft., now stump, "W" Nail & Plate O.K.

52" Fir S.12°E. 17.3 ft., now stump "W" O.K., plate replaced.

Set - 5/8" x 32" Monel Pipe, 1 1/2" x 10' Yellow fpipe for marker
driven alongside monel pipe.

1/4 Corner to Sec. 5, T24-2W. & Sec. 32, T23-2W. 23

Found - 30" Fir S.60°E. 17.82 ft., now 33" Fir Stump, chopped out.
(Orig. BT)

No trace of 5" Vine Maple N.47°E. 10.66 ft.

Set - 5/8" x 30" Monel Pipe with 2" x 19.6 ft. Bl.I.Pipe set 17 ft.
N. E., 3 ft. in the ground.

BT's: 42" Fir Stump N.24°E. 28.8 ft., "W" Nail & Plate.

33" Fir Stump S.60°E. 17.8 ft., "W" Nail & Plate (Orig. BT)

Sec. Cor. to Secs. 6 & 5, T24-2W. & Secs. 31 & 32, T23-2W. 24

Found - 15"x12"x5" Basalt Stone, gone. A deep, logging skid road
at point for corner.

1953 survey record: W. Co. Records

36" Fir N.17°W. 19.9 ft., now stump, plate gone, bark gone.
(Orig. bark scribe present)

38" Fir S.77°W. 18.1 ft., now stump, no writing on plate.

32" Fir East 26.9 ft., now stump, plate gone.

30" Fir, now stump, S.45°E. 40.8 ft., no writing on plate

Assessories Added, 1958 - "W" Nails & Plates to all four Fir
Stumps as shown above.

Closing Corner common to Secs. 19 & 30, T24-1W. 25

Set Square Stake, from which a: 35

30" D.Fir, Orig. BT with scribes visible, bears N.29°E. 8.0 ft.

20" D.Fir, Orig. BT., now missing.

Scribed - 60" D.Fir bears S.10°E. 71.0 ft., I scribed "T24SRLW S30 BT".

Closing Corner common to Sections 18 & 19, T24-1W. 26

I chiseled "X" on Rock Cliff at westerly side of Rock Creek, from which:

12" Cedar, Orig. BT. with old faces, bears N.4°E. 90.4 feet.

36" D.Fir Snag, Orig. BT. with old face, Bears N.88°E. 68.0 ft.

Weyerhaeuser Co.
C. S. File No. 53/110
- 1958-1961-1964

Weyerhaeuser Co.
1958 & 1963
C. S. File No. 53/106

BRUCE A. SHAWER
For Evans Products
April-May 1965
Map File M 29 - 65

36