

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 2 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97401

33

Township Corner.

R	3	S 36	S 31	R	2
W	S 1	S 6			

 T24S
T25S

Found - 1943 GLO Brass Cap Mkd.
Orig. 48", now 50" Fir Stump, N. 50 $\frac{1}{2}$ ° W. 42.2 ft., shows frag. scribe on burned face.
We rescribe: T25S R3W S 1 CS BT.
All other BT's. gone or out of place due to logging.
New BT: 54" D. Fir Stump, 8.0 ft. high) N. 37° E. 26.4 ft. mkd. T24S R2W S 31 CS BT.
No other trees available. Corner lies in greasewood thicket 20 ft. East of Cat Road & 20 ft. West of bottom of small draw.

34

Wit. Corner to Sec. Cor. to Sections 13 and 24 only, T24-2W.
Found - Stumps only of BT's. recorded in Ren. #27.
Corner falls on rock face of cut bank.
Set - Wit. Corner 30 ft. west, as follows:
Brass Cap at Cor. Mkd: County Surveyor's T24S Wit. Cor. R2W S 13 RLW Office, 1966 30' E. to Cor. S 24
New BT's: 20" D. Fir N. 30 $\frac{1}{2}$ ° W. 30.0 ft. Mkd. W.C. T24S R2W S13 CS BT.
14" D. Fir S. 62° W. 87.6 ft. mkd. W.C. T24S R2W S24 CS BT.
Note - This witness corner lies 25 ft. west of top of cut bank of new Rock Creek Access Road.

35

Cl. Corner to Sections 19 & 30, T24-1W.
Found - BT's. as recorded in Ren. #25, as follows:
Orig. 30" Fir N. 29° E. 8.0 ft. Alive. face pitched over.
60" D. Fir S. 10° E. 71.0 ft., scribe visible on pitched face. Alive.
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R2W S 19 RLW CC. Office, 1966 S 30
We do not mark new BT's. Closing Corner lies approx. 75 ft. East of new Rock Creek Access Road in rock fill.

36

Cl. Corner to Sections 18 & 19 only, T24-1W.
Found - Orig. 36" Fir N. 88° E. 68.0 ft., shows scar. Do not open. "X" on Rock face, as recorded in Ren. #26, now buried.
N. E. BT. gone.
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R2W S 18 RLW CC. Office, 1966 S 19
New BT: 16" D. Fir S. 30° E. 24.3 ft. mkd. CC T24S RLW S19 CS BT.
Note - No good trees to N. E. except across canyon.

37

Witness Corner to $\frac{1}{4}$ Corner Sec. 24 only, T24-2W.
Found - Stumps of BT's. as recorded in Ren. #28.
No trace Orig. BT's.
Corner falls in approx. center of new Rock Creek Access Road.
Set - Witness Corner 20 ft. W. at bottom of vertical rock cut bank.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T24S R2W $\frac{1}{4}$ S24 RLW Wit. Cor. 20' East to Cor.
Chisel 4" "X" in rock face, N. 1° W. 12.0 ft.
No trees available to west. This Wit. Cor. lies on W. side of road.

38

Section Corner to Sections 25 - 26 - 35 and 36.
Found - 1951 Cadastral Brass Cap, firmly set & properly mkd.
Orig. 28" Fir, alive, N. 60° E. 23.1 ft., shows scar.
Orig. 20" Hemlock, alive, S. 57° E. 35.0 ft., shows scar.
12" Hemlock N. 30 $\frac{1}{2}$ ° E. 25.1 ft., alive, scribe visible on unhealed blaze.
20" Fir S. 79° E. 44.9 ft., alive, blaze pitched over.
New BT's: 7" Hemlock S. 30° W. 45.2 ft. mkd. T24S R2W S35 CS BT.
8" D. Fir N. 60° W. 41.0 ft. mkd. T24S R2W S26 CS BT.
Note - This corner lies on steep west slope 150 ft. East of Rock Creek access road.
July 3, 1967

C.S. File No. 54/27

Vernon "Ray" Tracy
Joe Brady & Jack Heritage
July and August, 1966
C. S. File No. 52/42

RE-RENEWED, SEE CORNER NO. #108