

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 2 W R. W. W. M.

KOKI-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray" Tracy
Jack Heritage & V. Perron
July, 1968
C. S. File No. 54/27

Vernon "Ray" Tracy
Frank Jones & W. Perron
Glenn McChesney
C. S. File No. 54/27

50

$\frac{1}{4}$ Corner to Sections 26 and 25.
Found - $1\frac{1}{2}$ " I. Pipe at corner & BT's. as recorded in Ren. #4.
26", now 28" Fir, alive, S. 59° W. 9.0 ft., shows good scar. Do not open.
26", now 30" Fir, alive, N. 9° E. 34.3 ft., shows good scar. Do not open.
Orig. 7" Fir, down & badly decayed, N. 83° 30' W. 17.2 ft., find axe
marks & fragmentary reverse scribe.
Hole where NE BT. probably stood.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W
(Dep. old pipe alongside) Office, 1968 $\frac{1}{4}$ S 26 | S 25
This corner lies on west side of shallow draw 50 ft. & about 1100 ft. N.
of concrete bridge across Rock Creek. 7/22/68

SEPT '68

51

Section Corner to Sections 3 - 4 - 9 - 10.
Found - Orig. 18", now 20" Fir, alive, N. 27 $\frac{1}{2}$ ° E. 33.0 ft., scribe visible
on nearly healed blaze. Rescribe: "T24SR2WS3 CS BT".
Orig. 30", now 40" Fir, alive, S. 46 $\frac{1}{2}$ ° E. 11.9 ft., shows good scar.
We do not open.
Orig. 30", now 40" Hemlock S. 27° W. 19.5 ft., alive, scribe visible.
Rescribe "T24S R2W S9 CS BT". (Rec. S33W. 18.5')
Orig. 30", now 38" Fir, alive, N. 23° W. 31.7 ft., shows good scar.
We do not open. (All Dist. are from face & on slope)
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W
Office S 4 | S 3
1968 S 9 | S 10
This corner lies on steep N.W. slope, dry ravine course N.W. lies 33.0 ft.
west of corner as recorded in orig. field notes. "W" nails in each BT.
10/25/68

52

$\frac{1}{4}$ Corner to Sections 3 and 4.
Found - Orig. 7" Hemlock, now 7" down Hemlock, S. 50° E. 5.3 ft., fragmentary
scribe marks visible on decaying blaze. This BT. was
described as being a 5 ft. high stub in 1952 by Forest
Appraisal Information.
No trace S. W. Orig. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W
Office, 1968 $\frac{1}{4}$ S 4 | S 3
New BT's: 8" Hemlock N. 69° W. 12.4 ft. mkd: " $\frac{1}{4}$ S4 CS BT".
9" Hemlock N. 20° E. 14.5 ft. mkd: " $\frac{1}{4}$ S3 CS BT".
Weyerhaeuser BT's: 36" D. Fir Stump S. 77° W. 15.7 ft. with "W" Nail & Tag.
24" Cedar N. 52° E. 28.6 ft. with "W" nail & tag &
cruiser's mark.
This corner lies on N - S cutting line, clear cut in Section 4.
10/25/68

53

$\frac{1}{4}$ Corner to Sec. 4, T24-2W. and Sec. 33, T23-2.
Found - 12x10x6" Basalt Stone mkd. " $\frac{1}{4}$ " & unrecorded Monel Pipe, bent over.
Orig. 40", now 50" Fir, turned out & 20' downhill, N. 50° E. 21.1 ft.
we open and scribe visible.
Orig. 40", now 48" Fir, alive, S. 15° E. 17.8 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R2W $\frac{1}{4}$ S 33
Office T 24 S R2W $\frac{1}{4}$ S 4
New BT: 48" D. Fir N. 68° W. 24.5 ft. mkd: " $\frac{1}{4}$ S33 CS BT".
No small trees available.
Reset corner stone & Monel Pipe alongside Brass Cap. Corner lies on
very steep N.W. slope.
7/11/69

54

$\frac{1}{4}$ Corner to Sec. 2, T24-2 and Sec. 35, T23-2.
Found - Orig. 30", now 48" Fir, alive, S. 68° E. 35.0 ft., shows good scar.
Orig. 9", now 14" Fir, alive, N. 69° W. 9.9 ft., Open & find scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T23S $\frac{1}{4}$ S 35
Office, 1969 T24S R2W $\frac{1}{4}$ S 2
New BT's: 20" R. Fir N. 18° W. 24.2 ft. mkd: " $\frac{1}{4}$ S35 CS BT".
10" R. Fir S. 52° E. 36.6 ft. mkd: " $\frac{1}{4}$ S 2 CS BT".
This cor. lies on well blazed E-W line approx. 200 ft. W. of old Rock Creek
Trail, we put line tag on trail.
7/17/69