

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31991

Vernon "Ray" Tracy
Jack Heritage & V. Perron
August, 1969 Sept. 1969
C.S. File No. 54/27

72
 $\frac{1}{4}$ Corner to Sections 5 and 4. (Found Corner)
 Found - $1\frac{1}{2}$ " I. Pipe for $\frac{1}{4}$ corner, 10 ft. high, set from Orig. BT's.
 Orig. 18", now 24" Hemlock Stump, 19.1 ft. N.70°W., scribe marks visible, "W" Nail & Tag.
 Orig. 20" Fir, now 26" Stump, low cut, S.89°E. 25.7 ft., "W" Nail.
 28" D. Fir Stump S.8°W. 12.0 ft. "W" Nail & Tag".
 No new trees available, extremely dense greasewood, willow brush and small fir and hemlock reproduction.

73
 Section Corner to Sections 1 - 2 - 11 - 12.
 Found - Orig. 24", now 30" Fir, alive, N.66°E. 27.7 ft., shows (Rec. N60E) good scar.
 Orig. 16", now 17" Fir, 6 ft. high Stub, S.31°E. 4.6 ft., scribe visible.
 Orig. 6" Pine, down & blaze badly decayed S.45°W. 7.9 ft.
 Orig. 24", now 28" Fir, alive, N.18 $\frac{1}{2}$ °W. 29.7 ft., very good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 24 S R 2 W
 1969 S 2 | S 1
 S 11 | S 12
 New BT's: 26" D. Fir S.1°W. 11.7 ft. mkd: T24S R2W S11 CS BT.
 26" Hemlock S.53°E. 27.2 ft. mkd: T24S R2W S12 CS BT.
 Corner lie on moderate ~~W.E.~~ slope in dense rhododendron brush.
 (VAT 8-70)

74
 Section Corner to Sections 2 - 3 - 10 - 11.
 Found - Orig. 20", now 24" Hemlock, alive, N.9°E. 42.2 ft., scribe visible.
 We Rescribe: "T24S R2W S 2 CS BT".
 Orig. 60", now 62" Fir, alive, S.48°E. 26.4 ft., bark scribe, visible and lower scar.
 Orig. 12", now 20" Hemlock, alive, S.55°W. 9.2 ft., scribe visible on nearly healed blaze. Rescribe: "T24S R2W S10 CS BT".
 Orig. 5", now 8" Yew, alive, N.30°W. 15.8 ft., scribe visible on unhealed blaze. Rescribe: "S 3 CS BT".
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 24 S R 2 W
 1969 S 3 | S 2
 S 10 | S 11
 New BT: 12" Hemlock S.74°E. 54.5 ft. mkd: T24S R2W S11 CS BT.
 Rescribed Orig. BT's. as there are only larger trees close to corner.
 8/28/69

75
 $\frac{1}{4}$ Corner to Sec. 1, T24-2W. and Sec. 6, T24-1W.
 Found - Orig. 24", now 48" Fir, alive, N.25°E. 8.6 ft., "BT" bark scribe visible on lower blaze, upper blaze mostly gone.
 Orig. 20", now 24" W. Fir, alive, N.80°W. 25.1 ft., very faint scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 24 S
 1969 R2W $\frac{1}{4}$ S 1 | S 6 RLW
 New BT's: 14" W. Fir S.41°W. 10.0 ft. mkd: " $\frac{1}{4}$ S1 CS BT".
 8" W. Fir N.54°E. 28.2 ft. mkd: " $\frac{1}{4}$ S6 CS BT".
 This corner lies 60 ft. S. of 2 ft. wide creek, course SW.

76
 Sec. Cor. to Secs. 1 & 12, T24-2W and Secs. 6 & 7, T24-1W.
 Found - Orig. 10", now 30" Fir, alive, N.15°E. 54.1 ft., bark scribe, poor.
 Orig. 10", now 18" S. Pine, dead, S.42°W. 5.3 ft., scribe visible.
 Orig. 6", now 16" S. Pine, alive, N.27°W. 4.0 ft., shows faint scar.
 Rescribe: "T24S R2W S 1 CS BT".
 No trace of Original S.E. BT.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office R T 24 S R
 1969 2 S 1 | S 6 1
 W S 12 | S 7 W
 New BT's: 9" Sugar Pine N.15°E. 5.0 ft. mkd: T24S RLW S 6 CS BT.
 13" D. Fir S.72°E. 26.7 ft. mkd: T24S RLW S 7 CS BT.
 13" D. Fir S.70°W. 24.0 ft. mkd: T24S R2W S12 CS BT.
 This corner lies on top of spur, sloping south.
 9/18/69