

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Witness Corner to West  $\frac{1}{4}$  Corner to Section 18, T24-1W. 77  
Corner Point falls on 30' high road backslope.  
Set - 1" Iron Pipe with 3" Brass Cap, 50 ft. due west of  
True Corner Location, from which:  
An 18" Madrone bears N. 86° W. 37.1 ft. scribed: WC  $\frac{1}{4}$  S13 BT.  
A 30" D. Fir bears N. 55° W. 21.9 ft. scribed: WC  $\frac{1}{4}$  S13 BT.  
Nov. 1969

Dennis O.  
Bryant  
For Win. Ply.  
M 38 - 63

$\frac{1}{4}$  Corner to Sections 12 and 13. 78  
Found - No trace of Corner Stone.  
Orig. 14", now 20" Fir, alive, S. 11° W. 19.1 ft., we open & find scribe.  
Orig. 24", now 28" Fir, alive, N. 75° W. 26.4 ft., shows good scar, we tag.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W  
Office 1970  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{12}{13}$   
New BT's: 10" Cedar N. 63° E. 5.6 ft. mkd: " $\frac{1}{4}$  S12 CS BT".  
14" D. Fir S. 35° E. 31.1 ft. mkd: " $\frac{1}{4}$  S13 CS BT".  
This corner lies on very steep, S.W. slope of mountain about 650 ft.  
west of top.

Vernon  
Tracy  
C.S. File  
No.  
54/27

$\frac{1}{4}$  Corner to Sections 1 and 2. 7/17/70  
79  
Found - Orig. Corner Stone, as called for, in place, & mkd: " $\frac{1}{4}$ " on W. face.  
Orig. 24", now 30" Fir, alive, N. 58° W. 21.8 ft., shows good scars, we tag.  
Orig. 36", now 40" Fir, alive, N. 10° E. 13.9 ft., shows good scars, we tag.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W  
(Reset old stone alongside) Office, 1970  $\frac{1}{4}$  S 2 | S 1  
New BT: 16" Hemlock S. 34° E. 19.8 ft. mkd: " $\frac{1}{4}$  S 1 CS BT".  
This corner lies on moderate southerly slope about 620 ft. N. of a  
fork of Rock Creek, course S.E.

Vernon R. Tracy  
J. Heritage  
C.S. File No. 54/27

$\frac{1}{4}$  Corner to Sections 11 and 12. 7/24/70  
80  
Found - 30", now 39" D. Fir, S. 82° E. 9.9 ft., shows good scar.  
24", now 28" D. Fir, N. 47° W. 17.8 ft., shows good scar.  
18" x 12" x 6" Stone at  $\frac{1}{4}$  corner mkd: " $\frac{1}{4}$ " on west face.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W  
Office, 1970  $\frac{1}{4}$  S 11 | S 12  
All Bearing Trees O. K. and Tagged.

John M. Powell  
Willie Penley

$\frac{1}{4}$  Corner to Sections 1 and 12. 8/25/70  
81  
Found - 20", now 32" Hemlock, N. 20° W. 5.3 ft., shows good scar.  
20", now 30" D. Fir, S. 41° E. 27.1 ft., shows good scar.  
Very good E - W Blazed Line. Old forest appraisal Tag, & cruisers marks.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W  
Office 1970  $\frac{S}{S}$   $\frac{1}{12}$   
Bearing Trees O. K. and Tagged.  
Note - Paced call 9 chs. E. to creek, hits good. Due to call faces  
on trees, bearing & dist. to trees & line, I did not open BT's/  
8/26/70

August, 1970  
C. S. File No. 54/27

$\frac{1}{4}$  Corner to Sections 23 and 26. 82  
Found - 18", now 24" Hemlock, S. 40° W. 14.5 ft., shows good scar.  
6", now 12" Hemlock N. 7 $\frac{1}{2}$ ° E. 10.6 ft., opened for scribe "S4"  
12x8x8 Stone, firmly set, mkd: " $\frac{1}{4}$ " on north face.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 2 W  
Office 1970  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{23}{26}$   
New BT: 12" Hemlock N. 32° W. 24.3 ft. mkd: " $\frac{1}{4}$  S23 CS BT".  
8/26/70