

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 2 R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97001

99

Howard Johnstone
For: Roseburg Lbr.
Feb. 7, 1979
C.S. 58/188

NE Corner of Tract 37
Found - 1963 Cadastral Brass cap on Iron pipe marked T.24S., R.2W
Sec. 33 TR 37 Sec. 34 TR 38 See Pg. #13295
11" Cedar, S.66 1/2° W., 19.8 ft. broken off above visible
scribe.
11" Hemlock, N.19°W., 4.6 ft. down.
Scribed new BT's:
12" Cedar, N.72°W., 27.0 ft. "TR37 S33 BT"
8" Hemlock, S.19°W., 36.2 ft. "TR37 S33 BT".

2/7/79
100

Karen Reed
Doug. Co. Surveyors
Office
S.J. Flause
V.L. Woodral
July 10, 1979
C.S. 60/34

Section corner for Secs. 4 and 3; and Secs. 33, 34 of T.23-2
Found - A 1" x 36" I.P. with a 1969 County brass cap properly marked.
Ren. #57
A 36" Fir, now 52" bears S.27°E., 43.0 ft. (Rec. S.25°E., 46.2 ft.)
Tree has been chopped out visible scribing "T2 S R2W S3 T".
(Orig) A root hole with down Fir bears N.66°W., 36.3 ft. Tree
badly rotted.
(Orig.) An 18" Hemlock, now down bears N.11°E., 5.3 ft.
Left cap in place
New BT - A 21" Hemlock scribed "T24S R2W S4 CS BT" bears S.84°W., 51.5 ft.
Corner located at lower center of large rootwad.

7/10/79

Steven Ness
For: Guistina Bros
Lbr. & Doug. Co.
Lubr.
Witness: David Taylor
Oct. 29, 1980
M 86 - 10
C.S. 58/245

1/4 Corner for Sec. 12 (East) and Section 7 of T.24-1
Found - No evidence found. A thorough search for evidence was made
after the proportional position was determined. No evidence
was found of the two line trees called, nor were any original
blazes found along the line. As mentioned in my survey, topo-
graphic calls were of no help in determining the corner's position.
Set - 5/8" x 30" iron pin with unmarked 2" alum. cap. The pin is set
1/2" into rock. The monument is about 24 ft. above the base of
a rock bluff. The position was determined by proportion.
New BT's- a 40" D. Fir bears N.52 1/2°E., 62.8 ft.
A 4" Yew bears S.41°E., 38.1 ft.
Both BTs marked 1/4 S7 BT.

101

10/29/80

Center 1/4 corner for Section 12.
Set - 5/8" x 30" iron pin with 2" alum. cap set in ground 26", marked
"T24S R2W C 1/4 S12 1980" PLS 811.
New BT's- A 10" W.W. Pine bears N.56°W., 20.5 ft.
A 14" W.W. Pine bears S.2°E., 26.6 ft.
Both trees marked "C 1/4 S12 BT".

102

10/29/80

Glen Mc Chesney
For: Weyerhaeuser
Company
March 10, 1978
(Filed 12/80)
C.S. 58/8

Township Corner for Sec.1; and Sec. 6 of T.24-1; Sec. 31 of T.23-1
and Sec. 36 of T.23-2.
Found - 1964 BLM brass cap not disturbed by adjacent timber felling.
50" Fir stump, S.48°E., 22.0 ft. to face, 24.0 ft. center
measurement; no scribing found.
36" Hemlock, S.38°W., 18.0 ft. to face, 19.3 ft. center
measurement; scribing visible on mostly healed face.
32" White fir snag, N.66°W., 20.8 ft. to face, 21.9 ft. center
measurement; scribing, extremely fine, on round surface of
tree, not on a flat face.
18" White fir, N.34°E., 30.7 ft. center measurement; scribing
visible.

103

Accessories added this date:
64" Fir, N.8°W., 61.3 ft.
48" Fir stump, S.48°E., 21.1 ft. Original BT.
Bearings and distances are to "W" nails driven into base of reference trees.
Weyerhaeuser plates on trees.

3/10/78

North 1/4 Corner Section 16/
Found - Orig. 54" Fir, chopped open lower part of single face & exposed
scribed "T" bears N.40°E., 7.9 ft. face measurement
Orig. 6" Chinquapin, now 8" x 4 ft. Chinquapin stub, remainder of
tree on ground. Tree grew with lean to east. Evidence of old
face, scribing no longer visible, S.30°E., 28.4 ft. face measure.
(Fir BT identified by John Fuchek, Weyerhaeuser, in 1941)

104

Glen Mc Chesney
For: Weyerhaeuser Co.
June 10, 1977
(filed 12/80)
C.S. 58/8