

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

109

Sec. corner to Sec's. 1 & 2, and Sec's. 35 & 36 of T.23-2.

- Found - Brass Cap, firmly set, protruding 11" out of the ground, properly marked. Ren.# 94.
- BT's - 20" decayed stump (orig. 18" Fir) and log bears N.53°E., 13.9-ft. no face or scribing visible.
- 33" stump (orig. 30" Fir) with bark removed & metal cover on top bears S.29°E., 37.6-ft. (Rec. S.49°E.), no scar visible, with bark off.
- 65" stump (orig. 48" Fir), bears S.25°W., 21.1-ft. Stump is cut low. No face or scribing visible.
- 38" blowdown (orig. 30" Fir) with well healed double blaze, bears N.28°W., 19.1-ft. to center of root hole.
- 60" stump (orig. 52" Fir), with scribed "S BT" Ren.# 94. visible, bears N.13°E., 74.4-ft.
- New BO's- Set PK nail in burl on 45" Fir stump (stump has bark off and metal cover on top) which bears S.81°E., 20.0-ft.
- "W" nail 1.0-ft. above ground in 80" Fir stump, bears N.62°E., 31.5-ft.
- "W" nail near ground of orig. 30", now 33" Fir stump, bears S.29°E., 35.6-ft.
- 44" Fir bears N.85°W., 12.9-ft. scribed "T23S R2W S35 CS BT" in a single blaze. Old axe marks fd. above new blaze.
- 9/8/81

Gregory E. Quibell
Deputy Doug. County
Surveyor Office
Debbie Stewart, wit.
Sept. 8, 1981
C.S. 61 / 27

110

1/4 corner for Sec. 1 and Sec.36 of T.23-2.

- Found - Brass Cap buried under several large logs. After removing the logs, I find the B.C. firmly set, protruding 1" above the ground, properly marked. Ren.# 93
- BT's - 13" Hemlock (orig. 12"), alive, bears N.66 1/2 °W., 6.5-ft. (Rec.N.64°W., 6.6-ft.) with scribed "S36 CS BT" visible in unhealed blaze. Ren.# 93
- 12" Hemlock (orig. 10"), alive, bears S.8°W., 16.5-ft. (Rec. S.6°W.) with scribed "S1 CS BT" visible on unhealed blaze.
- "W" nail in base of 38" Fir snag, 17-ft. tall C.S. 58/8. bears S.3°W., 11.6-ft. Also found a ✓ cut deeply in bark.
- 9/9/81

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Debbie Stewart, witness
Sept. 9, 1981
C.S. 61 / 27

111

N.W. corner Tract #39

- Found - 1963 BLM brass cap, properly mkd., firmly set.
- 9" now 14" Pine per resurvey bears N.34°E., 34.5 ft. (Rec. 35.0ft.) with well healed scar.
- Rotted remains of 15" Fir per resurvey bears S.39°E., 40.9 ft.
- 8" now 14" Fir Ren. #44 bears S.63°E., 41.8 ft. with well healed scar.
- New BT's- 6" Fir bears S.54°W., 5.0 ft. scribed "S34 CS BT" in bark.
- 11" Fir bears S.83°W., 24.8 ft. scribed "S34 CS BT" in double blaze
- Note - Corner lies north of rock Rd. approx. 220 ft.
- 10/14/81

Gregory Quibell
Deputy, Douglas
Co. Surveyor
Witness: Teresa
Buley
Oct. 14, 1981
C.S. 61/29

112

1/4 Corner for Sections 26 and 27

- Found - 1970 County brass cap, properly mkd., firmly set.
- 20" now 26" Fir, Ren. #2, bears N.33°E., 46.0 ft. with orig. face still showing but burned over. Fd. visible scribing "1/4 S26 CS BT" from Ren. #86 along side.
- 13" Cedar per Ren. #86 down and at approx. orig. location. Unable to locate root hole or stump. Scribed "1/4 S27 CS BT" visible on tree.
- New BT's -18" Fir bears N.3°E., 30.0 ft. scribed "1/4 S26 CS BT" in double blaze.
- 14" Fir bears N.47°E., 38.7 ft. scribed "1/4 S26 CS BT" in double blaze.
- 10/14/81