

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

113

1/4 Corner for Secs. 14 and 15 and Witness Corner

Found - 1 1/2" x 30" I.P. Ren. #6, lying on top of 58" fir stump mentioned in C.S. 59/30 reference notes. (Now attached to these renewal notes.)

Orig. 36" now 38" hemlock stump with scribed "1/4S" visible on exposed face. (Rec. per ref. notes, S.18°E., 15.2 ft. to face)
12" now 15" hemlock with illegible scribing visible on partially healed face. (Rec. per ref. notes, N.86°E., 53.4 ft.)
PK nail in notch in the side of 34" fir stump. (Rec. per ref. notes S.23°E., 35.6 ft.)

PK nail in top of 58" fir stump. (rec. per ref. notes N.64°W., 37.6 ft.)

PK nail in root of 36" hemlock stump. Due to road const. this tree is no longer visible from corner location.

38" hemlock snag per Ref. notes was destroyed by road const.

Set - Using PK nail in top of 58" fir stump, I RESET 1 1/2" x 30" I.P. 12" below surface of road in road shoulder. I.P. bears S.64°E.; 37.6 ft. from PK nail. I check this position using PK nail in 34" fir stump, Orig. 38" hemlock stump & 12" now 15" hemlock BT. Bearing & dists. match record for all three BTS.

Set - 1" x 30" I.P. with brass cap marked "Douglas Co. Surveyor Wit. Cor. 50' East to 1/4 S15 S14 T24S R2W 1981" 50 ft. west of 1/4 for wit. cor. Brass cap protrudes 10" out of ground.

New BT's to Witness corner:

9" hemlock scribed "X CS BT" in double blaze bears N.9°W., 45.5 ft.

10" Hemlock scribed "CS BT" in double blaze bears N.1°E., 33.3 ft.

PK nail in 58" fir stump (per ref. notes) bears N.44°E., 23.5 ft.

(Sketch in file)

12/8/81

Section corner for Secs. 6 and 7; and Secs. 1 & 12 of T.24-³/₄

114

Found - Original 24" hemlock, now 28" 7 foot high stump with scribed T 24 S, R 3 W, S 12, BT visible in previously opened blaze. 40" fir stump with "W" nail in face per Weyerhauser Company unrecorded renewal. (attached to these notes in C.S. 62/1)

Set - 1" x 30" Iron pipe with brass cap attached at record bearing and distance (N.25°E., 20.5 ft.) from original hemlock BT. Cap marked Douglas Co. Surveyor T24S R3W S1 S12 S6 S7 R2W 1982"

New BTS - 40" fir stump bears N.24°W., 47.6 ft. to "W" nail on face.

6" hemlock scribed "S12 CS BT" in double blaze bears S.2°E., 11.4 ft.

11" hemlock scribed "S6 CS BT" in double blaze bears N.25°E., 47.7 ft.

5" chinquapin scribed "S7 CS BT" in double blaze bears S.74°E., 25.0 ft.

Douglas Co Surveyor Office BT tags on all trees. End of road 711 and line crossing tag bears N.20°E., approx. 600 ft. from corner.

12/16/82

115

Northeast corner, Tract #39 (Sec. 35)

Found - 1963 US GLO 2 1/2" dia. I. P. with brass cap leaning 7" west of plumb position. Cap properly marked.

13" now 14" dia. down and out of ground sugar pine with scribing visible "TR 39 S35 Bt" bears S.85°W., 63.6 ft. to center of root wad. Possible stump hole at record bearing and distance (S.80 1/4°W., 59.4 ft.)

NW BT gone. Stump hole at record bearing and distance. (N.31 1/2°W., 24.4 ft.)

Set - Position of BC/I.P. straightened to plumb. A 2 ft. mound of stone placed along west edge of I.P. (Sketch in file)

The Northwest corner TR 40, an iron pipe and brass cap bears S.21 1/2°W., 64.7'

New BTs - 9" dia. cedar double blazed "S35 CS BT" bears S.38 1/2°E., 35.5 ft.

10" dia. D. fir double blazed "S35 CS BT" bears N.73°W., 56.9 ft.

36" dia. 5 1/2 ft. high D. fir stump with a boat spike stamped "CS BO 1 1986" driven through BT tag in top of stump. Spike bears N.28°E., 34.6 ft.

18" dia. 3 ft. high D. fir stump with a boat spike stamped "CS BO 2 1986" driven through BT tag in top of stump. Boat spike bears S.23°W., 8.3 ft.

Corner lies at SW corner of new clear cut on steep NW slope.

12.9/86

Gregory Quibell,
Deputy, Doug. Co.
Surveyors Office
Debbie Stewart
Dec. 8, 1981
C.S. 61/29

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
Randy Smith; John
Powell
December 16, 1982
C.S. 62/1

Douglas County
Surveyors Office
Randall W. Smith
Stephen J. Flause
Dec. 9, 1986
C.S. 62/38