

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S.; T. S. R. 3 W. R. W. W. M.

Witnesses,
W. S. Crear and
Mr Dimmick Jr.
by A. Boyer dep.
C.S. File 16/30
Feb 12-1942

1/4 sec. cor bet secs 15 & 16
set by prop dists. bet sec. corners 1/2 mi to
the S. and the north. or 1/2 way bet.
set 4x4 post, fir, fr. wh.
40" ced; which in turn is 12" S.E. off 36" ced.
is S.78°W. 22.5 ft. mkd. 1/4 S.16 CS BT
12" ced. N.23°E. 36.8 ft. mkd 1/4 S 15 CS BT

7
CORNER NO. 64

A. R. Evans
/ 1952
Drawer 41
Envelope 100

Renewed Cor. Mid-section 29

Corner set by C. E. Roberts in F. B. 7, Pg. 7, This survey
was made for Tip Hilton, on May 26, 1908.

Fd. O. B. T., an alder.

Set 1 1/2" iron pipe for cor. from which;

a 14" Cedar bears S 65° E, 33.5'

a 14" Cedar bears N 53° E, 28.6'

SEE CORNER NO. #132

8

1/4 corner to secs. 31 and 32. *FND. OK BY D. EDWARDS OCT. 2002*
Found - 1 1/2 inch iron pipe at old board fence. Also found 12 inch Cedar
that shows old blaze S. 68 1/2° E., 6.3 feet. We did not cut out.
Pipe set flush with surface. *REN #3*
Blazed and scribed a 12 inch R. Fir, S. 31 1/2° W., 46.2 feet, mkd. S31 CS BT.

M137-52
9

James W. Byron, Deputy County Surveyor
Ray Irving
John Fee
December 27, 1954
C. S. File No. 46/94

South 1/4 sec. corner to section 31 only.
Found - Brass cap - - All B Ts gone. Checks the position of the N corner
of section 6, T25S, R3W. (Record).
Blazed and scribed:
18 inch R. Fir, S. 41° E., 37.0 feet;
24 inch R. Fir, N. 83° W., 55.5 feet. (Bark Blazed).
FOUND O.K. SEPT. 1966 - V.R.T.

10

1/4 Sec. corner to sec. 31, T24S, R3W and Sec. 36, T24S, R4W.
30 inch Cedar, N. 47° E., alive and good condition.
The S. 17° 45' W., Fir B T destroyed.
Brass Cap in place.
I Blaze and Scribe:
6 inch Cedar, S. 8° E., 25.8 feet mkd. 1/4 S 31 CS BT, 5.5 feet south of
fence corner.

11

1/4 corner to secs. 32 & 33.
Point for corner located by proportional measurement.
Set a 1 inch x 36 inch iron pipe at corner point.
From which:
5 inch Hemlock, N. 59° W., 32 feet scribed R. E. 3937 B. T.
22 inch Fir, S. 16° 30' E., 9.5 feet scribed R. E. 3937 B. T.

12

Clifford W.
Bryden
May 9, 1957
C. S. File No.
42/271.

Renewed Section Corner Common to Sections 28, 29, 32, & 33.
Set Brass Cap marked 29/28 T.24S. R.3W. County Surveyor's
32/33 Office, 1956.
Blazed & Scribed - 18" Cedar S.29 T24S R3W CS BT bears N.40°19'W.41.0 ft.
Rescribed 30" Fir S.32 T24S. R3W. CS BT, bears S.41°30'W. 7.9 ft.
10" W. Fir S33 T24S R3W CS BT, bears S.53°E 26.7 ft.
10" W. Fir S28 T24S R3W CS BT, bears N.38°57'E. 58.41 ft.
Corner set from record distances to original BTs. as found.

13

James W. Byron
For Rsbg. Lumber Co.
Oct. 29, 1956
C. S. File No. 47/132

1/2 Section Corner to Sections 29 & 32.
Reestablished corner by using the distances from point set by C.E.
Roberts as reestablished by A.R. Evans, shown above and distance from
Rock Bluff as called for in Government notes. Original BTs not found.
Set Brass Cap at corner marked 1/4 S 32 T24S R3W County Surveyor's Office,
1956. Blazed & Scribed A 39" Fir Stump 42" High bears S.16°W 47.0 ft.
1/4 S 32 CS BT.

14