

Douglas County Surveyor's Record of
Government Corners Renewed

T 24 S. T. S. R 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

WEYERHAEUSER COMPANY
Marion D. Hale
November 1961
C. S. File No. 51/31

CS53/111

Sec. Cor. to Secs. 5 & 6, T24-3 and Secs. 31 & 32, T23-3W. 23
G.L.O. Resurvey Record - 1950
Found - Brass Cap & following BT's: #83
18" Yew N.38 $\frac{1}{2}$ °E. 49 lks., now dead, scribing visible.
42" Fir S.22°E. 34 lks., faint scribing visible.
14" Yew S.60°W. 10 lks., pushed over slightly
7" Yew N.49 $\frac{3}{4}$ °W. 42 lks., shattered off close to ground by logging.
Referenced by M. Hale (Plates & "W" nails only) Decl.20° Nov. 18, 1958
46" Fir Stp. N.13°E. 52.7 ft.
42" Fir S.19°E. 22.6 ft.
50" Fir S.70°W. 53.8 ft.
44" Fir Stp. N.26°W. 46.1 ft.

RE-RENEWED, SEE CORNER NO. #83

$\frac{1}{4}$ Corner common to Sec. 6, T24-3 and Sec. 31, T23-3W. 24
GLO Resurvey - Record - 1950
Found - Brass Cap & 10" Hemlock S.16 $\frac{1}{2}$ °E. 19 lks.
10" Yew N.64 $\frac{3}{4}$ °W. 14 lks.

Closing Corner to Township 25
T24-4 S1/S6 T24-3
GLO Resurvey Record - 1950.
Brass Cap, found and 9" Fir S.48°E. 65 lks.
7" Cedar S.43 $\frac{1}{2}$ °W. 82 lks.

RE-RENEWED, SEE CORNER NO. 36

Corner to Sections 6 & 7 only T24-3W. 26
Found - G. L. O. Brass Cap dated 1950.
36" Fir N.68°E. 29.7 ft., recent blowdown, scribing visible
on not healed over scar.
36" Fir S.62°45'E. 48.2 ft., recent blowdown, face pitched
over, scribe marks, not readily visible.
New BT's: 19" Red Cedar N.36°E. 20.5 ft. Mkd: T24S R3W S6 CS BT.
Doug. Fir S.45°E. 63.7 ft. Mkd: T24S R3W S7 CS BT.

Closing Corner to Sections 1 and 12, T24-4W. 27
Found - G. L. O. Brass Cap dated 1950.
Found - 28" Fir N.31 $\frac{1}{2}$ °W. 25.1 ft, recent blowdown, Portions of scribe
marks visible in not completely healed scar.
26" Fir S.54°45'W. 32.3 ft., recent blowdown, scar visible
lying face down.
New BT's: 13" D.Fir N.57°W. 10.2 ft. Mkd: T24S R4W S1 CC CS BT.
7" Incense Cedar S.79°W. 28.2 ft. Mkd: CC S12 CS BT.

Cors. O.K. 9-11-67 J.M.P.

Corner to Sections 7 and 18 only, T24-3W. 28
Found - Brass Cap set in 1950.
Dead Cedar Snag, now 24", S.85°E. 61.4 ft., shows good scar.
Fir Stump N.35 $\frac{1}{2}$ °E. 68.6 ft. is almost completely buried in road fill.
Blaze & Scribe New BT's:
14" Red Cedar N.33°E. 103.8 ft. Mkd: T24S R3W S7 CS BT.
6" D.Fir S.39 $\frac{1}{2}$ °E. 69.2 ft. Mkd: T24S R3W S18 CS BT.
Corner is on high mound in center of logging road.

RE-RENEWED, SEE CORNER NO. #116

9-11-67 Cor. Fo. O.K. J.M.P.

Township Corner -

R4W	S36	S31	R3W
S1	S6		

29
T25S
Found - Brass Cap set by Norman Price, 1944, (buried under fill on W.
side of logging road.
18" D.Fir S.58°E. 71.9 ft. Cut open & fd. traces of scribing on
badly rotted face.
Stump of 50" Fir S.69°W. 219.8 ft. (across Calapaha from corner)
No trace remains of N. E. or N. W. BT.
Dig around & straighten up Brass Cap, Drive Cedar Stake alongside.
Blaze & Rescribe: 18" D.Fir S.58°E. 71.9 ft. Mkd: T25S R3W S6 CS BT.
New BT's: 9" D.Fir N.82 $\frac{1}{2}$ °E. 66.1 ft. Mkd: T24S R3W S31 CS BT.
10" D.Fir S.81°W. 34.5 ft. Mkd: T25S R4W S1 CS BT.
18" D.Fir N.4°W. 50.4 ft. Mkd: T24S R4W S36 CS BT.

CORNER O.K.
8-29-67
V.R.T.

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Mike Stone
February and March 1963
C. S. File No. 53/9

CS53/111