

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 24 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

30

West  $\frac{1}{4}$  Corner to Section 18 only.

(on East line Section 13, T24S R4W)

Found - Iron Pipe with G.L.O. Brass Cap set in 1950, in good condition.  
22" Fir S.  $19^{\circ}$ E. 38.3 ft. is alive & in good condition, scar plain.  
Sawed Stump of 22" Fir N.  $43\frac{1}{4}^{\circ}$ E. 76.6 ft., scribe visible.  
New BT: 6" W. Fir N.  $52^{\circ}$ E. 26.9 ft. Mkd:  $\frac{1}{4}$  S18 CS BT.

31

Closing Corner Sections 12 and 13, T24S R4W.

(on West Line of Section 7, T24S R3W) - Coc. O.K. 9/1967 J.M.P.

Found - G.L.O. Brass Cap set in 1950, mkd. as described in Gov't. notes.  
8" Fir S.  $81\frac{1}{2}^{\circ}$ W. 31.0 ft. is broken, down & dead, some scribing  
visible on partly rotted face.

No trace of N.E. bearing tree.

New BT's: 11" Red Cedar N.  $42^{\circ}$ W. 78.7 ft. Mkd: T24S R4W CC S12 CS BT.

9" Red Cedar S.  $46^{\circ}$ W. 14.9 ft. Mkd: T24S R4W CC S13 CS BT.

32

West  $\frac{1}{4}$  Corner to Section 19 only.

On E. Line Section 24, T24-4W.

Found - G. L. O. Brass Cap set in 1950

The 13" Red Cedar S.  $84\frac{1}{2}^{\circ}$ E. 59.4 ft. Alive & in good condition.  
Sawed Stump of 32" Fir N.  $64\frac{1}{2}^{\circ}$ E. 19.8 ft. Face still on stump,  
pitched over.

New BT: 12" Hemlock N.  $77\frac{1}{2}^{\circ}$ E. 55.3 ft. Mkd:  $\frac{1}{4}$  S19 CS BT.

33

East  $\frac{1}{4}$  Corner to Section 12 only, T24-4W.

On West line Sec. 7, T24S R3W.

Found - Brass Cap at Corner set by G.L.O. 1950 survey.

20" Red Cedar S.  $64^{\circ}$ W. 54.1 ft. All scribing ( $\frac{1}{4}$ S12 BT) visible  
in, not yet healed over blaze. Tree alive & in good condtn.

20" Hemlock to the N. W. is uprooted, down & dead.

New BT: 7" Hemlock N.  $44^{\circ}$ W. 45.5 ft. Mkd:  $\frac{1}{4}$  S12 CS BT.

Note - Corner lies on bench near foot of steep S. W. slope.

34

Orig. Closing Corner Sections 12 and 13 only, T24-4W.

(on West line Sec. 7, T24S R3W.) 9-1967; Coc. O.K. J.M.P.

Found - 34" Cedar S.  $73^{\circ}$ W. 21.8 ft. Previously opened, old scribing  
visible on old face. Tree still alive, but top broken out  
approx. 40 ft. above ground, newer scribing vis. "AM BT".

32" Fir N.  $6^{\circ}$ W. 31.0 ft. Has been opened previously but scar  
nearly healed shut, no scribing visible, newer blaze below,  
also healed over.

Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R4W Orig. CC S12  
Office, 1963 S13

Note - From this cor., Brass Cap set by Price for CC S12 bears  
West 41.6 ft. (63 lks. not 62 lks.) S13

DID not mark any new Bearing Trees.

35

S. W. Corner Section 31, T23-3W. SW Cor. S 31

Found - Brass Cap set by Price in mound of rocks.

30" Fir Stump, sawed high, N.  $21^{\circ}$ E. 175.6 ft. All scbng. vis.

82" Fir Stump N.  $63\frac{3}{4}^{\circ}$ E. 169.6 ft., scribing visible "31 BT".

2 Fir Snags mentioned by Price:

22" Fir Stub S.  $57\frac{3}{4}^{\circ}$ W. 24.4 ft., charred face.

50" Fir Snag N.  $30^{\circ}$ W. 59.4 ft. Axe scar on bark, charred.

New BT's: 28" D. Fir S.  $59^{\circ}$ W. 55.1 ft. Mkd: T23S R3W S31 CS BT.

7" Chinq. N.  $54^{\circ}$ E. 35.8 ft. Mkd: T23S R3W S31 CS BT.

No more suitable trees available to N.E.

36

Closing Corner Sec. 1, T24-4W. & Sec. 6, T24-3W. cc  $\frac{S31}{S13}$

Found - Brass Cap set by Price in 1950. (Ben # 25)  $\frac{S13}{S16}$

9" Fir Snag S.  $48^{\circ}$ E. 42.9 ft. All scribing visible on open face.

7" Short Cedar Snag S.  $43\frac{1}{4}^{\circ}$ W. 54.1 ft. All scribing visible.

New BT's: 10" D. Fir S.  $58^{\circ}$ E. 28.2 ft. Mkd: T24S R3W S6 CC CS BT.

13" Red Cedar S.  $54\frac{1}{2}^{\circ}$ W. 47.9 ft. Mkd: T24S R4W S1 CC CS BT.

July 15, 1963

Milo E. Godfrey, Deputy  
V. Tracy & M. Stone  
June 12, 1963  
C.S. File No. 53/9

Milo E. Godfrey and Crew  
June 1963  
C. S. File No. 53/9