

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 24

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

93

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
John Powell;
Randy Smith
December 16, 1982
C.S. 62/1

Section corner for Secs. 1 and 12; and Secs. 6 & 7 of T.24-2
 Found - Original 24" hemlock, now 28" 7 foot high stump with scribed
 T 24 S, R 3 W, S 12, BT visible in previously opened blaze.
 40" fir stump with "W" nail in face per Weyerhaeuser Company
 unrecorded renewal. (attached to these notes in C.S. 62/1)
 Set - 1" x 30" iron pipe with brass cap attached at record bearing and
 distance (N.25°E., 20.5 ft.) from original hemlock BT.
 Cap marked Douglas Co. Surveyor T24S R3W S1 S12 S6 S7 R2W 1982
 New BTs - 40" fir stump bears N.24°W., 47.6 ft. to "W" nail on face.
 6" hemlock scribed "S12 CS BT" in double blaze bears S.2°E., 11.4
 11" hemlock scribed "S6 CS BT" in double blaze bears N.25°E.,
 47.7 ft.
 5" chinquapin scribed "S7 CS BT" in double blaze bears S.74°E.,
 25.0 ft.
 Douglas Co Surveyor Office BT tags on all trees. End of road 711 and line
 crossing tag bears N.20°E., approx. 600 ft. from corner.

12/16/82

94

1/4 Corner for Secs. 10 and 15
 Found - 1 1/4" iron pipe with Douglas Co. Brass cap "1967". Ren. #55
 36" fir stump, N.45°W., 12.7 ft. (ctr. meas.) Orig. BT. No marks.
 33 Fir stump, S.28°W., 15.8 ft. (ctr. meas.) Orig. BT. no marks.
 28" maple, N.85°E., 111.5 ft. (ctr. meas.) Doug. Co. BT. Scribe
 visible.
 New BTs - 14" fir, N.32 1/2°E., 9.4 ft.
 13" fir, S.18°E., 5.6 ft.

95

Section corner for Secs. 10, 11, 14, 15.
 Set - 1 3/4" x 33" iron pipe with brass cap mkd. with standard markings
 and "PLS 1978".
 BT's - 26" fir, N.27°E., 11.3 ft.
 18" hemlock, S.23°E., 45.5 ft.
 23" fir, S.23°W., 43.4 ft.
 58" fir stump, N.20°W., 27.4 ft.
 Note - 2" alum. pipe set by Weyerhaeuser Co. bears S.30°27'17"W.,
 15.50 ft. (CS 54/27)

96

1/4 Corner for sections 11 and 14.
 Set - 1 5/8" x 41" iron pipe with brass cap mkd. with standard markings
 and "PLS 1978".
 BTs - 48" fir stump, N.31°E., 79.9 ft.
 52" fir stump, S.30°W., 43.6 ft. (not scribed).

97

Section corner for Secs. 11, 12, 13, and 14.
 Found - 58" fir stump, N.50°E., 66.5 ft. (dist. to "W" nail).
 11" hemlock stump, S.33°E., 30.7 ft. (dist. to "W" nail.)
 42" fir stub, S.50°1/2°W., 48.2 ft. (dist. to "W" nail.)
 43" fir stump (20' high), N.10°W., 33.2 ft. (dist. to "W" nail.)
 Orig. Sec. 13 BT (bark scribed) uprooted and slid downhill,
 center of roots, S.17°E., 13.9 ft. (Rec. S.17°W.)
 Set - 2" x 36" iron pipe with brass cap mkd. with standard markings
 and "PLS 1978".

98

1/4 Corner for Secs. 14 and 15
 Set - 1 3/4" x 36" iron pipe with brass cap mkd with standar markings
 and "PLS 1978".
 New BTs - 50" fir stump, N.24°E., 27.7 ft.
 25" cedar, N.42°W., 45.9 ft.
 Note - 1/2" monel pipe set by Weyer. Co. bears S.42°12'56"W., 13.66 ft. Ren. #43

99

Section corner for Secs. 15, 16, 21, 22.
 Found - 1950 US GLO iron pipe with brass cap. Ren. #54
 12" maple, N.10°W., 12.8 ft. (dist. to "W" nail.)
 8" maple, N.80 1/2°W., 21.9 ft. (dist. to "W: nail.)
 New BTs 10" fir, S.74°E., 78.5 ft.
 9" fir, S.43°W., 22.8 ft.

Daniel Baker, Peel Baker Land Surveying
 For: Weyerhaeuser Company
 December 8, 1983
 M 90 - 48