

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 24

T. S.

R 3

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

108

Sec. cor. cont. 22, 22, 27 and 28)

Set - 60" fir stump, S.53°W., 53.3 ft. (dist. to "W" nail.)
31" cedar, N.67°W., 56.2 ft. (dist. to "W" nail.)
14" fir, N.72°E., 39.0 ft.

109

1/4 Corner for Secs. 22 and 27.

Set - 1 5/8" x 40" iron pipe with brass cap with standard markings
and "PLS 1978".
New BTs - 7" fir, N.88°E., 6.9 ft.
7" fir, S.47°E., 14.7 ft.

110

1/4 Corner for Secs. 23 and 26.

Set - 1 5/8" x 40" iron pipe with brass cap with standard markings
and "PLS 1978"
New BTs - 11" fir, N.5°W., 13.4 ft.
9" fir, S.84°W., 15.6 ft.

111

Section corner for secs. 23, 24, 25 and 26.

Found - 48" fir stump, N.42°E., 27.4 ft. (dist. to RR spike.)
28" hemlock stump, S.52°E., 25.3 ft. (some scribing visible.)
(dist. to "W" nail.)
42" fir stump, S.47°W., 29.5 ft. (dist. to "W" nail.)
34" fir stump, N.51°W., 29.4 ft. (Doug. Co. BT - scribe visible
dist. to "W" nail. Ren. #71)
42" fir stump, S.50°E., 42.7 ft. (Doug. Co. BT scribe visible
dist. to "W" nail.)
Set - 2" x 36" iron pipe with brass cap with standard markings and
"PLS 1978".
(Set iron pipe from 3 original BTs - slope distance and face
measurement.)

Note - No trace of Douglas Co. corner monument. Ren. #71

12/8/83

112

West 1/4 Corner for Section 18 only.

Found - 1950 GLO brass cap on a 1" I.P. extends 14" above ground.
28" rotted fir stump bears N.43 1/4°E., 76.30 ft. (Rec. 76.6)
scribing visible (1950)
34" fir bears S.19°E., 38.28 ft. closed face.
New BT - 17" W. fir bears N.52°E., 26.9 ft. scribed 1/4 S18 BT. This
tree had a 1963 BLM tag (BT) on it, but no face. Ren. #30
Located along N/S wire fence.

113

Section corner for Secs. 7, 8, 17 and 18

Found - U.S. GLO 1950 brass cap on a 2" I.P. extends 14" above ground.
19" Fir "BT" bears S.02°W., 26.57 ft. closed face. (1950) Rec.
27.72 ft.
Root Hole bears S.87 1/2°E., 6.6 ft. "BT" down and uprooted. (1950)
36" Fir stump "BT" bears N.85 1/2°W., 35.64 ft. No scribing
visible (1950)
Root hole bears N.26°E., 9.9 ft. (1950)
New BTs- 22" Cedar bears N.65°W., 19.9 ft. and scribed "T24S R3W S7 BT".
22" Cedar bears S.75°E., 38.25 ft. and scribed "T24S R3W S17 BT".
4" Fir bears N.51°E., 29.26 ft. scribed "X BT".

114

East 1/4 Corner for Section 18.

Found - 1950 GLO brass cap on a 1" I.P. extends 7" above ground. properly
marked.
32" Fir bears S.49 1/4°E., 21.78 ft. closed face. (1950)
26" Fir stump bears N.80 1/2°W., (Rec. N.83 1/4°W.) 44.63 ft.
(Rec. 44.22 ft.) scribing visible. (1950)
New BT - 5" Fir bears S.55 1/2°W., 8.17 ft. scribed 1/4 S18 BT.

Daniel Baker, Peel Baker Land Surveying
For: Weyerhaeuser Company
December 8, 1983
M 90 - 48

Ronald Geisler
Champion
International
October 9, 1985
C.S. 63/22