

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 24 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91891

122

Corner for Sections 26, 27, 34 & 35.

Found - 1½" Iron Pipe. See renewal # 92.
 56" D.Fir stump N.37°38'E., 18.5 ft. to center no 'W' nail.
 Weyco. T tag on stump. (N.46°E., 15.8')
 38" D.Fir snag 15' tall S.63°30'W., 31.4 ft. to center 29.87 ft.
 to 'W' nail. (S.66°W., 30.3 ft.)
 57" D.Fir stump N.32°36'W., 39.5 ft. to center, 37.23 ft. to 'W'
 nail (N.27°W., 37.4 ft.)

Set - Cemented a 2½" Brass Cap to top of found 1½" Iron Pipe marked:

T24S R3W	
S27	S26
S34	S35

1993 RLS 811

BTs Marked -

9" D.Fir, N.41°20'E., 29.3 ft. to center, could not measure to 'W'
 nail. Scribed "T24S R3W S26 BT"
 15" D.Fir, S.30°27'E., 29.4 ft. to center, 28.54 ft. to 'W' nail.
 Scribed "T24S R3W S35 BT"
 10" D.Fir S.34°52'W., 20.4 ft. to center, 19.89 ft. to 'W' nail.
 Scribed "T24S R3W S34 BT"
 14" D.Fir N.26°42'W., 14.7 ft. to center, 14.14 ft. to 'W' nail.
 Scribed "T24S R3W S27 BT"

South 1/4 Corner Section 26.

Found - No trace of 1883 GLO monument or accessories.

Set - 2" X 38" iron pipe with 2½" Brass cap cemented to top at
 proportioned point marked:

T24S R3W	
1	S 26
4	S 35

1993 RLS 811

BTs Marked -

14" D.Fir, N.24°06'E., 44.9 ft. to center, 44.19 ft. to 'W' nail.
 Scribed "¼ S26 BT"
 13" D.Fir, S.50°21'E., 23.2 ft. to center, 22.70 ft. to 'W' nail.
 Scribed "¼ S35 BT"
 14" D.Fir, S.33°09'W., 13.2 ft. to center, 12.47 ft. to 'W' nail.
 Scribed "¼ S35 BT"
 11" D.Fir, N.36°52'W., 48.9 ft. to center, 48.57 ft. to 'W' nail.
 Scribed "¼ S26 BT"

123

Corner for Sections 25, 26, 36 & 35.

Found - 1½" Iron Pipe.
 30" D.Fir stump, N.58°55'E., 19.5 ft. to center, 18.02 ft. to 'W'
 nail, (N.60°E., 18.3 ft.)
 38" D.Fir stump, S.28°10'E., 8.3 ft. to center, no measure to 'W'
 nail, (S34°E., 6.5 ft.)
 48" D.Fir stump, S.52°10'W., 61.6 ft. to center, 60.68 ft. to 'W'
 nail, (no record of this stump on Weyco report)
 42" D.Fir stump, N.44°15'W., 9.1 ft. to center, 7.42 ft. to 'W'
 nail, (N.46°W., 7.2 ft.)

Set - Cemented a 2½" Brass Cap to top of found 1½" iron pipe marked:

T24S R3W	
S26	S25
S35	S36

1993 RLS 811

BTs Marked -

15" D.Fir, N.36°17'E., 27.1 ft. to center, 26.27 ft. to 'W' nail.
 Scribed "T24S R3W S25 BT"
 14" D.Fir, S.48°26'E., 28.3 ft. to center, 27.36 ft. to 'W' nail.
 Scribed "T24S R3W S36 BT"
 16" D.Fir, S.49°45'W., 23.9 ft. to center, 23.13 ft. to 'W' nail.
 Scribed "T24S R3W S35 BT"
 16" D.Fir, N.26°14'W., 40.2 ft. to center, 39.29 ft. to 'W' nail.
 Scribed "T24S R3W S26 BT"

124

Steven P. Ness
 For: Weyerhaeuser Co.
 July 1993
 M 117 - 35