

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 24 S.      T. S.      R. 3 W.      R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91881

FO. OK BY R. WARD 12/2001 M139-34

SECTION CORNER 29, 30, 31, 32

**130**

Mon. Fd.- Douglas county brass cap dated 1956  
 Bt's Fd.- 24" cedar, S.3°W. 13.2' - rec. S.6°W. 13.3' - 1956 Do. Co.  
 16" cedar, S.84°W. 35.8' - rec. S.84°W. 35.3' - 1956 Do. Co.  
 18" hemlock, S.84°E. 29.3' - rec. S.79°E. 29.3' - Do. Co.  
 18" fir snag, N.28°E. 31.3' - rec. unknown  
 Hemlock snag, N.75°W. 32.4' - rec. unknown  
 New Bt's- 8" Hemlock, N.7°W. 22.3' - scribed "T24S R3W S30 BT"  
 6' Fencepost 1' north.

FO. OK BY R. WARD 12/2001 - M139-34

1/4 CORNER 29, 30

**131**

Mon. Set- 1 1/4" X36" Iron pipe with brass cap dated 1994  
 New Bt's- 13" fir, S.4°E. 28.9', scribed "1/4 S29 BT"  
 12" fir, S.76°W. 14.6', scribed "1/4 S30 BT"  
 9" fir, N.78°E. 2.8', scribed "1/4 S29 BT"  
 16" fir, N.26°W. 8', scribed "1/4 S30 BT"  
 6' Fencepost 1' north.

Daniel Baker  
 Weyerhaeuser Co  
 12/15/94  
 M 121 - 58 A&B

CENTER 1/4 CORNER 29

**132**

Mon. Set- 1 1/4" X36" Iron pipe with brass cap dated 1994  
 Bt's Set- 28" cedar, N.42°E. 25' scribed "C 1/4 S29 BT"  
 11" maple, S.30°E. 14.4' scribed "C 1/4 S29 BT"  
 20" cedar, S.8°W. 24' scribed "C 1/4 S29 BT"  
 8" maple, N.50°W. 5.8' scribed "C 1/4 S29 BT"  
 6' Fencepost 1' north.  
 Note: 1 1/2" Iron pipe set by A.R. Evans in CSF# 41/100 as per C.E. Roberts  
 Survey, F.B.#7, pg.7.  
 Noted in CSF#41/293 & CSF# M1-18 as midpoint of North-South  
 centerline bears S.17°50'43"W. 146.23'.  
 27" cedar, S.62°E. 32.3' - rec. S.65°E. 33.5' - Evans 1952  
 31" cedar, N.52°E. 28' - rec. N.53°E. 28.6' - Evans 1952.

Daniel Baker  
 Oct. 18, 1995  
 C.S. File 65/1-4

1/4 Corner for Sections 25 & 36

**133**

Found - 5/8" Monel pipe      See Renewal # 21  
 40" Fir stump, S.29°E., 28.7 ft. to "W" nail.  
 rec: S.32°E., 28.7 ft. to "W" nail.  
 43" Fir stump, N.30°E., 42.2 ft. to "W" nail. (same as record)  
 16" Fir stump, N.32°E., 16.3 ft. to "W" nail.  
 rec: Weyerhaeuser Co. 1956, N.40°E., 13.6 ft. to "W" nail.

Monument Set -

Replaced pipe with 2"x32" iron pipe with brass cap marked:

T 24 S      R 3 W

1/4 S 25  
 S 36

PLS 1978 1995

New Accessories -

16" Fir, N.37°W., 4.9 ft. to "W" nail.  
 11" Fir, S.46°W., 6.3 ft. to "W" nail.  
 15" Fir, S.71°E., 12.2 ft. to "W" nail.  
 15" Fir, N.37°E., 25.5 ft. to "W" nail.  
 Metal fence post bears 1 ft. West.

Rob Ward  
 Ward NW Inc.  
 12/2001  
 For: Seneca  
 Jones CO.  
 M139-34

1/4 Cor. Secs. 19 & 30

**134**

Found - 2 1/2" GLO brass cap dated 1950 with the following  
 accessories:  
 60" D.Fir stump (not of rec.) bears N.22°E., 11.0  
 ft. to a 60D nail in top of stump.  
 30" I.Cedar stump bears S.1°45'E., 38 lks., rotten  
 face.  
 New BT - 10" R.Cedar bears N.26°W., 25.7 ft. scribed "1/4 S19  
 BT"  
 18" Hemlock bears N.81°W., 17.1 ft. scribed "1/4 S30  
 BT"