

Douglas County Surveyor's Record of
Government Corners Renewed

Trp. 24 S. T. S. R. 4 N. R. W. W. M.

May 4th. 1914.
F. J. Cole D. C. S.
Wit:
Verner Abeene
O. J. Hunt.
Filed: FB 39, p. 34.
Vol. 2, p. 256

N. W. COR. OF SEC. 1.
Renew corner from remains of orig. B. T's.
Set a post from which
Original B. T. an Oak 12" dia. brs. S. 37° E. 181 lks.
New B. T. W. Oak 6" Dia. brs. S. 42° W. 33 lks.
New B. T. W. Oak 9" Dia. brs. N. 54° W. 28 lks.
New B. T. 9" W. Oak, brs. N. 30° E. 96 lks.
SEC. COR. N. SIDE OF SEC. 2.
Old Trees not in evidence. Set a post from which:
A Cedar 14" in Dia., brs. S. 68 1/2° W. 57 lks.
A Fir 18" Dia., brs. N. 58° W. 67 lks.

THESE CORNERS ARE IN SEC 1 AND 2, R4W.

Feburary 1917.
F. C. Frear Dep. Co. Surveyor
WIT:
Alve Manning.
Harrison Manning.

COR. BET. SECS. 32 & 5 ON TP. LINE TWP. 24 & 25 S. R. 4 W.
Renew from old B. Ts. Set in 10" x 10" x 24" Sand
stone, from which:
A 18" W. Oak brs. N. 3° 00' E. 1.27 chs.

SEC. COR. COMMON TO SECS. 31, 32, 5 & 6. NOT BY M.C. # 157
Renew Cor. by proportional disto. Set in a 10" x
10" Sand Stone, buried.
Witnessed by sound.

SEC. BET SECS. 29 & 32 Tp. 24 -4
Renew per. old B. Ts. Set in a 8" x 10" x 24"
Sand Stone from which:
A. B. Oak brs. W. 16 1/2° E. 30 lks.
A. W. Oak brs. S. 28 1/2° E. 90 lks.
A Fir 10" Dia. brs. N. 65 1/2° E. 5 lks.

COR. BET. SECS. 31 & 32.
Renew from old B. T. Set in a 10" x 10" x 18"
Sand Stone from which:
A. W. Oak brs. S. 25 1/2° W. 3.28 chains.
A W. Oak brs. N. 84° E. 9.74 chains.

SEC. COR. FOR SECS. 29, 30, 31 & 32.
Renew from old B. Ts. Set in 8" x 10" x 24"
Sand Stone from which:
A 14" Fir, brs. S. 65 1/2° E. 10 1/2 lks.
A 12" Fir, brs. S. 27 1/2° W. 24 lks.

CORNER BET. SECS. 29 & 30.
Set post for corner from an old fir Bearing Tree,
other tree gone. Marked New Trees as follows:
Fir 15" dia. N. 73° E. 116 lks.
Fir 15" dia. N. 74° W. 107 lks.

N. W. COR. OF JOHNATHAN M. COZAD D. L. C. No. 37.
From the original B. Ts. as follows a stump 30" in
Dia. bears S. 60° E. 124 lks. scribe marks Plain.
Other tree down badly rotted did not find scribe marks
N. 60° E. 7.5 lks.
Set a 1" x 28" Round Iron Bar for corner
from which:
W. Oak 16" Dia, Brs. N. 70° E. 33.8 feet.
W. Oak 16" Dia., Brs. S. 4° E. 9.4 feet

COR. BET. SECS. 25 & 36 (F. B. No. 7 Page 14)
Reset post Made new B. T.
Fir 48" Dia. N. 67° E. 22 lks.

SEARCHED FOR - NOT FOUND
4/10/63 L.L.

Jan 9th. 1928
F. C. Frear Co. Surveyor
WIT:
W. S. Crear.
Aug. 1931
F. C. Frear Co. Rdmr.
WIT:
L. D. Pinkston.
B. A. Lene
N. E. Richardson
Milton Palm.
May 1903.
C. E. Roberts
Co. Sur.

F.B. 43 P. 52
F.B. 43 P. 53
F.B. 43 P. 54

RE-RENEWED, SEE CORNER NO. 122

RE-RENEWED, SEE CORNER NO. 157

RE-RENEWED, SEE CORNER NO. 121

RE-RENEWED, SEE CORNER NO. 120

RE-RENEWED, SEE CORNER NO. 119

RE-RENEWED, SEE CORNER NO. 43

RE-RENEWED, SEE CORNER NO. 77

1
2
3
4
5
6
7
8